
faker-file Documentation

Release 0.11.5

Artur Barseghyan <artur.barseghyan@gmail.com>

Feb 28, 2023

CONTENTS

1	Prerequisites	3
2	Documentation	5
3	Online demos	7
4	Installation	9
4.1	Latest stable version from PyPI	9
4.2	Or development version from GitHub	10
5	Features	11
5.1	Supported file types	11
5.2	Additional providers	12
5.3	Supported file storages	12
6	Usage examples	13
6.1	With Faker	13
6.2	With factory_boy	13
6.2.1	upload/models.py	13
6.2.2	upload/factories.py	14
7	File storages	15
7.1	Usage example with storages	15
7.1.1	FileSystemStorage example	15
7.1.2	PathyFileSystemStorage example	16
7.1.3	AWSS3Storage example	16
8	Testing	17
9	Writing documentation	19
10	License	21
11	Support	23
12	Author	25
13	Project documentation	27
13.1	Quick start	28
13.1.1	Installation	28
13.1.2	Usage	28
13.1.2.1	With Faker	28

13.1.2.2	With <code>factory_boy</code>	30
13.1.2.2.1	upload/models.py	31
13.1.2.2.2	upload/factories.py	32
13.1.2.2.3	Usage example	34
13.2	Recipes	34
13.2.1	When using with <code>Faker</code>	34
13.2.1.1	Imports and initializations	34
13.2.1.2	Create a TXT file with static content	35
13.2.1.3	Create a DOCX file with dynamically generated content	35
13.2.1.4	Create a ZIP file consisting of TXT files with static content	35
13.2.1.5	Create a ZIP file consisting of 3 DOCX files with dynamically generated content	35
13.2.1.6	Create a ZIP file of 9 DOCX files with content generated from template	36
13.2.1.7	Create a nested ZIP file	36
13.2.1.8	Create a ZIP file with variety of different file types within	37
13.2.1.9	Create a EML file consisting of TXT files with static content	38
13.2.1.10	Create a EML file consisting of 3 DOCX files with dynamically generated content	38
13.2.1.11	Create a nested EML file	39
13.2.1.12	Create an EML file with variety of different file types within	39
13.2.1.13	Create a TXT file with static content	40
13.2.1.14	Create a DOCX file with dynamically generated content	40
13.2.1.15	Create a PDF file with predefined template containing dynamic fixtures	41
13.2.1.16	Create a MP3 file	41
13.2.1.17	Create a MP3 file by explicitly specifying MP3 generator class	41
13.2.1.17.1	Google Text-to-Speech	41
13.2.1.17.2	Microsoft Edge Text-to-Speech	42
13.2.1.18	Create a MP3 file with custom MP3 generator	43
13.2.1.19	Pick a random file from a directory given	44
13.2.1.20	Generate a file of a certain size	44
13.2.1.20.1	BIN	44
13.2.1.20.2	TXT	44
13.2.1.21	Generate a lot of files using multiprocessing	45
13.2.1.21.1	Generate 100 DOCX files	45
13.2.1.21.2	Randomize the file format	45
13.2.1.22	Generating files from existing documents using NLP augmentation	46
13.2.1.23	Using <code>raw=True</code> features in tests	48
13.2.2	When using with Django (and <code>factory_boy</code>)	49
13.2.2.1	Basic example	49
13.2.2.1.1	Imaginary Django model	49
13.2.2.1.2	Correspondent <code>factory_boy</code> factory	49
13.2.2.2	Randomize provider choice	51
13.2.2.3	Use a different locale	52
13.2.2.4	Other Django usage examples	53
13.3	Security Policy	54
13.3.1	Reporting a Vulnerability	54
13.3.2	Supported Versions	54
13.4	Contributor Covenant Code of Conduct	55
13.4.1	Our Pledge	55
13.4.2	Our Standards	55
13.4.3	Enforcement Responsibilities	55
13.4.4	Scope	56
13.4.5	Enforcement	56
13.4.6	Enforcement Guidelines	56
13.4.6.1	1. Correction	56
13.4.6.2	2. Warning	56

	13.4.6.3	3. Temporary Ban	56
	13.4.6.4	4. Permanent Ban	57
	13.4.7	Attribution	57
13.5		Contributor guidelines	57
	13.5.1	Developer prerequisites	57
	13.5.1.1	pre-commit	57
	13.5.2	Code standards	57
	13.5.3	Requirements	58
	13.5.4	Virtual environment	58
	13.5.5	Documentation	58
	13.5.6	Testing	58
	13.5.7	Pull requests	58
	13.5.8	Questions	59
	13.5.9	Issues	59
13.6		Release history and notes	59
	13.6.1	0.11.5	59
	13.6.2	0.11.4	59
	13.6.3	0.11.3	60
	13.6.4	0.11.2	60
	13.6.5	0.11.1	60
	13.6.6	0.11	60
	13.6.7	0.10.12	60
	13.6.8	0.10.11	61
	13.6.9	0.10.10	61
	13.6.10	0.10.9	61
	13.6.11	0.10.8	61
	13.6.12	0.10.7	61
	13.6.13	0.10.6	62
	13.6.14	0.10.5	62
	13.6.15	0.10.4	62
	13.6.16	0.10.3	62
	13.6.17	0.10.2	62
	13.6.18	0.10.1	63
	13.6.19	0.10	63
	13.6.20	0.9.3	63
	13.6.21	0.9.2	63
	13.6.22	0.9.1	63
	13.6.23	0.9	63
	13.6.24	0.8	64
	13.6.25	0.7	64
	13.6.26	0.6	64
	13.6.27	0.5	64
	13.6.28	0.4	65
	13.6.29	0.3	65
	13.6.30	0.2	65
	13.6.31	0.1	65
13.7		Package	67
	13.7.1	faker_file package	67
	13.7.1.1	Subpackages	67
	13.7.1.1.1	faker_file.providers package	67
	13.7.1.1.1.1	Subpackages	67
	13.7.1.1.1.2	faker_file.providers.augment_file_from_dir package	67
	13.7.1.1.1.3	Subpackages	67
	13.7.1.1.1.4	faker_file.providers.augment_file_from_dir.augmenters package	67

13.7.1.1.1.5	Submodules	67
13.7.1.1.1.6	faker_file.providers.augment_file_from_dir.augmenters.base module	67
13.7.1.1.1.7	faker_file.providers.augment_file_from_dir.augmenters.nlpaug_augmenter module	67
13.7.1.1.1.8	Module contents	67
13.7.1.1.1.9	faker_file.providers.augment_file_from_dir.extractors package . .	67
13.7.1.1.1.10	Submodules	67
13.7.1.1.1.11	faker_file.providers.augment_file_from_dir.extractors.base module	67
13.7.1.1.1.12	faker_file.providers.augment_file_from_dir.extractors.tika_extractor module	67
13.7.1.1.1.13	Module contents	67
13.7.1.1.1.14	Module contents	67
13.7.1.1.1.15	faker_file.providers.helpers package	67
13.7.1.1.1.16	Submodules	67
13.7.1.1.1.17	faker_file.providers.helpers.inner module	67
13.7.1.1.1.18	Module contents	76
13.7.1.1.1.19	faker_file.providers.mixins package	76
13.7.1.1.1.20	Submodules	76
13.7.1.1.1.21	faker_file.providers.mixins.image_mixin module	76
13.7.1.1.1.22	faker_file.providers.mixins.tablular_data_mixin module	76
13.7.1.1.1.23	Module contents	77
13.7.1.1.1.24	faker_file.providers.mp3_file package	77
13.7.1.1.1.25	Subpackages	77
13.7.1.1.1.26	faker_file.providers.mp3_file.generators package	77
13.7.1.1.1.27	Submodules	77
13.7.1.1.1.28	faker_file.providers.mp3_file.generators.base module	77
13.7.1.1.1.29	faker_file.providers.mp3_file.generators.edge_tts_generator module	77
13.7.1.1.1.30	faker_file.providers.mp3_file.generators.gtts_generator module . .	78
13.7.1.1.1.31	Module contents	78
13.7.1.1.1.32	Module contents	78
13.7.1.1.1.33	Submodules	80
13.7.1.1.1.34	faker_file.providers.bin_file module	80
13.7.1.1.1.35	faker_file.providers.csv_file module	81
13.7.1.1.1.36	faker_file.providers.docx_file module	82
13.7.1.1.1.37	faker_file.providers.eml_file module	83
13.7.1.1.1.38	faker_file.providers.epub_file module	85
13.7.1.1.1.39	faker_file.providers.ico_file module	86
13.7.1.1.1.40	faker_file.providers.jpeg_file module	87
13.7.1.1.1.41	faker_file.providers.odp_file module	88
13.7.1.1.1.42	faker_file.providers.ods_file module	89
13.7.1.1.1.43	faker_file.providers.odt_file module	90
13.7.1.1.1.44	faker_file.providers.pdf_file module	91
13.7.1.1.1.45	faker_file.providers.png_file module	92
13.7.1.1.1.46	faker_file.providers.pptx_file module	93
13.7.1.1.1.47	faker_file.providers.random_file_from_dir module	94
13.7.1.1.1.48	faker_file.providers.rtf_file module	95
13.7.1.1.1.49	faker_file.providers.svg_file module	96
13.7.1.1.1.50	faker_file.providers.tar_file module	97
13.7.1.1.1.51	faker_file.providers.txt_file module	98
13.7.1.1.1.52	faker_file.providers.webp_file module	99
13.7.1.1.1.53	faker_file.providers.xlsx_file module	100
13.7.1.1.1.54	faker_file.providers.zip_file module	102
13.7.1.1.1.55	Module contents	103
13.7.1.1.2	faker_file.storages package	103

13.7.1.1.2.1	Submodules	103
13.7.1.1.2.2	faker_file.storages.aws_s3 module	103
13.7.1.1.2.3	faker_file.storages.azure_cloud_storage module	103
13.7.1.1.2.4	faker_file.storages.base module	104
13.7.1.1.2.5	faker_file.storages.cloud module	104
13.7.1.1.2.6	faker_file.storages.filesystem module	105
13.7.1.1.2.7	faker_file.storages.google_cloud_storage module	106
13.7.1.1.2.8	Module contents	107
13.7.1.1.3	faker_file.tests package	107
13.7.1.1.3.1	Submodules	107
13.7.1.1.3.2	faker_file.tests.test_augment_file_from_dir_provider module	107
13.7.1.1.3.3	faker_file.tests.test_django_integration module	107
13.7.1.1.3.4	faker_file.tests.test_providers module	107
13.7.1.1.3.5	faker_file.tests.test_sqlalchemy_integration module	108
13.7.1.1.3.6	faker_file.tests.test_storages module	108
13.7.1.1.3.7	faker_file.tests.texts module	108
13.7.1.1.3.8	Module contents	108
13.7.1.2	Submodules	108
13.7.1.3	faker_file.base module	108
13.7.1.4	faker_file.constants module	109
13.7.1.5	faker_file.helpers module	109
13.7.1.6	Module contents	109
13.8	Indices and tables	109
Python Module Index		111
Index		113

Create files with fake data. In many formats. With no efforts.

PREREQUISITES

All of core dependencies of this package are *MIT* licensed. Most of optional dependencies of this package are *MIT* licensed, while a few are *BSD*-, *Apache 2*- or *GPLv3* licensed. All licenses are mentioned below between the brackets.

- Core package requires Python 3.7, 3.8, 3.9, 3.10 or 3.11.
- [Faker](#) (*MIT*) is the only required dependency.
- [Django](#) (*BSD*) integration with [factory_boy](#) (*MIT*) has been tested with Django 2.2, 3.0, 3.1, 3.2, 4.0 and 4.1.
- DOCX file support requires [python-docx](#) (*MIT*).
- EPUB file support requires [xml2epub](#) (*MIT*) and [Jinja2](#) (*BSD*).
- ICO, JPEG, PNG, SVG and WEBP files support requires [imgkit](#) (*MIT*) and [wkhtmltopdf](#) (*LGPLv3*).
- MP3 file support requires [gTTS](#) (*MIT*) or [edge-tts](#) (*GPLv3*).
- PDF file support requires [pdftkit](#) (*MIT*) and [wkhtmltopdf](#) (*LGPLv3*).
- PPTX file support requires [python-pptx](#) (*MIT*).
- ODP file support requires [odfpy](#) (*Apache 2*).
- ODS file support requires [tablib](#) (*MIT*) and [odfpy](#) (*Apache 2*).
- ODT file support requires [odfpy](#) (*Apache 2*).
- XLSX file support requires [tablib](#) (*MIT*) and [openpyxl](#) (*MIT*).
- `PathyFileSystemStorage` storage support requires [pathy](#) (*Apache 2*).
- `AWSS3Storage` storage support requires [pathy](#) (*Apache 2*) and [boto3](#) (*Apache 2*).
- `AzureCloudStorage` storage support requires [pathy](#) (*Apache 2*) and [azure-storage-blob](#) (*MIT*).
- `GoogleCloudStorage` storage support requires [pathy](#) (*Apache 2*) and [google-cloud-storage](#) (*Apache 2*).
- `AugmentFileFromDirProvider` provider requires [nlpaug](#) (*MIT*), [PyTorch](#) (*BSD*), [transformers](#) (*Apache 2*), [numpy](#) (*BSD*), [pandas](#) (*BSD*), [tika](#) (*Apache 2*) and [Apache Tika](#) (*Apache 2*).

DOCUMENTATION

- Documentation is available on [Read the Docs](#).
- For bootstrapping check the [Quick start](#).
- For various ready to use code examples see the [Recipes](#).
- For guidelines on contributing check the [Contributor guidelines](#).

ONLINE DEMOS

Check the demo(s):

- [REST API demo](#)

INSTALLATION

4.1 Latest stable version from PyPI

With all dependencies

```
pip install faker-file[all]
```

Only core

```
pip install faker-file
```

With most common dependencies

Everything, except ML libraries which are required for data augmentation only

```
pip install faker-file[common]
```

With DOCX support

```
pip install faker-file[docx]
```

With EPUB support

```
pip install faker-file[epub]
```

With images support

```
pip install faker-file[images]
```

With MP3 support

```
pip install faker-file[mp3]
```

With XLSX support

```
pip install faker-file[xlsx]
```

With ODS support

```
pip install faker-file[ods]
```

With ODT support

```
pip install faker-file[odt]
```

With data augmentation support

```
pip install faker-file[data-augmentation]
```

4.2 Or development version from GitHub

```
pip install https://github.com/barseghyanartur/faker-file/archive/main.tar.gz
```

FEATURES

5.1 Supported file types

- BIN
- CSV
- DOCX
- EML
- EPUB
- ICO
- JPEG
- MP3
- ODS
- ODT
- ODP
- PDF
- PNG
- RTF
- PPTX
- SVG
- TAR
- TXT
- WEBP
- XLSX
- ZIP

5.2 Additional providers

- `AugmentFileFromDirProvider`: Make an augmented copy of randomly picked file from given directory. The following types are supported : DOCX, EML, EPUB, ODT, PDF, RTF and TXT.
- `RandomFileFromDirProvider`: Pick a random file from given directory.

5.3 Supported file storages

- Native file system storage
- AWS S3 storage
- Azure Cloud Storage
- Google Cloud Storage

USAGE EXAMPLES

6.1 With Faker

One way

```
from faker import Faker
from faker_file.providers.txt_file import TxtFileProvider

FAKER = Faker()

file = TxtFileProvider(FAKER).txt_file()
```

If you just need bytes back (instead of creating the file), provide the `raw=True` argument (works with all provider classes and inner functions):

```
raw = TxtFileProvider(FAKER).txt_file(raw=True)
```

Or another

```
from faker import Faker
from faker_file.providers.txt_file import TxtFileProvider

FAKER = Faker()
FAKER.add_provider(TxtFileProvider)

file = FAKER.txt_file()
```

If you just need bytes back:

```
raw = FAKER.txt_file(raw=True)
```

6.2 With factory_boy

6.2.1 upload/models.py

```
from django.db import models

class Upload(models.Model):
```

(continues on next page)

(continued from previous page)

```
# ...  
file = models.FileField()
```

6.2.2 upload/factories.py

Note, that when using `faker-file` with Django and native file system storages, you need to pass your `MEDIA_ROOT` setting as `root_path` value to the chosen file storage as show below.

```
import factory  
from django.conf import settings  
from factory import Faker  
from factory.django import DjangoModelFactory  
from faker_file.providers.docx_file import DocxFileProvider  
from faker_file.storages.filesystem import FileSystemStorage  
  
from upload.models import Upload  
  
FS_STORAGE = FileSystemStorage(  
    root_path=settings.MEDIA_ROOT,  
    rel_path="tmp"  
)  
factory.Faker.add_provider(DocxFileProvider)  
  
class UploadFactory(DjangoModelFactory):  
  
    # ...  
    file = Faker("docx_file", storage=FS_STORAGE)  
  
    class Meta:  
        model = Upload
```

FILE STORAGES

All file operations are delegated to a separate abstraction layer of storages.

The following storages are implemented:

- `FileSystemStorage`: Does not have additional requirements.
- `PathyFileSystemStorage`: Requires `pathy`.
- `AzureCloudStorage`: Requires `pathy` and *Azure* related dependencies.
- `GoogleCloudStorage`: Requires `pathy` and *Google Cloud* related dependencies.
- `AWSS3Storage`: Requires `pathy` and *AWS S3* related dependencies.

7.1 Usage example with storages

7.1.1 *FileSystemStorage* example

Native file system storage. Does not have dependencies.

```
import tempfile
from faker import Faker
from faker_file.providers.txt_file import TxtFileProvider
from faker_file.storages.filesystem import FileSystemStorage

FS_STORAGE = FileSystemStorage(
    root_path=tempfile.gettempdir(), # Use settings.MEDIA_ROOT for Django
    rel_path="tmp",
)

FAKER = Faker()

file = TxtFileProvider(FAKER).txt_file(storage=FS_STORAGE)

FS_STORAGE.exists(file)
```

7.1.2 PathyFileSystemStorage example

Native file system storage. Requires pathy.

```
import tempfile
from pathy import use_fs
from faker import Faker
from faker_file.providers.txt_file import TxtFileProvider
from faker_file.storages.cloud import PathyFileSystemStorage

use_fs(tempfile.gettempdir())
PATHY_FS_STORAGE = PathyFileSystemStorage(
    bucket_name="bucket_name",
    root_path="tmp",
    rel_path="sub-tmp",
)

FAKER = Faker()

file = TxtFileProvider(FAKER).txt_file(storage=PATHY_FS_STORAGE)

PATHY_FS_STORAGE.exists(file)
```

7.1.3 AWSS3Storage example

AWS S3 storage. Requires pathy and boto3.

```
from faker import Faker
from faker_file.providers.txt_file import TxtFileProvider
from faker_file.storages.aws_s3 import AWSS3Storage

S3_STORAGE = AWSS3Storage(
    bucket_name="bucket_name",
    root_path="tmp", # Optional
    rel_path="sub-tmp", # Optional
    # Credentials are optional too. If your AWS credentials are properly
    # set in the ~/.aws/credentials, you don't need to send them
    # explicitly.
    credentials={
        "key_id": "YOUR KEY ID",
        "key_secret": "YOUR KEY SECRET"
    },
)

FAKER = Faker()

file = TxtFileProvider(FAKER).txt_file(storage=S3_STORAGE)

S3_STORAGE.exists(file)
```


TESTING

Simply type:

```
pytest -vrx
```

Or use tox:

```
tox
```

Or use tox to check specific env:

```
tox -e py310-django41
```


WRITING DOCUMENTATION

Keep the following hierarchy.

```
====  
title  
====  
  
header  
=====  
  
sub-header  
-----  
  
sub-sub-header  
~~~~~  
  
sub-sub-sub-header  
^^^^^^  
  
sub-sub-sub-sub-header  
+++++++  
  
sub-sub-sub-sub-sub-header  
*****
```


LICENSE

MIT

SUPPORT

For security issues contact me at the e-mail given in the *Author* section.

For overall issues, go to [GitHub](#).

CHAPTER
TWELVE

AUTHOR

Artur Barseghyan <artur.barseghyan@gmail.com>

PROJECT DOCUMENTATION

Contents:

Table of Contents

- *faker-file*
 - *Prerequisites*
 - *Documentation*
 - *Online demos*
 - *Installation*
 - * *Latest stable version from PyPI*
 - * *Or development version from GitHub*
 - *Features*
 - * *Supported file types*
 - * *Additional providers*
 - * *Supported file storages*
 - *Usage examples*
 - * *With Faker*
 - * *With factory_boy*
 - *upload/models.py*
 - *upload/factories.py*
 - *File storages*
 - * *Usage example with storages*
 - *FileSystemStorage example*
 - *PathyFileSystemStorage example*
 - *AWSS3Storage example*
 - *Testing*
 - *Writing documentation*
 - *License*

- *Support*
- *Author*
- *Project documentation*

13.1 Quick start

13.1.1 Installation

```
pip install faker-file[all]
```

13.1.2 Usage

13.1.2.1 With Faker

Imports and initialization

```
from faker import Faker
from faker_file.providers.augment_file_from_dir import AugmentFileFromDirProvider
from faker_file.providers.bin_file import BinFileProvider
from faker_file.providers.csv_file import CsvFileProvider
from faker_file.providers.docx_file import DocxFileProvider
from faker_file.providers.eml_file import EmlFileProvider
from faker_file.providers.epub_file import EpubFileProvider
from faker_file.providers.ico_file import IcoFileProvider
from faker_file.providers.jpeg_file import JpegFileProvider
from faker_file.providers.mp3_file import Mp3FileProvider
from faker_file.providers.odp_file import OdpFileProvider
from faker_file.providers.ods_file import OdsFileProvider
from faker_file.providers.odt_file import OdtFileProvider
from faker_file.providers.pdf_file import PdfFileProvider
from faker_file.providers.png_file import PngFileProvider
from faker_file.providers.pptx_file import PptxFileProvider
from faker_file.providers.random_file_from_dir import RandomFileFromDirProvider
from faker_file.providers.rtf_file import RtfFileProvider
from faker_file.providers.svg_file import SvgFileProvider
from faker_file.providers.tar_file import TarFileProvider
from faker_file.providers.txt_file import TxtFileProvider
from faker_file.providers.webp_file import WebpFileProvider
from faker_file.providers.xlsx_file import XlsxFileProvider
from faker_file.providers.zip_file import ZipFileProvider

FAKER = Faker()
FAKER.add_provider(AugmentFileFromDirProvider)
FAKER.add_provider(BinFileProvider)
FAKER.add_provider(CsvFileProvider)
FAKER.add_provider(DocxFileProvider)
FAKER.add_provider(EmlFileProvider)
```

(continues on next page)

(continued from previous page)

```

FAKER.add_provider(EpubFileProvider)
FAKER.add_provider(IcoFileProvider)
FAKER.add_provider(JpegFileProvider)
FAKER.add_provider(Mp3FileProvider)
FAKER.add_provider(OdpFileProvider)
FAKER.add_provider(OdsFileProvider)
FAKER.add_provider(OdtFileProvider)
FAKER.add_provider(PdfFileProvider)
FAKER.add_provider(PngFileProvider)
FAKER.add_provider(PptxFileProvider)
FAKER.add_provider(RandomFileFromDirProvider)
FAKER.add_provider(RtfFileProvider)
FAKER.add_provider(SvgFileProvider)
FAKER.add_provider(TarFileProvider)
FAKER.add_provider(TxtFileProvider)
FAKER.add_provider(WebpFileProvider)
FAKER.add_provider(XlsxFileProvider)
FAKER.add_provider(ZipFileProvider)

```

Usage examples

```

augmented_file = FAKER.augment_file_from_dir(source_dir_path="/path/to/source/",)
bin_file = FAKER.bin_file()
csv_file = FAKER.csv_file()
docx_file = FAKER.docx_file()
eml_file = FAKER.eml_file()
epub_file = FAKER.epub_file()
ico_file = FAKER.ico_file()
jpeg_file = FAKER.jpeg_file()
mp3_file = FAKER.mp3_file()
odp_file = FAKER.odp_file()
ods_file = FAKER.ods_file()
odt_file = FAKER.odt_file()
pdf_file = FAKER.pdf_file()
png_file = FAKER.png_file()
pptx_file = FAKER.pptx_file()
random_file = FAKER.random_file_from_dir(source_dir_path="/path/to/source/",)
rtf_file = FAKER.rtf_file()
svg_file = FAKER.svg_file()
tar_file = FAKER.tar_file()
txt_file = FAKER.txt_file()
webp_file = FAKER.webp_file()
xlsx_file = FAKER.xlsx_file()
zip_file = FAKER.zip_file()

```

If you just need bytes back (instead of creating the file), provide the `raw=True` argument (works with all provider classes and inner functions):

```

augmented_raw = FAKER.augment_file_from_dir(
    source_dir_path="/path/to/source/",
    raw=True,
)

```

(continues on next page)

(continued from previous page)

```

bin_raw = FAKER.bin_file(raw=True)
csv_raw = FAKER.csv_file(raw=True)
docx_raw = FAKER.docx_file(raw=True)
eml_raw = FAKER.eml_file(raw=True)
epub_raw = FAKER.epub_file(raw=True)
ico_raw = FAKER.ico_file(raw=True)
jpeg_raw = FAKER.jpeg_file(raw=True)
mp3_raw = FAKER.mp3_file(raw=True)
odp_raw = FAKER.odp_file(raw=True)
ods_raw = FAKER.ods_file(raw=True)
odt_raw = FAKER.odt_file(raw=True)
pdf_raw = FAKER.pdf_file(raw=True)
png_raw = FAKER.png_file(raw=True)
pptx_raw = FAKER.pptx_file(raw=True)
random_raw = FAKER.random_file_from_dir(
    source_dir_path="/path/to/source/",
    raw=True,
)
rtf_raw = FAKER.rtf_file(raw=True)
svg_raw = FAKER.svg_file(raw=True)
tar_raw = FAKER.tar_file(raw=True)
txt_raw = FAKER.txt_file(raw=True)
webp_raw = FAKER.webp_file(raw=True)
xlsx_raw = FAKER.xlsx_file(raw=True)
zip_raw = FAKER.zip_file(raw=True)

```

13.1.2.2 With factory_boy

Imports and initialization

```

from factory import Faker

from faker_file.providers.augment_file_from_dir import AugmentFileFromDirProvider
from faker_file.providers.bin_file import BinFileProvider
from faker_file.providers.csv_file import CsvFileProvider
from faker_file.providers.docx_file import DocxFileProvider
from faker_file.providers.eml_file import EmlFileProvider
from faker_file.providers.epub_file import EpubFileProvider
from faker_file.providers.ico_file import IcoFileProvider
from faker_file.providers.jpeg_file import JpegFileProvider
from faker_file.providers.mp3_file import Mp3FileProvider
from faker_file.providers.odp_file import OdpFileProvider
from faker_file.providers.ods_file import OdsFileProvider
from faker_file.providers.odt_file import OdtFileProvider
from faker_file.providers.pdf_file import PdfFileProvider
from faker_file.providers.png_file import PngFileProvider
from faker_file.providers.pptx_file import PptxFileProvider
from faker_file.providers.random_file_from_dir import RandomFileFromDirProvider
from faker_file.providers.rtf_file import RtfFileProvider
from faker_file.providers.svg_file import SvgFileProvider
from faker_file.providers.tar_file import TarFileProvider

```

(continues on next page)

(continued from previous page)

```

from faker_file.providers.txt_file import TxtFileProvider
from faker_file.providers.webp_file import WebpFileProvider
from faker_file.providers.xlsx_file import XlsxFileProvider
from faker_file.providers.zip_file import ZipFileProvider

Faker.add_provider(AugmentFileFromDirProvider)
Faker.add_provider(BinFileProvider)
Faker.add_provider(CsvFileProvider)
Faker.add_provider(DocxFileProvider)
Faker.add_provider(EmlFileProvider)
Faker.add_provider(EpubFileProvider)
Faker.add_provider(IcoFileProvider)
Faker.add_provider(JpegFileProvider)
Faker.add_provider(Mp3FileProvider)
Faker.add_provider(OdpFileProvider)
Faker.add_provider(OdsFileProvider)
Faker.add_provider(OdtFileProvider)
Faker.add_provider(PdfFileProvider)
Faker.add_provider(PngFileProvider)
Faker.add_provider(PptxFileProvider)
Faker.add_provider(RandomFileFromDirProvider)
Faker.add_provider(RtfFileProvider)
Faker.add_provider(SvgFileProvider)
Faker.add_provider(TarFileProvider)
Faker.add_provider(TxtFileProvider)
Faker.add_provider(WebpFileProvider)
Faker.add_provider(XlsxFileProvider)
Faker.add_provider(ZipFileProvider)

```

13.1.2.2.1 upload/models.py

```

from django.db import models

class Upload(models.Model):
    """Upload model."""

    name = models.CharField(max_length=255, unique=True)
    description = models.TextField(null=True, blank=True)

    # File
    file = models.FileField(null=True)

    class Meta:
        verbose_name = "Upload"
        verbose_name_plural = "Upload"

    def __str__(self):
        return self.name

```

13.1.2.2.2 upload/factories.py

```
from django.conf import settings

from factory import Faker
from factory.django import DjangoModelFactory

from factory import Faker

# Import all needed providers
from faker_file.providers.augment_file_from_dir import (
    AugmentFileFromDirProvider,
)
from faker_file.providers.bin_file import BinFileProvider
from faker_file.providers.csv_file import CsvFileProvider
from faker_file.providers.docx_file import DocxFileProvider
from faker_file.providers.eml_file import EmlFileProvider
from faker_file.providers.epub_file import EpubFileProvider
from faker_file.providers.ico_file import IcoFileProvider
from faker_file.providers.jpeg_file import JpegFileProvider
from faker_file.providers.mp3_file import Mp3FileProvider
from faker_file.providers.odp_file import OdpFileProvider
from faker_file.providers.ods_file import OdsFileProvider
from faker_file.providers.odt_file import OdtFileProvider
from faker_file.providers.pdf_file import PdfFileProvider
from faker_file.providers.png_file import PngFileProvider
from faker_file.providers.pptx_file import PptxFileProvider
from faker_file.providers.random_file_from_dir import (
    RandomFileFromDirProvider,
)
from faker_file.providers.rtf_file import RtfFileProvider
from faker_file.providers.svg_file import SvgFileProvider
from faker_file.providers.tar_file import TarFileProvider
from faker_file.providers.txt_file import TxtFileProvider
from faker_file.providers.webp_file import WebpFileProvider
from faker_file.providers.xlsx_file import XlsxFileProvider
from faker_file.providers.zip_file import ZipFileProvider

# Import file storage, because we need to customize things in
# order for it to work with Django.
from faker_file.storages.filesystem import FileSystemStorage

from upload.models import Upload

# Add all needed providers
Faker.add_provider(AugmentFileFromDirProvider)
Faker.add_provider(BinFileProvider)
Faker.add_provider(CsvFileProvider)
Faker.add_provider(DocxFileProvider)
Faker.add_provider(EmlFileProvider)
Faker.add_provider(EpubFileProvider)
Faker.add_provider(IcoFileProvider)
```

(continues on next page)

(continued from previous page)

```

Faker.add_provider(JpegFileProvider)
Faker.add_provider(Mp3FileProvider)
Faker.add_provider(OdpFileProvider)
Faker.add_provider(OdsFileProvider)
Faker.add_provider(OdtFileProvider)
Faker.add_provider(PdfFileProvider)
Faker.add_provider(PngFileProvider)
Faker.add_provider(PptxFileProvider)
Faker.add_provider(RandomFileFromDirProvider)
Faker.add_provider(RtfFileProvider)
Faker.add_provider(SvgFileProvider)
Faker.add_provider(TarFileProvider)
Faker.add_provider(TxtFileProvider)
Faker.add_provider(WebpFileProvider)
Faker.add_provider(XlsxFileProvider)
Faker.add_provider(ZipFileProvider)

# Define a file storage.
STORAGE = FileSystemStorage(
    root_path=settings.MEDIA_ROOT,
    rel_path="tmp"
)

# Define the upload factory
class UploadFactory(DjangoModelFactory):
    """Upload factory."""

    name = Faker("text", max_nb_chars=100)
    description = Faker("text", max_nb_chars=1000)

    class Meta:
        model = Upload

    class Params:
        bin_file = Trait(file=Faker("bin_file", storage=STORAGE))
        csv_file = Trait(file=Faker("csv_file", storage=STORAGE))
        docx_file = Trait(file=Faker("docx_file", storage=STORAGE))
        eml_file = Trait(file=Faker("eml_file", storage=STORAGE))
        epub_file = Trait(file=Faker("epub_file", storage=STORAGE))
        ico_file = Trait(file=Faker("ico_file", storage=STORAGE))
        jpeg_file = Trait(file=Faker("jpeg_file", storage=STORAGE))
        mp3_file = Trait(file=Faker("mp3_file", storage=STORAGE))
        odp_file = Trait(file=Faker("odp_file", storage=STORAGE))
        ods_file = Trait(file=Faker("ods_file", storage=STORAGE))
        odt_file = Trait(file=Faker("odt_file", storage=STORAGE))
        pdf_file = Trait(file=Faker("pdf_file", storage=STORAGE))
        png_file = Trait(file=Faker("png_file", storage=STORAGE))
        pptx_file = Trait(file=Faker("pptx_file", storage=STORAGE))
        rtf_file = Trait(file=Faker("rtf_file", storage=STORAGE))
        svg_file = Trait(file=Faker("svg_file", storage=STORAGE))
        tar_file = Trait(file=Faker("tar_file", storage=STORAGE))
        txt_file = Trait(file=Faker("txt_file", storage=STORAGE))

```

(continues on next page)

(continued from previous page)

```
webp_file = Trait(file=Faker("webp_file", storage=STORAGE))
xlsx_file = Trait(file=Faker("xlsx_file", storage=STORAGE))
zip_file = Trait(file=Faker("zip_file", storage=STORAGE))
```

13.1.2.2.3 Usage example

```
UploadFactory(bin_file=True) # Upload with BIN file
UploadFactory(docx_file=True) # Upload with DOCX file
UploadFactory(jpeg_file=True) # Upload with JPEG file
UploadFactory(zip_file=True) # Upload with ZIP file
```

13.2 Recipes

13.2.1 When using with Faker

When using with Faker, there are two ways of using the providers.

13.2.1.1 Imports and initializations

One way

```
from faker import Faker
from faker_file.providers.bin_file import BinFileProvider
from faker_file.providers.docx_file import DocxFileProvider
from faker_file.providers.pdf_file import PdfFileProvider
from faker_file.providers.pptx_file import PptxFileProvider
from faker_file.providers.txt_file import TxtFileProvider
from faker_file.providers.zip_file import ZipFileProvider

FAKER = Faker()

# Usage example
file = TxtFileProvider(FAKER).txt_file(content="Lorem ipsum")
```

Or another

```
from faker import Faker
from faker_file.providers.docx_file import DocxFileProvider
from faker_file.providers.pdf_file import PdfFileProvider
from faker_file.providers.pptx_file import PptxFileProvider
from faker_file.providers.txt_file import TxtFileProvider
from faker_file.providers.zip_file import ZipFileProvider

FAKER = Faker()
FAKER.add_provider(DocxFileProvider)
FAKER.add_provider(PdfFileProvider)
FAKER.add_provider(PptxFileProvider)
```

(continues on next page)

(continued from previous page)

```
FAKER.add_provider(TxtFileProvider)
FAKER.add_provider(ZipFileProvider)

# Usage example
file = FAKER.txt_file(content="Lorem ipsum")
```

Throughout documentation we will be mixing these approaches.

13.2.1.2 Create a TXT file with static content

- Content of the file is Lorem ipsum.

```
file = TxtFileProvider(FAKER).txt_file(content="Lorem ipsum")
```

13.2.1.3 Create a DOCX file with dynamically generated content

- Content is generated dynamically.
- Content is limited to 1024 chars.
- Wrap lines after 80 chars.
- Prefix the filename with zzz.

```
file = DocxFileProvider(FAKER).docx_file(
    prefix="zzz",
    max_nb_chars=1_024,
    wrap_chars_after=80,
)
```

13.2.1.4 Create a ZIP file consisting of TXT files with static content

- 5 TXT files in the ZIP archive (default value is 5).
- Content of all files is Lorem ipsum.

```
file = ZipFileProvider(FAKER).zip_file(
    options={"create_inner_file_args": {"content": "Lorem ipsum"}}
)
```

13.2.1.5 Create a ZIP file consisting of 3 DOCX files with dynamically generated content

- 3 DOCX files in the ZIP archive.
- Content is generated dynamically.
- Content is limited to 1024 chars.
- Prefix the filenames in archive with xxx_.
- Prefix the filename of the archive itself with zzz.
- Inside the ZIP, put all files in directory yyy.

```
from faker_file.providers.helpers.inner import create_inner_docx_file
file = ZipFileProvider(FAKER).zip_file(
    prefix="zzz",
    options={
        "count": 3,
        "create_inner_file_func": create_inner_docx_file,
        "create_inner_file_args": {
            "prefix": "xxx_",
            "max_nb_chars": 1_024,
        },
        "directory": "yyy",
    }
)
```

13.2.1.6 Create a ZIP file of 9 DOCX files with content generated from template

- 9 DOCX files in the ZIP archive.
- Content is generated dynamically from given template.

```
from faker_file.providers.helpers.inner import create_inner_docx_file

TEMPLATE = "Hey {{name}},\n{{text}},\nBest regards\n{{name}}"

file = ZipFileProvider(FAKER).zip_file(
    options={
        "count": 9,
        "create_inner_file_func": create_inner_docx_file,
        "create_inner_file_args": {
            "content": TEMPLATE,
        },
    }
)
```

13.2.1.7 Create a nested ZIP file

Create a ZIP file which contains 5 ZIP files which contain 5 ZIP files which contain 5 DOCX files.

- 5 ZIP files in the ZIP archive.
- Content is generated dynamically.
- Prefix the filenames in archive with `nested_level_1_`.
- Prefix the filename of the archive itself with `nested_level_0_`.
- Each of the ZIP files inside the ZIP file in their turn contains 5 other ZIP files, prefixed with `nested_level_2_`, which in their turn contain 5 DOCX files.

```
from faker_file.providers.helpers.inner import (
    create_inner_docx_file,
    create_inner_zip_file,
)
```

(continues on next page)

(continued from previous page)

```

file = ZipFileProvider(FAKER).zip_file(
    prefix="nested_level_0_",
    options={
        "create_inner_file_func": create_inner_zip_file,
        "create_inner_file_args": {
            "prefix": "nested_level_1_",
            "options": {
                "create_inner_file_func": create_inner_zip_file,
                "create_inner_file_args": {
                    "prefix": "nested_level_2_",
                    "options": {
                        "create_inner_file_func": create_inner_docx_file,
                    }
                }
            }
        },
    },
)

```

13.2.1.8 Create a ZIP file with variety of different file types within

- 50 files in the ZIP archive (limited to DOCX, EPUB and TXT types).
- Content is generated dynamically.
- Prefix the filename of the archive itself with zzz_archive_.
- Inside the ZIP, put all files in directory zzz.

```

from faker import Faker
from faker_file.providers.helpers.inner import (
    create_inner_docx_file,
    create_inner_epub_file,
    create_inner_txt_file,
    fuzzy_choice_create_inner_file,
)
from faker_file.providers.zip_file import ZipFileProvider
from faker_file.storages.filesystem import FileSystemStorage

FAKER = Faker()
STORAGE = FileSystemStorage()

kwargs = {"storage": STORAGE, "generator": FAKER}
file = ZipFileProvider(FAKER).zip_file(
    prefix="zzz_archive_",
    options={
        "count": 50,
        "create_inner_file_func": fuzzy_choice_create_inner_file,
        "create_inner_file_args": {
            "func_choices": [
                (create_inner_docx_file, kwargs),
                (create_inner_epub_file, kwargs),
            ]
        }
    }
)

```

(continues on next page)

(continued from previous page)

```
        (create_inner_txt_file, kwargs),
    ],
    },
    "directory": "zzz",
}
)
```

13.2.1.9 Create a EML file consisting of TXT files with static content

- 5 TXT files in the EML email (default value is 5).
- Content of all files is Lorem ipsum.

```
from faker import Faker
from faker_file.providers.eml_file import EmlFileProvider

FAKER = Faker()

file = EmlFileProvider(FAKER).eml_file(
    options={"create_inner_file_args": {"content": "Lorem ipsum"}}
)
```

13.2.1.10 Create a EML file consisting of 3 DOCX files with dynamically generated content

- 3 DOCX files in the EML email.
- Content is generated dynamically.
- Content is limited to 1024 chars.
- Prefix the filenames in email with xxx_.
- Prefix the filename of the email itself with zzz.

```
from faker import Faker
from faker_file.providers.eml_file import EmlFileProvider
from faker_file.providers.helpers.inner import create_inner_docx_file

FAKER = Faker()

file = EmlFileProvider(FAKER).eml_file(
    prefix="zzz",
    options={
        "count": 3,
        "create_inner_file_func": create_inner_docx_file,
        "create_inner_file_args": {
            "prefix": "xxx_",
            "max_nb_chars": 1_024,
        },
    },
)
)
```

13.2.1.11 Create a nested EML file

Create a EML file which contains 5 EML files which contain 5 EML files which contain 5 DOCX files.

- 5 EML files in the EML file.
- Content is generated dynamically.
- Prefix the filenames in EML email with `nested_level_1_`.
- Prefix the filename of the EML email itself with `nested_level_0_`.
- Each of the EML files inside the EML file in their turn contains 5 other EML files, prefixed with `nested_level_2_`, which in their turn contain 5 DOCX files.

```
from faker import Faker
from faker_file.providers.eml_file import EmlFileProvider
from faker_file.providers.helpers.inner import (
    create_inner_docx_file,
    create_inner_eml_file,
)

FAKER = Faker()

file = EmlFileProvider(FAKER).eml_file(
    prefix="nested_level_0_",
    options={
        "create_inner_file_func": create_inner_eml_file,
        "create_inner_file_args": {
            "prefix": "nested_level_1_",
            "options": {
                "create_inner_file_func": create_inner_eml_file,
                "create_inner_file_args": {
                    "prefix": "nested_level_2_",
                    "options": {
                        "create_inner_file_func": create_inner_docx_file,
                    }
                }
            }
        }
    }
)
```

13.2.1.12 Create an EML file with variety of different file types within

- 10 files in the EML file (limited to DOCX, EPUB and TXT types).
- Content is generated dynamically.
- Prefix the filename of the EML itself with `zzz`.

```
from faker import Faker
from faker_file.providers.helpers.inner import (
    create_inner_docx_file,
    create_inner_epub_file,
    create_inner_txt_file,
```

(continues on next page)

(continued from previous page)

```
        fuzzy_choice_create_inner_file,
    )
    from faker_file.providers.eml_file import EmlFileProvider
    from faker_file.storages.filesystem import FileSystemStorage

    FAKER = Faker()
    STORAGE = FileSystemStorage()

    kwargs = {"storage": STORAGE, "generator": FAKER}

    file = EmlFileProvider(FAKER).eml_file(
        prefix="zzz",
        options={
            "count": 10,
            "create_inner_file_func": fuzzy_choice_create_inner_file,
            "create_inner_file_args": {
                "func_choices": [
                    (create_inner_docx_file, kwargs),
                    (create_inner_epub_file, kwargs),
                    (create_inner_txt_file, kwargs),
                ],
            },
        },
    )
```

13.2.1.13 Create a TXT file with static content

```
file = FAKER.txt_file(content="Lorem ipsum dolor sit amet")
```

13.2.1.14 Create a DOCX file with dynamically generated content

- Content is generated dynamically.
- Content is limited to 1024 chars.
- Wrap lines after 80 chars.
- Prefix the filename with zzz.

```
file = FAKER.docx_file(
    prefix="zzz",
    max_nb_chars=1_024,
    wrap_chars_after=80,
)
```


13.2.1.15 Create a PDF file with predefined template containing dynamic fixtures

- Content template is predefined and contains dynamic fixtures.
- Wrap lines after 80 chars.

```

TEMPLATE = """
{{date}} {{city}}, {{country}}

Hello {{name}},

{{text}} {{text}} {{text}}

{{text}} {{text}} {{text}}

{{text}} {{text}} {{text}}

Address: {{address}}

Best regards,

{{name}}
{{address}}
{{phone_number}}
"""

file = FAKER.pdf_file(content=TEMPLATE, wrap_chars_after=80)

```

13.2.1.16 Create a MP3 file

```
file = FAKER.mp3_file()
```

13.2.1.17 Create a MP3 file by explicitly specifying MP3 generator class

13.2.1.17.1 Google Text-to-Speech

```

from faker import Faker
from faker_file.providers.mp3_file import Mp3FileProvider
from faker_file.providers.mp3_file.generators.gtts_generator import (
    GttsMp3Generator,
)

FAKER = Faker()

file = Mp3FileProvider(FAKER).mp3_file(mp3_generator_cls=GttsMp3Generator)

```

You can tune arguments too:

```

from faker import Faker
from faker_file.providers.mp3_file import Mp3FileProvider
from faker_file.providers.mp3_file.generators.gtts_generator import (

```

(continues on next page)

(continued from previous page)

```
GttsMp3Generator,  
)  
  
FAKER = Faker()  
  
file = Mp3FileProvider(FAKER).mp3_file(  
    mp3_generator_cls=GttsMp3Generator,  
    mp3_generator_kwargs={  
        "lang": "en",  
        "tld": "co.uk",  
    }  
)
```

Refer to <https://gtts.readthedocs.io/en/latest/module.html#languages-gtts-lang> for list of accepted values for `lang` argument.

Refer to <https://gtts.readthedocs.io/en/latest/module.html#localized-accents> for list of accepted values for `tld` argument.

13.2.1.17.2 Microsoft Edge Text-to-Speech

```
from faker import Faker  
from faker_file.providers.mp3_file import Mp3FileProvider  
from faker_file.providers.mp3_file.generators.edge_tts_generator import (  
    EdgeTtsMp3Generator,  
)  
  
FAKER = Faker()  
  
file = Mp3FileProvider(FAKER).mp3_file(mp3_generator_cls=EdgeTtsMp3Generator)
```

You can tune arguments too:

```
from faker import Faker  
from faker_file.providers.mp3_file import Mp3FileProvider  
from faker_file.providers.mp3_file.generators.edge_tts_generator import (  
    EdgeTtsMp3Generator,  
)  
  
FAKER = Faker()  
  
file = Mp3FileProvider(FAKER).mp3_file(  
    mp3_generator_cls=EdgeTtsMp3Generator,  
    mp3_generator_kwargs={  
        "voice": "en-GB-LibbyNeural",  
    }  
)
```

Run `edge-tts -l` from terminal for list of available voices.

13.2.1.18 Create a MP3 file with custom MP3 generator

Default MP3 generator class is `GttsMp3Generator` which uses Google Text-to-Speech services to generate an MP3 file from given or randomly generated text. It does not require additional services to run and the only dependency here is the `gtts` package. You can however implement your own custom MP3 generator class and pass it to the `mp3_file` method in `mp3_generator_cls` argument instead of the default `GttsMp3Generator`. Read about quotas of Google Text-to-Speech services [here](#).

Usage with custom MP3 generator class.

```
# Imaginary `marytts` Python library
from marytts import MaryTTS

# Import BaseMp3Generator
from faker_file.providers.base.mp3_generator import (
    BaseMp3Generator,
)

# Define custom MP3 generator
class MaryTtsMp3Generator(BaseMp3Generator):

    locale: str = "cmu-rms-hsmm"
    voice: str = "en_US"

    def handle_kwargs(self, **kwargs) -> None:
        # Since it's impossible to unify all TTS systems it's allowed
        # to pass arbitrary arguments to the `BaseMp3Generator`
        # constructor. Each implementation class contains its own
        # additional tuning arguments. Check the source code of the
        # implemented MP3 generators as an example.
        if "locale" in kwargs:
            self.locale = kwargs["locale"]
        if "voice" in kwargs:
            self.voice = kwargs["voice"]

    def generate(self) -> bytes:
        # Your implementation here. Note, that `self.content`
        # in this context is the text to make MP3 from.
        # `self.generator` would be the `Faker` or `Generator`
        # instance from which you could extract information on
        # active locale.
        # What comes below is pseudo implementation.
        mary_tts = MaryTTS(locale=self.locale, voice=self.voice)
        return mary_tts.synth_mp3(self.content)

# Generate MP3 file from random text
file = FAKER.mp3_file(
    mp3_generator_cls=MaryTtsMp3Generator,
)
```

See exact implementation of `marytts_mp3_generator` in the examples.

13.2.1.19 Pick a random file from a directory given

- Create an exact copy of the randomly picked file under a different name.
- Prefix of the destination file would be zzz.
- `source_dir_path` is the absolute path to the directory to pick files from.

```
from faker_file.providers.random_file_from_dir import (
    RandomFileFromDirProvider,
)

file = RandomFileFromDirProvider(FAKER).random_file_from_dir(
    source_dir_path="/tmp/tmp/",
    prefix="zzz",
)
```

13.2.1.20 Generate a file of a certain size

The only two file types for which it is easy to foresee the file size are BIN and TXT. Note, that size of BIN files is always exact, while for TXT it is approximate.

13.2.1.20.1 BIN

```
file = BinFileProvider(FAKER).bin_file(length=1024**2) # 1 Mb
file = BinFileProvider(FAKER).bin_file(length=3*1024**2) # 3 Mb
file = BinFileProvider(FAKER).bin_file(length=10*1024**2) # 10 Mb

file = BinFileProvider(FAKER).bin_file(length=1024) # 1 Kb
file = BinFileProvider(FAKER).bin_file(length=3*1024) # 3 Kb
file = BinFileProvider(FAKER).bin_file(length=10*1024) # 10 Kb
```

13.2.1.20.2 TXT

```
file = TxtFileProvider(FAKER).txt_file(max_nb_chars=1024**2) # 1 Mb
file = TxtFileProvider(FAKER).txt_file(max_nb_chars=3*1024**2) # 3 Mb
file = TxtFileProvider(FAKER).txt_file(max_nb_chars=10*1024**2) # 10 Mb

file = TxtFileProvider(FAKER).txt_file(max_nb_chars=1024) # 1 Kb
file = TxtFileProvider(FAKER).txt_file(max_nb_chars=3*1024) # 3 Kb
file = TxtFileProvider(FAKER).txt_file(max_nb_chars=10*1024) # 10 Kb
```

13.2.1.21 Generate a lot of files using multiprocessing

13.2.1.21.1 Generate 100 DOCX files

- Use template.
- Generate 100 DOCX files.

```
from multiprocessing import Pool
from faker import Faker
from faker_file.providers.helpers.inner import create_inner_docx_file
from faker_file.storages.filesystem import FileSystemStorage

FAKER = Faker()
STORAGE = FileSystemStorage()

# Document template
TEMPLATE = "Hey {{name}}, \n{{text}}, \nBest regards \n{{name}}"

with Pool(processes=8) as pool:
    for _ in range(100): # Number of times we want to run our function
        pool.apply_async(
            create_inner_docx_file,
            # Apply async doesn't support kwargs. We have to pass all
            # arguments.
            [STORAGE, "mp", FAKER, None, None, TEMPLATE],
        )
    pool.close()
    pool.join()
```

13.2.1.21.2 Randomize the file format

```
from multiprocessing import Pool

from faker import Faker
from faker_file.providers.helpers.inner import (
    create_inner_docx_file,
    create_inner_epub_file,
    create_inner_pdf_file,
    create_inner_txt_file,
    fuzzy_choice_create_inner_file,
)
from faker_file.storages.filesystem import FileSystemStorage

FAKER = Faker()
STORAGE = FileSystemStorage()

# Document template
TEMPLATE = ""
{{date}} {{city}}, {{country}}

Hello {{name}},
```

(continues on next page)

(continued from previous page)

```

{{text}} {{text}} {{text}}

{{text}} {{text}} {{text}}

{{text}} {{text}} {{text}}

Address: {{address}}

Best regards,

{{name}}
{{address}}
{{phone_number}}
"""

kwargs = {"storage": STORAGE, "generator": FAKER, "content": TEMPLATE}

with Pool(processes=8) as pool:
    for _ in range(100): # Number of times we want to run our function
        pool.apply_async(
            fuzzy_choice_create_inner_file,
            [
                [
                    (create_inner_docx_file, kwargs),
                    (create_inner_epub_file, kwargs),
                    (create_inner_pdf_file, kwargs),
                    (create_inner_txt_file, kwargs),
                ]
            ],
        )
    pool.close()
    pool.join()

```

13.2.1.22 Generating files from existing documents using NLP augmentation

See the following example:

```

from faker import Faker
from faker_file.providers.augment_file_from_dir import (
    AugmentFileFromDirProvider,
)

FAKER = Faker()

file = AugmentFileFromDirProvider(FAKER).augment_file_from_dir(
    source_dir_path="/path/to/source/",
)

```

Generated file will resemble text of the original document, but will not be the same. This is useful when you don't want to test on text generated by Faker, but rather something that makes more sense for your use case, still want to ensure uniqueness of the documents.

The following file types are supported:

- DOCX
- EML
- EPUB
- ODT
- PDF
- RTF
- TXT

By default, all supported files are eligible for random selection. You could however narrow that list by providing `extensions` argument:

```
file = AugmentFileFromDirProvider(FAKER).augment_file_from_dir(
    source_dir_path="/path/to/source/",
    extensions={"docx", "pdf"}, # Pick only DOCX or PDF
)
```

By default `bert-base-multilingual-cased` model is used, which is pretrained on the top 104 languages with the largest Wikipedia using a masked language modeling (MLM) objective. If you want to use a different model, specify the proper identifier in the `model_path` argument. Some well working options for `model_path` are:

- `bert-base-multilingual-cased`
- `bert-base-multilingual-uncased`
- `bert-base-cased`
- `bert-base-uncased`
- `bert-base-german-cased`
- `GroNLP/bert-base-dutch-cased`

```
from faker_file.providers.augment_file_from_dir.augmenters import (
    nlpaug_augmenter
)

file = AugmentFileFromDirProvider(FAKER).augment_file_from_dir(
    text_augmenter_cls=(
        nlpaug_augmenter.ContextualWordEmbeddingsAugmenter
    ),
    text_augmenter_kwargs={
        "model_path": "bert-base-cased",
        "action": "substitute", # or "insert"
    }
)
```

Refer to [nlpaug docs](#) and check *Textual augmenters* examples.

13.2.1.23 Using *raw=True* features in tests

If you pass *raw=True* argument to any provider or inner function, instead of creating a file, you will get bytes back (or to be totally correct, bytes-like object *BytesValue*, which is basically bytes enriched with meta-data). You could then use the bytes content of the file to build a test payload as shown in the example test below:

```
import os
from io import BytesIO

from django.test import TestCase
from django.urls import reverse
from faker import Faker
from faker_file.providers.docx_file import DocxFileProvider
from rest_framework.status import HTTP_201_CREATED
from upload.models import Upload

FAKER = Faker()
FAKER.add_provider(DocxFileProvider)

class UploadTestCase(TestCase):
    """Upload test case."""

    def test_create_docx_upload(self) -> None:
        """Test create an Upload."""
        url = reverse("api:upload-list")

        raw = FAKER.docx_file(raw=True)
        test_file = BytesIO(raw)
        test_file.name = os.path.basename(raw.data["filename"])

        payload = {
            "name": FAKER.word(),
            "description": FAKER.paragraph(),
            "file": test_file,
        }

        response = self.client.post(url, payload, format="json")

        # Test if request is handled properly (HTTP 201)
        self.assertEqual(response.status_code, HTTP_201_CREATED)

        test_upload = Upload.objects.get(id=response.data["id"])

        # Test if the name is properly recorded
        self.assertEqual(str(test_upload.name), payload["name"])

        # Test if file name recorded properly
        self.assertEqual(str(test_upload.file.name), test_file.name)
```


13.2.2 When using with Django (and factory_boy)

When used with Django (to generate fake data with `factory_boy` factories), the `root_path` argument of the correspondent file storage shall be provided. Otherwise (although no errors will be triggered) the generated files will reside outside the `MEDIA_ROOT` directory (by default in `/tmp/` on Linux) and further operations with those files through Django will cause `SuspiciousOperation` exception.

13.2.2.1 Basic example

13.2.2.1.1 Imaginary Django model

```
from django.db import models

class Upload(models.Model):
    """Upload model."""

    name = models.CharField(max_length=255, unique=True)
    description = models.TextField(null=True, blank=True)

    # File
    file = models.FileField(null=True)

    class Meta:
        verbose_name = "Upload"
        verbose_name_plural = "Upload"

    def __str__(self):
        return self.name
```

13.2.2.1.2 Correspondent factory_boy factory

```
from django.conf import settings

from factory import Faker
from factory.django import DjangoModelFactory

# Import all providers we want to use
from faker_file.providers.bin_file import BinFileProvider
from faker_file.providers.csv_file import CsvFileProvider
from faker_file.providers.docx_file import DocxFileProvider
from faker_file.providers.eml_file import EmlFileProvider
from faker_file.providers.epub_file import EpubFileProvider
from faker_file.providers.ico_file import IcoFileProvider
from faker_file.providers.jpeg_file import JpegFileProvider
from faker_file.providers.mp3_file import Mp3FileProvider
from faker_file.providers.ods_file import OdsFileProvider
from faker_file.providers.odt_file import OdtFileProvider
from faker_file.providers.pdf_file import PdfFileProvider
from faker_file.providers.png_file import PngFileProvider
from faker_file.providers.pptx_file import PptxFileProvider
```

(continues on next page)

(continued from previous page)

```

from faker_file.providers.rtf_file import RtfFileProvider
from faker_file.providers.svg_file import SvgFileProvider
from faker_file.providers.txt_file import TxtFileProvider
from faker_file.providers.webp_file import WebpFileProvider
from faker_file.providers.xlsx_file import XlsxFileProvider
from faker_file.providers.zip_file import ZipFileProvider

# Import file storage, because we need to customize things in order for it
# to work with Django.
from faker_file.storages.filesystem import FileSystemStorage

from upload.models import Upload

# Add all providers we want to use
Faker.add_provider(BinFileProvider)
Faker.add_provider(CsvFileProvider)
Faker.add_provider(DocxFileProvider)
Faker.add_provider(EmlFileProvider)
Faker.add_provider(EpubFileProvider)
Faker.add_provider(IcoFileProvider)
Faker.add_provider(JpegFileProvider)
Faker.add_provider(Mp3FileProvider)
Faker.add_provider(OdsFileProvider)
Faker.add_provider(OdtFileProvider)
Faker.add_provider(PdfFileProvider)
Faker.add_provider(PngFileProvider)
Faker.add_provider(PptxFileProvider)
Faker.add_provider(RtfFileProvider)
Faker.add_provider(SvgFileProvider)
Faker.add_provider(TxtFileProvider)
Faker.add_provider(WebpFileProvider)
Faker.add_provider(XlsxFileProvider)
Faker.add_provider(ZipFileProvider)

# Define a file storage. When working with Django and FileSystemStorage
# you need to set the value of `root_path` argument to
# `settings.MEDIA_ROOT`.
STORAGE = FileSystemStorage(
    root_path=settings.MEDIA_ROOT,
    rel_path="tmp"
)

class UploadFactory(DjangoModelFactory):
    """Upload factory."""

    name = Faker("text", max_nb_chars=100)
    description = Faker("text", max_nb_chars=1000)

    class Meta:
        model = Upload

    class Params:

```

(continues on next page)

(continued from previous page)

```

bin_file = Trait(file=Faker("bin_file", storage=STORAGE))
csv_file = Trait(file=Faker("csv_file", storage=STORAGE))
docx_file = Trait(file=Faker("docx_file", storage=STORAGE))
eml_file = Trait(file=Faker("eml_file", storage=STORAGE))
epub_file = Trait(file=Faker("epub_file", storage=STORAGE))
ico_file = Trait(file=Faker("ico_file", storage=STORAGE))
jpeg_file = Trait(file=Faker("jpeg_file", storage=STORAGE))
mp3_file = Trait(file=Faker("mp3_file", storage=STORAGE))
ods_file = Trait(file=Faker("ods_file", storage=STORAGE))
odt_file = Trait(file=Faker("odt_file", storage=STORAGE))
pdf_file = Trait(file=Faker("pdf_file", storage=STORAGE))
png_file = Trait(file=Faker("png_file", storage=STORAGE))
pptx_file = Trait(file=Faker("pptx_file", storage=STORAGE))
rtf_file = Trait(file=Faker("rtf_file", storage=STORAGE))
svg_file = Trait(file=Faker("svg_file", storage=STORAGE))
txt_file = Trait(file=Faker("txt_file", storage=STORAGE))
webp_file = Trait(file=Faker("webp_file", storage=STORAGE))
xlsx_file = Trait(file=Faker("xlsx_file", storage=STORAGE))
zip_file = Trait(file=Faker("zip_file", storage=STORAGE))

```

And then somewhere in your code:

```

UploadFactory(bin_file=True) # Upload with BIN file
UploadFactory(docx_file=True) # Upload with DOCX file
UploadFactory(jpeg_file=True) # Upload with JPEG file
UploadFactory(zip_file=True) # Upload with ZIP file

```

13.2.2.2 Randomize provider choice

```

from factory import LazyAttribute
from faker import Faker
from random import choice

FAKER = Faker()

PROVIDER_CHOICES = [
    lambda: BinFileProvider(FAKER).bin_file(storage=STORAGE),
    lambda: CsvFileProvider(FAKER).csv_file(storage=STORAGE),
    lambda: DocxFileProvider(FAKER).docx_file(storage=STORAGE),
    lambda: EmlFileProvider(FAKER).eml_file(storage=STORAGE),
    lambda: EpubFileProvider(FAKER).epub_file(storage=STORAGE),
    lambda: IcoFileProvider(FAKER).ico_file(storage=STORAGE),
    lambda: JpegFileProvider(FAKER).jpeg_file(storage=STORAGE),
    lambda: Mp3FileProvider(FAKER).mp3_file(storage=STORAGE),
    lambda: OdsFileProvider(FAKER).ods_file(storage=STORAGE),
    lambda: OdtFileProvider(FAKER).odt_file(storage=STORAGE),
    lambda: PdfFileProvider(FAKER).pdf_file(storage=STORAGE),
    lambda: PngFileProvider(FAKER).png_file(storage=STORAGE),
    lambda: PptxFileProvider(FAKER).pptx_file(storage=STORAGE),
    lambda: RtfFileProvider(FAKER).rtf_file(storage=STORAGE),
    lambda: SvgFileProvider(FAKER).svg_file(storage=STORAGE),

```

(continues on next page)

(continued from previous page)

```
lambda: TxtFileProvider(FAKER).txt_file(storage=STORAGE),
lambda: XlsxFileProvider(FAKER).xlsx_file(storage=STORAGE),
lambda: ZipFileProvider(FAKER).zip_file(storage=STORAGE),
]

def pick_random_provider(*args, **kwargs):
    return choice(PROVIDER_CHOICES)()

class UploadFactory(DjangoModelFactory):
    """Upload factory that randomly picks a file provider."""

    # ...
    class Params:
        # ...
        random_file = Trait(file=LazyAttribute(pick_random_provider))
        # ...
```

And then somewhere in your code:

```
UploadFactory(random_file=True) # Upload with random file
```

13.2.2.3 Use a different locale

```
from factory import Faker
from factory.django import DjangoModelFactory
from faker_file.providers.ods_file import OdsFileProvider

Faker._DEFAULT_LOCALE = "hy_AM" # Set locale to Armenian

Faker.add_provider(OdsFileProvider)

class UploadFactory(DjangoModelFactory):
    """Base Upload factory."""

    name = Faker("text", max_nb_chars=100)
    description = Faker("text", max_nb_chars=1000)
    file = Faker("ods_file")

    class Meta:
        """Meta class."""

        model = Upload
```

13.2.2.4 Other Django usage examples

Faker example with AWS S3 storage

```
from django.conf import settings
from faker import Faker
from faker_file.providers.pdf_file import PdfFileProvider
from faker_file.storages.aws_s3 import AWSS3Storage

FAKER = Faker()
STORAGE = AWSS3Storage(
    bucket_name=settings.AWS_STORAGE_BUCKET_NAME,
    root_path="",
    rel_path="",
)
FAKER.add_provider(PdfFileProvider)

file = PdfFileProvider(FAKER).pdf_file(storage=STORAGE)
```

factory-boy example with AWS S3 storage

```
import factory

from django.conf import settings
from factory import Faker
from factory.django import DjangoModelFactory
from faker_file.storages.aws_s3 import AWSS3Storage

from upload.models import Upload

STORAGE = AWSS3Storage(
    bucket_name=settings.AWS_STORAGE_BUCKET_NAME,
    root_path="",
    rel_path="",
)

Faker.add_provider(PdfFileProvider)

class UploadFactory(DjangoModelFactory):
    name = Faker('word')
    description = Faker('text')
    file = Faker("pdf_file", storage=STORAGE)

    class Meta:
        model = Upload

upload = UploadFactory()
```

Flexible storage selection

```
from django.conf import settings
from django.core.files.storage import default_storage
from faker_file.storages.aws_s3 import AWSS3Storage
from faker_file.storages.filesystem import FileSystemStorage
```

(continues on next page)

(continued from previous page)

```

from storages.backends.s3boto3 import S3Boto3Storage

# Faker doesn't know anything about Django. That's why, if we want to
# support remote storages, we need to manually check which file storage
# backend is used. If `Boto3` storage backend (of the `django-storages`
# package) is used we use the correspondent `AWSS3Storage` class of the
# `faker-file`.
# Otherwise, fall back to native file system storage (`FileSystemStorage`)
# of the `faker-file`.
if isinstance(default_storage, S3Boto3Storage):
    STORAGE = AWSS3Storage(
        bucket_name=settings.AWS_STORAGE_BUCKET_NAME,
        credentials={
            "key_id": settings.AWS_ACCESS_KEY_ID,
            "key_secret": settings.AWS_SECRET_ACCESS_KEY,
        },
        rel_path="tmp",
    )
else:
    STORAGE = FileSystemStorage(
        root_path=settings.MEDIA_ROOT,
        rel_path="tmp",
    )

```

13.3 Security Policy

13.3.1 Reporting a Vulnerability

Do not report security issues on GitHub!

Please report security issues by emailing Artur Barseghyan <artur.barseghyan@gmail.com>.

13.3.2 Supported Versions

Make sure to use the latest version.

The two most recent `faker-file` release series receive security support.

For example, during the development cycle leading to the release of `faker-file` 0.11.x, support will be provided for `faker-file` 0.10.x.

Upon the release of `faker-file` 0.12.x, security support for `faker-file` 0.10.x will end.

Version	Supported	
0.11.x	Yes	
0.10.x	Yes	

(continues on next page)

(continued from previous page)

< 0.10

No

13.4 Contributor Covenant Code of Conduct

13.4.1 Our Pledge

We as members, contributors, and leaders pledge to make participation in our community a harassment-free experience for everyone, regardless of age, body size, visible or invisible disability, ethnicity, sex characteristics, gender identity and expression, level of experience, education, socio-economic status, nationality, personal appearance, race, religion, or sexual identity and orientation.

We pledge to act and interact in ways that contribute to an open, welcoming, diverse, inclusive, and healthy community.

13.4.2 Our Standards

Examples of behavior that contributes to a positive environment for our community include:

- Demonstrating empathy and kindness toward other people
- Being respectful of differing opinions, viewpoints, and experiences
- Giving and gracefully accepting constructive feedback
- Accepting responsibility and apologizing to those affected by our mistakes, and learning from the experience
- Focusing on what is best not just for us as individuals, but for the overall community

Examples of unacceptable behavior include:

- The use of sexualized language or imagery, and sexual attention or advances of any kind
- Trolling, insulting or derogatory comments, and personal or political attacks
- Public or private harassment
- Publishing others' private information, such as a physical or email address, without their explicit permission
- Other conduct which could reasonably be considered inappropriate in a professional setting

13.4.3 Enforcement Responsibilities

Community leaders are responsible for clarifying and enforcing our standards of acceptable behavior and will take appropriate and fair corrective action in response to any behavior that they deem inappropriate, threatening, offensive, or harmful.

Community leaders have the right and responsibility to remove, edit, or reject comments, commits, code, wiki edits, issues, and other contributions that are not aligned to this Code of Conduct, and will communicate reasons for moderation decisions when appropriate.

13.4.4 Scope

This Code of Conduct applies within all community spaces, and also applies when an individual is officially representing the community in public spaces. Examples of representing our community include using an official e-mail address, posting via an official social media account, or acting as an appointed representative at an online or offline event.

13.4.5 Enforcement

Instances of abusive, harassing, or otherwise unacceptable behavior may be reported to the community leaders responsible for enforcement at artur.barseghyan@gmail.com. All complaints will be reviewed and investigated promptly and fairly.

All community leaders are obligated to respect the privacy and security of the reporter of any incident.

13.4.6 Enforcement Guidelines

Community leaders will follow these Community Impact Guidelines in determining the consequences for any action they deem in violation of this Code of Conduct:

13.4.6.1 1. Correction

Community Impact: Use of inappropriate language or other behavior deemed unprofessional or unwelcome in the community.

Consequence: A private, written warning from community leaders, providing clarity around the nature of the violation and an explanation of why the behavior was inappropriate. A public apology may be requested.

13.4.6.2 2. Warning

Community Impact: A violation through a single incident or series of actions.

Consequence: A warning with consequences for continued behavior. No interaction with the people involved, including unsolicited interaction with those enforcing the Code of Conduct, for a specified period of time. This includes avoiding interactions in community spaces as well as external channels like social media. Violating these terms may lead to a temporary or permanent ban.

13.4.6.3 3. Temporary Ban

Community Impact: A serious violation of community standards, including sustained inappropriate behavior.

Consequence: A temporary ban from any sort of interaction or public communication with the community for a specified period of time. No public or private interaction with the people involved, including unsolicited interaction with those enforcing the Code of Conduct, is allowed during this period. Violating these terms may lead to a permanent ban.

13.4.6.4 4. Permanent Ban

Community Impact: Demonstrating a pattern of violation of community standards, including sustained inappropriate behavior, harassment of an individual, or aggression toward or disparagement of classes of individuals.

Consequence: A permanent ban from any sort of public interaction within the community.

13.4.7 Attribution

This Code of Conduct is adapted from the [Contributor Covenant](https://www.contributor-covenant.org/version/2/0/code_of_conduct.html), version 2.0, available at https://www.contributor-covenant.org/version/2/0/code_of_conduct.html.

Community Impact Guidelines were inspired by [Mozilla's code of conduct enforcement ladder](#).

For answers to common questions about this code of conduct, see the FAQ at <https://www.contributor-covenant.org/faq>. Translations are available at <https://www.contributor-covenant.org/translations>.

13.5 Contributor guidelines

13.5.1 Developer prerequisites

13.5.1.1 pre-commit

Refer to [pre-commit](#) for installation instructions.

TL;DR:

```
pip install pipx --user # Install pipx
pipx install pre-commit # Install pre-commit
pre-commit install # Install pre-commit hooks
```

Installing [pre-commit](#) will ensure you adhere to the project code quality standards.

13.5.2 Code standards

[black](#), [isort](#), [ruff](#) and [doc8](#) will be automatically triggered by [pre-commit](#). Still, if you want to run checks manually:

```
./scripts/black.sh
./scripts/doc8.sh
./scripts/isort.sh
./scripts/ruff.sh
```

13.5.3 Requirements

Requirements are compiled using [pip-tools](#).

```
./scripts/compile_requirements.sh
```

13.5.4 Virtual environment

You are advised to work in virtual environment.

TL;DR:

```
python -m venv env
pip install -e .
pip install -r examples/requirements/django_3_2_and_flask.txt
```

13.5.5 Documentation

Check [documentation](#).

13.5.6 Testing

Check [testing](#).

If you introduce changes or fixes, make sure to test them locally using all supported environments. For that use `tox`.

```
tox
```

In any case, GitHub Actions will catch potential errors, but using `tox` speeds things up.

13.5.7 Pull requests

You can contribute to the project by making a [pull request](#).

For example:

- To fix documentation typos.
- To improve documentation (for instance, to add new recipe or fix an existing recipe that doesn't seem to work).
- To introduce a new feature (for instance, add support for a non-supported file type).

Good to know:

- Test suite makes extensive use of parametrization. Make sure you have added your changes in the right place.

General list to go through:

- Does your change require documentation update?
- Does your change require update to tests?
- Did you test both Latin and Unicode characters?
- Does your change rely on third-party cloud based service? If so, please make sure it's added to tests that should be retried a couple of times. Example: `@pytest.mark.flaky(reruns=5)`.

When fixing bugs (in addition to the general list):

- Make sure to add regression tests.

When adding a new feature (in addition to the general list):

- Check the licenses of added dependencies carefully and make sure to list them in [prerequisites](#).
- Make sure to update the documentation (check whether the [installation](#), [features](#), [recipes](#) and [quick start](#) require changes).

13.5.8 Questions

Questions can be asked on GitHub [discussions](#).

13.5.9 Issues

For reporting a bug or filing a feature request use GitHub [issues](#).

Do not report security issues on GitHub. Check the [support](#) section.

13.6 Release history and notes

[Sequence based identifiers](#) are used for versioning (schema follows below):

<code>major.minor[.revision]</code>

- It's always safe to upgrade within the same minor version (for example, from 0.3 to 0.3.4).
- Minor version changes might be backwards incompatible. Read the release notes carefully before upgrading (for example, when upgrading from 0.3.4 to 0.4).
- All backwards incompatible changes are mentioned in this document.

13.6.1 0.11.5

2023-02-20

- Fixes in typing of `CsvFileProvider.Tuple[str, str]` becomes `Tuple[str, ...]`.

13.6.2 0.11.4

2023-02-16

Note: Release dedicated to my dear valentine - Anahit.

- Added `filename` to data property of values returned by `Mp3FileProvider` provider (`StringValue`, `BytesValue`).

13.6.3 0.11.3

2023-02-10

- Moved several interface classes from one location to another. If you haven't implemented custom generators, this won't affect you. If you did, make sure to update your imports:
 - `BaseTextAugmenter` has been moved from `faker_file.providers.augment_file_from_dir.augmenters.base` to `faker_file.providers.base.text_augmenter`.
 - `BaseTextExtractor` has been moved from `faker_file.providers.augment_file_from_dir.extractors.base` to `faker_file.providers.base.text_extractor`.
 - `BaseMp3Generator` has been moved from `faker_file.providers.mp3_file.generators.base` to `faker_file.providers.base.mp3_generator`.

13.6.4 0.11.2

2023-02-07

- Add `filename` to data property of values returned by providers (`StringValue`, `BytesValue`).

13.6.5 0.11.1

2023-01-31

- Documentation improvements.
- MyPy fixes.

13.6.6 0.11

2023-01-25

- Allow returning binary contents of the file by providing the `raw=True` argument (`False` by default, works with all provider classes and inner functions). If you have subclassed or overridden provider classes or written custom inner functions, make sure to reflect the changes in your code.

13.6.7 0.10.12

2023-01-21

- Add `TarFileProvider` and `create_inner_tar_file` function.
- Add `OdpFileProvider` and `create_inner_odp_file` function.

13.6.8 0.10.11

2023-01-20

- Improve EPUB document layout.
- Improve PDF document layout.
- Minor documentation improvements.

13.6.9 0.10.10

2023-01-19

- Allow passing `model_name` and `action` arguments to the `ContextualWordEmbeddingsAugmenter`.
- Replace `bert-base-cased` with `bert-base-multilingual-cased` as a default model for `ContextualWordEmbeddingsAugmenter`.
- Improve PPTX document layout.
- Minor fixes in documentation.

13.6.10 0.10.9

2023-01-18

- Add an installation directive `[common]` to install everything except ML libraries.
- Added testing of UTF8 content.

13.6.11 0.10.8

2023-01-16

- Switch to PyPI releases of `gtts`.
- Stop testing against Django 3.0 and 3.1.
- Documentation improvements.
- Tests improvements.

13.6.12 0.10.7

2023-01-13

- Add `OdtFileProvider` and `create_inner_odt_file` function.
- Documentation improvements.
- Async related deprecation fixes in `EdgeTtsMp3Generator`.
- Optimize example factories.

13.6.13 0.10.6

2023-01-11

- Add `AugmentFileFromDirProvider` provider for making augmented copies of randomly picked files from given directory.
- Documentation improvements.
- Fixes in setup.

13.6.14 0.10.5

2023-01-09

- Add `fuzzy_choice_create_inner_file` inner function for easy diversion of files within archives (ZIP, EML).
- Documentation improvements.
- Add `MaryTTS` example (another MP3 generator for `Mp3FileProvider`).

13.6.15 0.10.4

2023-01-08

- Add missing `mp3_generator_kwargs` argument to the `create_inner_mp3_file` function.
- Clean-up.

13.6.16 0.10.3

2023-01-07

Improvements of the `Mp3FileProvider` module:

- Pass active generator to the `Mp3FileProvider` in the `generator` argument if `BaseMp3Generator` (and all implementations).
- Introduce `handle_kwargs` method in the `BaseMp3Generator` to handle arbitrary provider specific tuning.
- Add `EdgeTtsMp3Generator` MP3 generator.
- Add `mp3_generator_kwargs` argument to the `Mp3FileProvider.mp3_file` method.

13.6.17 0.10.2

2023-01-06

- Add `Mp3FileProvider`.
- Add `create_inner_mp3_file` inner function.

13.6.18 0.10.1

2023-01-05

- Fixes in ZipFileProvider.

13.6.19 0.10

2023-01-04

Note, that this release introduces breaking changes!

- Move all `create_inner*_file` functions from `faker_file.providers.zip_file` to `faker_file.providers.helpers.inner` module. Adjust your imports accordingly.
- Add `EmlFileProvider`.
- Add `create_inner_eml_file` inner function.

13.6.20 0.9.3

2023-01-03

- Add `EpubFileProvider` provider.

13.6.21 0.9.2

2022-12-23

- Add `RrfFileProvider`.
- Added SQLAlchemy factory example.

13.6.22 0.9.1

2022-12-19

- Fixes in cloud storage.
- Documentation fixes.

13.6.23 0.9

2022-12-17

- Add optional encoding argument to `CsvFileProvider` and `PdfFileProvider` providers.
- Add `root_path` argument to cloud storages.
- Moved all image related code (`IcoFileProvider`, `JpegFileProvider`, `PngFileProvider`, `SvgFileProvider`, `WebpFileProvider`) to `ImageMixin`. Moved all tabular data related code (`OdsFileProvider`, `XlsxFileProvider`) to `TabularDataMixin`.
- Documentation improvements.

13.6.24 0.8

2022-12-16

Note, that this release introduces breaking changes!

- All file system based operations are moved to a separate abstraction layer of file storages. The following storages have been implemented: `FileSystemStorage`, `PathyFileSystemStorage`, `AWSS3Storage`, `GoogleCloudStorage` and `AzureStorage`. The `root_path` and `rel_path` params of the providers are deprecated in favour of storages. See the docs more usage examples.

13.6.25 0.7

2022-12-12

- Added `RandomFileFromDirProvider` which picks a random file from directory given.
- Improved docs.

13.6.26 0.6

2022-12-11

- Pass optional `generator` argument to inner functions of the `ZipFileProvider`.
- Added `create_inner_zip_file` inner function which allows to create nested ZIPs.
- Reached test coverage of 100%.

13.6.27 0.5

2022-12-10

Note, that this release introduces breaking changes!

- Added `ODS` file support.
- Switched to `tablib` for easy, non-variant support of various formats (`XLSX`, `ODS`).
- Silence `imgkit` logging output.
- `ZipFileProvider` allows to pass arbitrary arguments to inner functions. Put all your inner function arguments into a dictionary and pass it in `create_inner_file_args` key inside `options` argument. See the example below.

```
zip_file = ZipFileProvider(None).file(
    prefix="zzz_archive_",
    options={
        "count": 5,
        "create_inner_file_func": create_inner_docx_file,
        "create_inner_file_args": {
            "prefix": "zzz_file_",
            "max_nb_chars": 1_024,
            "content": "{{date}}\r\n{{text}}\r\n{{name}}",
        },
        "directory": "zzz",
    }
)
```


13.6.28 0.4

2022-12-09

Note, that this release introduces breaking changes!

- Remove the concept of content generators (and the correspondent `content_generator` arguments in implemented providers). Instead, allow usage of dynamic fixtures in the provided `content` argument.
- Remove temporary files when creating ZIP archives.
- Various improvements and fixes in docs.

13.6.29 0.3

2022-12-08

- Add support for *BIN*, *CSV* and *XLSX* files.
- Better visual representation of generated images and PDFs.

13.6.30 0.2

2022-12-07

- Added support for *ICO*, *JPEG*, *PNG*, *SVG* and *WEBP* files.
- Documentation improvements.

13.6.31 0.1

2022-12-06

- Initial beta release.

13.7 Package

13.7.1 faker_file package

13.7.1.1 Subpackages

13.7.1.1.1 faker_file.providers package

13.7.1.1.1.1 Subpackages

13.7.1.1.1.2 faker_file.providers.augment_file_from_dir package

13.7.1.1.1.3 Subpackages

13.7.1.1.1.4 faker_file.providers.augment_file_from_dir.augmenters package

13.7.1.1.1.5 Submodules

13.7.1.1.1.6 faker_file.providers.augment_file_from_dir.augmenters.base module

13.7.1.1.1.7 faker_file.providers.augment_file_from_dir.augmenters.nlpaug_augmenter module

13.7.1.1.1.8 Module contents

13.7.1.1.1.9 faker_file.providers.augment_file_from_dir.extractors package

13.7.1.1.1.10 Submodules

13.7.1.1.1.11 faker_file.providers.augment_file_from_dir.extractors.base module

13.7.1.1.1.12 faker_file.providers.augment_file_from_dir.extractors.tika_extractor module

13.7.1.1.1.13 Module contents

13.7.1.1.1.14 Module contents

13.7.1.1.1.15 faker_file.providers.helpers package

13.7.1.1.1.16 Submodules

13.7.1.1.1.17 faker_file.providers.helpers.inner module

`faker_file.providers.helpers.inner.create_inner_bin_file`(*storage*: *Optional*[[BaseStorage](#)] = *None*,
prefix: *Optional*[*str*] = *None*, *generator*:
Optional[*Union*[*Faker*, *Generator*,
Provider]] = *None*, *length*: *int* = *1 * 1024*
** 1024*, *content*: *Optional*[*bytes*] = *None*,
raw: *bool* = *True*, ***kwargs*) →
[BytesValue](#)

```
faker_file.providers.helpers.inner.create_inner_bin_file(storage: Optional[BaseStorage] = None,  
                                                         prefix: Optional[str] = None, generator:  
                                                         Optional[Union[Faker, Generator,  
Provider]] = None, length: int = 1 * 1024  
* 1024, content: Optional[bytes] = None,  
**kwargs) → StringValue
```

Create inner BIN file.

```
faker_file.providers.helpers.inner.create_inner_csv_file(storage: Optional[BaseStorage] = None,  
                                                         prefix: Optional[str] = None, generator:  
                                                         Optional[Union[Faker, Generator,  
Provider]] = None, header:  
Optional[Sequence[str]] = None,  
data_columns: Tuple[str, str] =  
('{{name}}', '{{address}}'), num_rows: int  
= 10, include_row_ids: bool = False,  
content: Optional[str] = None, raw: bool  
= True, **kwargs) → BytesValue
```

```
faker_file.providers.helpers.inner.create_inner_csv_file(storage: Optional[BaseStorage] = None,  
                                                         prefix: Optional[str] = None, generator:  
                                                         Optional[Union[Faker, Generator,  
Provider]] = None, header:  
Optional[Sequence[str]] = None,  
data_columns: Tuple[str, str] =  
('{{name}}', '{{address}}'), num_rows: int  
= 10, include_row_ids: bool = False,  
content: Optional[str] = None, **kwargs)  
→ StringValue
```

Create inner CSV file.

```
faker_file.providers.helpers.inner.create_inner_docx_file(storage: Optional[BaseStorage] = None,  
                                                         prefix: Optional[str] = None, generator:  
                                                         Optional[Union[Faker, Generator,  
Provider]] = None, max_nb_chars: int =  
DEFAULT_TEXT_MAX_NB_CHARS,  
wrap_chars_after: Optional[int] =  
None, content: Optional[str] = None,  
raw: bool = True, **kwargs) →  
BytesValue
```

```
faker_file.providers.helpers.inner.create_inner_docx_file(storage: Optional[BaseStorage] = None,  
                                                         prefix: Optional[str] = None, generator:  
                                                         Optional[Union[Faker, Generator,  
Provider]] = None, max_nb_chars: int =  
DEFAULT_TEXT_MAX_NB_CHARS,  
wrap_chars_after: Optional[int] =  
None, content: Optional[str] = None,  
**kwargs) → StringValue
```

Create inner DOCX file.

```
faker_file.providers.helpers.inner.create_inner eml_file(storage: Optional[BaseStorage] = None,
                                                         prefix: Optional[str] = None, generator:
                                                         Optional[Union[Faker, Generator,
                                                         Provider]] = None, options:
                                                         Optional[Dict[str, Any]] = None,
                                                         max_nb_chars: int =
                                                         DEFAULT_TEXT_MAX_NB_CHARS,
                                                         wrap_chars_after: Optional[int] = None,
                                                         content: Optional[str] = None, raw: bool
                                                         = True, **kwargs) → BytesValue
```

```
faker_file.providers.helpers.inner.create_inner eml_file(storage: Optional[BaseStorage] = None,
                                                         prefix: Optional[str] = None, generator:
                                                         Optional[Union[Faker, Generator,
                                                         Provider]] = None, options:
                                                         Optional[Dict[str, Any]] = None,
                                                         max_nb_chars: int =
                                                         DEFAULT_TEXT_MAX_NB_CHARS,
                                                         wrap_chars_after: Optional[int] = None,
                                                         content: Optional[str] = None, **kwargs)
                                                         → StringValue
```

Create inner EML file.

```
faker_file.providers.helpers.inner.create_inner epub_file(storage: Optional[BaseStorage] = None,
                                                           prefix: Optional[str] = None, generator:
                                                           Optional[Union[Faker, Generator,
                                                           Provider]] = None, max_nb_chars: int =
                                                           DEFAULT_TEXT_MAX_NB_CHARS,
                                                           wrap_chars_after: Optional[int] =
                                                           None, content: Optional[str] = None,
                                                           title: Optional[str] = None,
                                                           chapter_title: Optional[str] = None,
                                                           raw: bool = True, **kwargs) →
                                                           BytesValue
```

```
faker_file.providers.helpers.inner.create_inner epub_file(storage: Optional[BaseStorage] = None,
                                                           prefix: Optional[str] = None, generator:
                                                           Optional[Union[Faker, Generator,
                                                           Provider]] = None, max_nb_chars: int =
                                                           DEFAULT_TEXT_MAX_NB_CHARS,
                                                           wrap_chars_after: Optional[int] =
                                                           None, content: Optional[str] = None,
                                                           title: Optional[str] = None,
                                                           chapter_title: Optional[str] = None,
                                                           **kwargs) → StringValue
```

Create inner EPUB file.

```
faker_file.providers.helpers.inner.create_inner ico_file(storage: Optional[BaseStorage] = None,
                                                          prefix: Optional[str] = None, generator:
                                                          Optional[Union[Faker, Generator,
                                                          Provider]] = None, max_nb_chars: int =
                                                          DEFAULT_IMAGE_MAX_NB_CHARS,
                                                          wrap_chars_after: Optional[int] = None,
                                                          content: Optional[str] = None, raw: bool
                                                          = True, **kwargs) → BytesValue
```

```
faker_file.providers.helpers.inner.create_inner_ico_file(storage: Optional[BaseStorage] = None,  
                                                         prefix: Optional[str] = None, generator:  
                                                         Optional[Union[Faker, Generator,  
Provider]] = None, max_nb_chars: int =  
DEFAULT_IMAGE_MAX_NB_CHARS,  
wrap_chars_after: Optional[int] = None,  
content: Optional[str] = None, **kwargs)  
→ StringValue
```

Create inner ICO file.

```
faker_file.providers.helpers.inner.create_inner_jpeg_file(storage: Optional[BaseStorage] = None,  
                                                           prefix: Optional[str] = None, generator:  
                                                           Optional[Union[Faker, Generator,  
Provider]] = None, max_nb_chars: int =  
DEFAULT_IMAGE_MAX_NB_CHARS,  
wrap_chars_after: Optional[int] =  
None, content: Optional[str] = None,  
raw: bool = True, **kwargs) →  
BytesValue
```

```
faker_file.providers.helpers.inner.create_inner_jpeg_file(storage: Optional[BaseStorage] = None,  
                                                           prefix: Optional[str] = None, generator:  
                                                           Optional[Union[Faker, Generator,  
Provider]] = None, max_nb_chars: int =  
DEFAULT_IMAGE_MAX_NB_CHARS,  
wrap_chars_after: Optional[int] =  
None, content: Optional[str] = None,  
**kwargs) → StringValue
```

Create inner JPEG file.

```
faker_file.providers.helpers.inner.create_inner_mp3_file(storage: Optional[BaseStorage] = None,  
                                                           prefix: Optional[str] = None, generator:  
                                                           Optional[Union[Faker, Generator,  
Provider]] = None, max_nb_chars: int =  
DEFAULT_AUDIO_MAX_NB_CHARS,  
content: Optional[str] = None,  
mp3_generator_cls:  
Optional[Type[BaseMp3Generator]] =  
None, mp3_generator_kwargs:  
Optional[Dict[str, Any]] = None, raw:  
bool = True, **kwargs) → BytesValue
```

```
faker_file.providers.helpers.inner.create_inner_mp3_file(storage: Optional[BaseStorage] = None,  
                                                           prefix: Optional[str] = None, generator:  
                                                           Optional[Union[Faker, Generator,  
Provider]] = None, max_nb_chars: int =  
DEFAULT_AUDIO_MAX_NB_CHARS,  
content: Optional[str] = None,  
mp3_generator_cls:  
Optional[Type[BaseMp3Generator]] =  
None, mp3_generator_kwargs:  
Optional[Dict[str, Any]] = None,  
**kwargs) → StringValue
```

Create inner ODS file.

```
faker_file.providers.helpers.inner.create_inner_odp_file(storage: Optional[BaseStorage] = None,
                                                         prefix: Optional[str] = None, generator:
                                                         Optional[Union[Faker, Generator,
                                                         Provider]] = None, max_nb_chars: int =
                                                         DEFAULT_TEXT_MAX_NB_CHARS,
                                                         wrap_chars_after: Optional[int] = None,
                                                         content: Optional[str] = None, raw: bool
                                                         = True, **kwargs) → BytesValue
```

```
faker_file.providers.helpers.inner.create_inner_odp_file(storage: Optional[BaseStorage] = None,
                                                         prefix: Optional[str] = None, generator:
                                                         Optional[Union[Faker, Generator,
                                                         Provider]] = None, max_nb_chars: int =
                                                         DEFAULT_TEXT_MAX_NB_CHARS,
                                                         wrap_chars_after: Optional[int] = None,
                                                         content: Optional[str] = None, **kwargs)
                                                         → Union[BytesValue, StringValue]
```

Create inner ODP file.

```
faker_file.providers.helpers.inner.create_inner_ods_file(storage: Optional[BaseStorage] = None,
                                                         prefix: Optional[str] = None, generator:
                                                         Optional[Union[Faker, Generator,
                                                         Provider]] = None, data_columns:
                                                         Optional[Dict[str, str]] = None,
                                                         num_rows: int = 10, content:
                                                         Optional[str] = None, raw: bool = True,
                                                         **kwargs) → BytesValue
```

```
faker_file.providers.helpers.inner.create_inner_ods_file(storage: Optional[BaseStorage] = None,
                                                         prefix: Optional[str] = None, generator:
                                                         Optional[Union[Faker, Generator,
                                                         Provider]] = None, data_columns:
                                                         Optional[Dict[str, str]] = None,
                                                         num_rows: int = 10, content:
                                                         Optional[str] = None, **kwargs) →
                                                         StringValue
```

Create inner ODS file.

```
faker_file.providers.helpers.inner.create_inner_odt_file(storage: Optional[BaseStorage] = None,
                                                         prefix: Optional[str] = None, generator:
                                                         Optional[Union[Faker, Generator,
                                                         Provider]] = None, max_nb_chars: int =
                                                         DEFAULT_TEXT_MAX_NB_CHARS,
                                                         wrap_chars_after: Optional[int] = None,
                                                         content: Optional[str] = None, raw: bool
                                                         = True, **kwargs) → BytesValue
```

```
faker_file.providers.helpers.inner.create_inner_odt_file(storage: Optional[BaseStorage] = None,
                                                         prefix: Optional[str] = None, generator:
                                                         Optional[Union[Faker, Generator,
                                                         Provider]] = None, max_nb_chars: int =
                                                         DEFAULT_TEXT_MAX_NB_CHARS,
                                                         wrap_chars_after: Optional[int] = None,
                                                         content: Optional[str] = None, **kwargs)
                                                         → StringValue
```

Create inner ODT file.

```
faker_file.providers.helpers.inner.create_inner_pdf_file(storage: Optional[BaseStorage] = None,  
                                                         prefix: Optional[str] = None, generator:  
                                                         Optional[Union[Faker, Generator,  
Provider]] = None, max_nb_chars: int =  
DEFAULT_TEXT_MAX_NB_CHARS,  
wrap_chars_after: Optional[int] = None,  
content: Optional[str] = None, raw: bool  
= True, **kwargs) → BytesValue
```

```
faker_file.providers.helpers.inner.create_inner_pdf_file(storage: Optional[BaseStorage] = None,  
                                                         prefix: Optional[str] = None, generator:  
                                                         Optional[Union[Faker, Generator,  
Provider]] = None, max_nb_chars: int =  
DEFAULT_TEXT_MAX_NB_CHARS,  
wrap_chars_after: Optional[int] = None,  
content: Optional[str] = None, **kwargs)  
→ StringValue
```

Create inner PDF file.

```
faker_file.providers.helpers.inner.create_inner_png_file(storage: Optional[BaseStorage] = None,  
                                                         prefix: Optional[str] = None, generator:  
                                                         Optional[Union[Faker, Generator,  
Provider]] = None, max_nb_chars: int =  
DEFAULT_IMAGE_MAX_NB_CHARS,  
wrap_chars_after: Optional[int] = None,  
content: Optional[str] = None, raw: bool  
= True, **kwargs) → BytesValue
```

```
faker_file.providers.helpers.inner.create_inner_png_file(storage: Optional[BaseStorage] = None,  
                                                         prefix: Optional[str] = None, generator:  
                                                         Optional[Union[Faker, Generator,  
Provider]] = None, max_nb_chars: int =  
DEFAULT_IMAGE_MAX_NB_CHARS,  
wrap_chars_after: Optional[int] = None,  
content: Optional[str] = None, **kwargs)  
→ StringValue
```

Create inner PNG file.

```
faker_file.providers.helpers.inner.create_inner_pptx_file(storage: Optional[BaseStorage] = None,  
                                                         prefix: Optional[str] = None, generator:  
                                                         Optional[Union[Faker, Generator,  
Provider]] = None, max_nb_chars: int =  
DEFAULT_TEXT_MAX_NB_CHARS,  
wrap_chars_after: Optional[int] =  
None, content: Optional[str] = None,  
raw: bool = True, **kwargs) →  
BytesValue
```

```
faker_file.providers.helpers.inner.create_inner_pptx_file(storage: Optional[BaseStorage] = None,  
                                                         prefix: Optional[str] = None, generator:  
                                                         Optional[Union[Faker, Generator,  
Provider]] = None, max_nb_chars: int =  
DEFAULT_TEXT_MAX_NB_CHARS,  
wrap_chars_after: Optional[int] =  
None, content: Optional[str] = None,  
**kwargs) → StringValue
```


Create inner PPTX file.

```
faker_file.providers.helpers.inner.create_inner_rtf_file(storage: Optional[BaseStorage] = None,
                                                         prefix: Optional[str] = None, generator:
                                                         Optional[Union[Faker, Generator,
                                                         Provider]] = None, max_nb_chars: int =
                                                         DEFAULT_TEXT_MAX_NB_CHARS,
                                                         wrap_chars_after: Optional[int] = None,
                                                         content: Optional[str] = None, raw: bool
                                                         = True, **kwargs) → BytesValue
```

```
faker_file.providers.helpers.inner.create_inner_rtf_file(storage: Optional[BaseStorage] = None,
                                                         prefix: Optional[str] = None, generator:
                                                         Optional[Union[Faker, Generator,
                                                         Provider]] = None, max_nb_chars: int =
                                                         DEFAULT_TEXT_MAX_NB_CHARS,
                                                         wrap_chars_after: Optional[int] = None,
                                                         content: Optional[str] = None, **kwargs)
                                                         → StringValue
```

Create inner RTF file.

```
faker_file.providers.helpers.inner.create_inner_svg_file(storage: Optional[BaseStorage] = None,
                                                         prefix: Optional[str] = None, generator:
                                                         Optional[Union[Faker, Generator,
                                                         Provider]] = None, max_nb_chars: int =
                                                         DEFAULT_IMAGE_MAX_NB_CHARS,
                                                         wrap_chars_after: Optional[int] = None,
                                                         content: Optional[str] = None, raw: bool
                                                         = True, **kwargs) → BytesValue
```

```
faker_file.providers.helpers.inner.create_inner_svg_file(storage: Optional[BaseStorage] = None,
                                                         prefix: Optional[str] = None, generator:
                                                         Optional[Union[Faker, Generator,
                                                         Provider]] = None, max_nb_chars: int =
                                                         DEFAULT_IMAGE_MAX_NB_CHARS,
                                                         wrap_chars_after: Optional[int] = None,
                                                         content: Optional[str] = None, **kwargs)
                                                         → StringValue
```

Create inner SVG file.

```
faker_file.providers.helpers.inner.create_inner_tar_file(storage: Optional[BaseStorage] = None,
                                                         prefix: Optional[str] = None, generator:
                                                         Optional[Union[Faker, Generator,
                                                         Provider]] = None, options:
                                                         Optional[Dict[str, Any]] = None,
                                                         compression: Optional[str] = None, raw:
                                                         bool = True, **kwargs) → BytesValue
```

```
faker_file.providers.helpers.inner.create_inner_tar_file(storage: Optional[BaseStorage] = None,
                                                         prefix: Optional[str] = None, generator:
                                                         Optional[Union[Faker, Generator,
                                                         Provider]] = None, options:
                                                         Optional[Dict[str, Any]] = None,
                                                         compression: Optional[str] = None,
                                                         **kwargs) → StringValue
```

Create inner TAR file.

```
faker_file.providers.helpers.inner.create_inner_txt_file(storage: Optional[BaseStorage] = None,  
                                                         prefix: Optional[str] = None, generator:  
                                                         Optional[Union[Faker, Generator,  
Provider]] = None, max_nb_chars: int =  
DEFAULT_TEXT_MAX_NB_CHARS,  
wrap_chars_after: Optional[int] = None,  
content: Optional[str] = None, raw: bool  
= True, **kwargs) → BytesValue
```

```
faker_file.providers.helpers.inner.create_inner_txt_file(storage: Optional[BaseStorage] = None,  
                                                         prefix: Optional[str] = None, generator:  
                                                         Optional[Union[Faker, Generator,  
Provider]] = None, max_nb_chars: int =  
DEFAULT_TEXT_MAX_NB_CHARS,  
wrap_chars_after: Optional[int] = None,  
content: Optional[str] = None, **kwargs)  
→ StringValue
```

Create inner TXT file.

```
faker_file.providers.helpers.inner.create_inner_webp_file(storage: Optional[BaseStorage] = None,  
                                                           prefix: Optional[str] = None, generator:  
                                                           Optional[Union[Faker, Generator,  
Provider]] = None, max_nb_chars: int =  
DEFAULT_IMAGE_MAX_NB_CHARS,  
wrap_chars_after: Optional[int] =  
None, content: Optional[str] = None,  
raw: bool = True, **kwargs) →  
BytesValue
```

```
faker_file.providers.helpers.inner.create_inner_webp_file(storage: Optional[BaseStorage] = None,  
                                                           prefix: Optional[str] = None, generator:  
                                                           Optional[Union[Faker, Generator,  
Provider]] = None, max_nb_chars: int =  
DEFAULT_IMAGE_MAX_NB_CHARS,  
wrap_chars_after: Optional[int] =  
None, content: Optional[str] = None,  
**kwargs) → StringValue
```

Create inner WEBP file.

```
faker_file.providers.helpers.inner.create_inner_xlsx_file(storage: Optional[BaseStorage] = None,  
                                                           prefix: Optional[str] = None, generator:  
                                                           Optional[Union[Faker, Generator,  
Provider]] = None, data_columns:  
Optional[Dict[str, str]] = None,  
num_rows: int = 10, content:  
Optional[str] = None, raw: bool = True,  
**kwargs) → BytesValue
```

```
faker_file.providers.helpers.inner.create_inner_xlsx_file(storage: Optional[BaseStorage] = None,  
                                                           prefix: Optional[str] = None, generator:  
                                                           Optional[Union[Faker, Generator,  
Provider]] = None, data_columns:  
Optional[Dict[str, str]] = None,  
num_rows: int = 10, content:  
Optional[str] = None, **kwargs) →  
StringValue
```

Create inner XLSX file.

```
faker_file.providers.helpers.inner.create_inner_zip_file(storage: Optional[BaseStorage] = None,
                                                         prefix: Optional[str] = None, generator:
                                                         Optional[Union[Faker, Generator,
                                                         Provider]] = None, options:
                                                         Optional[Dict[str, Any]] = None, raw:
                                                         bool = True, **kwargs) → BytesValue
```

```
faker_file.providers.helpers.inner.create_inner_zip_file(storage: Optional[BaseStorage] = None,
                                                         prefix: Optional[str] = None, generator:
                                                         Optional[Union[Faker, Generator,
                                                         Provider]] = None, options:
                                                         Optional[Dict[str, Any]] = None,
                                                         **kwargs) → StringValue
```

Create inner ZIP file.

```
faker_file.providers.helpers.inner.fuzzy_choice_create_inner_file(func_choices:
                                                                    List[Tuple[Callable, Dict[str,
                                                                    Any]]], **kwargs) →
                                                                    StringValue
```

Create inner file from given list of function choices.

Parameters

func_choices – List of functions to choose from.

Returns

StringValue.

Usage example:

```
from faker import Faker
from faker_file.providers.helpers.inner import (
    create_inner_docx_file, create_inner_epub_file, create_inner_txt_file,
    fuzzy_choice_create_inner_file,
)
from faker_file.storages.filesystem import FileSystemStorage

FAKER = Faker()
STORAGE = FileSystemStorage()

kwargs = {"storage": STORAGE, "generator": FAKER}
file = fuzzy_choice_create_inner_file(
    [
        (create_inner_docx_file, kwargs),
        (create_inner_epub_file, kwargs),
        (create_inner_txt_file, kwargs),
    ]
)
```

You could use it in archives to make a variety of different file types within the archive.

```
from faker import Faker
from faker_file.providers.helpers.inner import (
    create_inner_docx_file, create_inner_epub_file, create_inner_txt_file,
    fuzzy_choice_create_inner_file,
)
from faker_file.providers.zip_file import ZipFileProvider
from faker_file.storages.filesystem import FileSystemStorage

FAKER = Faker()
STORAGE = FileSystemStorage()

kwargs = {"storage": STORAGE, "generator": FAKER}
file = ZipFileProvider(FAKER).zip_file(
```

```
    prefix="zzz_archive_", options={
        "count": 50, "create_inner_file_func": fuzzy_choice_create_inner_file, "create_inner_file_args": {
            "func_choices": [
                (create_inner_docx_file, kwargs), (create_inner_epub_file, kwargs), (create_inner_txt_file, kwargs),
            ],
        }, "directory": "zzz",
    }
)
```

13.7.1.1.1.18 Module contents

13.7.1.1.1.19 `faker_file.providers.mixins` package

13.7.1.1.1.20 Submodules

13.7.1.1.1.21 `faker_file.providers.mixins.image_mixin` module

```
class faker_file.providers.mixins.image_mixin.ImageMixin
    Bases: FileMixin
    Image mixin.
    extension: str
    formats: List[str]
    generator: Union[Faker, Generator, Provider]
    numerify: Callable
    random_element: Callable
```

13.7.1.1.1.22 `faker_file.providers.mixins.tablular_data_mixin` module

```
class faker_file.providers.mixins.tablular_data_mixin.TabularDataMixin
    Bases: FileMixin
    Tabular data mixin.
    extension: str
    formats: List[str]
    generator: Union[Faker, Generator, Provider]
    numerify: Callable
    random_element: Callable
```

13.7.1.1.1.23 Module contents

13.7.1.1.1.24 `faker_file.providers.mp3_file` package

13.7.1.1.1.25 Subpackages

13.7.1.1.1.26 `faker_file.providers.mp3_file.generators` package

13.7.1.1.1.27 Submodules

13.7.1.1.1.28 `faker_file.providers.mp3_file.generators.base` module

13.7.1.1.1.29 `faker_file.providers.mp3_file.generators.edge_tts_generator` module

```
class faker_file.providers.mp3_file.generators.edge_tts_generator.EdgeTtsMp3Generator(content:
                                                                    str,
                                                                    gen-
                                                                    era-
                                                                    tor:
                                                                    Union[Faker,
                                                                    Gen-
                                                                    era-
                                                                    tor,
                                                                    Provider],
                                                                    **kwargs)
```

Bases: `BaseMp3Generator`

Edge Text-to-Speech generator.

Usage example:

```
from faker import Faker from faker_file.providers.mp3_file import Mp3FileProvider from
faker_file.providers.mp3_file.generators import edge_tts_generator
```

```
FAKER = Faker()
```

```
file = Mp3FileProvider(FAKER).mp3_file(
    mp3_generator_cls=edge_tts_generator.EdgeTtsMp3Generator
)
```

generate(**kwargs) → bytes

Generate MP3.

handle_kwargs(**kwargs) → None

Handle kwargs.

voice: str = 'en-GB-SoniaNeural'

13.7.1.1.1.30 `faker_file.providers.mp3_file.generators.gtts_generator` module

```
class faker_file.providers.mp3_file.generators.gtts_generator.GttsMp3Generator(content: str,  
                                                                           generator:  
                                                                           Union[Faker,  
                                                                           Generator,  
                                                                           Provider],  
                                                                           **kwargs)
```

Bases: `BaseMp3Generator`

Google Text-to-Speech generator.

Usage example:

```
from faker import Faker from faker_file.providers.mp3_file import Mp3FileProvider from  
faker_file.providers.mp3_file.generators.gtts_generator import (  
    GttsMp3Generator,  
)  
FAKER = Faker()  
file = Mp3FileProvider(FAKER).mp3_file(  
    mp3_generator_cls=GttsMp3Generator  
)  
generate(**kwargs) → bytes  
    Generate MP3.  
handle_kwargs(**kwargs) → None  
    Handle kwargs.  
lang: str = 'en'  
tld: str = 'com'
```

13.7.1.1.1.31 Module contents

13.7.1.1.1.32 Module contents

```
class faker_file.providers.mp3_file.Mp3FileProvider(generator: Any)
```

Bases: `BaseProvider`, `FileMixin`

MP3 file provider.

Usage example:

```
from faker import Faker from faker_file.providers.mp3_file import Mp3FileProvider  
FAKER = Faker() file = Mp3FileProvider(FAKER).mp3_file()
```

Usage example with options:

```
file = Mp3FileProvider(FAKER).mp3_file(  
    prefix="zzz", max_nb_chars=500,  
)
```

Usage example with `FileSystemStorage` storage (for *Django*):

```

from django.conf import settings
from faker_file.storages.filesystem import FileSystemStorage

file = Mp3FileProvider(FAKER).mp3_file(
    storage=FileSystemStorage(
        root_path=settings.MEDIA_ROOT, rel_path="tmp",
    ), prefix="zzz", max_nb_chars=500,
)

```

Default MP3 generator class is *GttsMp3Generator* which uses Google Text-to-Speech services to generate an MP3 file from given or randomly generated text. It does not require additional services to run and the only dependency here is the *gtts* package. You can however implement your own custom MP3 generator class and pass it to the *mp3_file* method in *mp3_generator_cls* argument instead of the default *GttsMp3Generator*.

Usage with custom MP3 generator class.

```

# Imaginary marytts Python library from marytts import MaryTTS
# Import BaseMp3Generator from faker_file.providers.base.mp3_generator import (
    BaseMp3Generator,
)

# Define custom MP3 generator class MaryTtsMp3Generator(BaseMp3Generator):
    locale: str = "cmu-rms-hsmm" voice: str = "en_US"

    def handle_kwargs(self, **kwargs) -> None:
        # Since it's impossible to unify all TTS systems it's allowed # to pass arbitrary arguments to the BaseMp3Generator # constructor. Each implementation class contains its own # additional tuning arguments. Check the source code of the # implemented MP3 generators as an example. if "locale" in kwargs:
            self.locale = kwargs["locale"]

        if "voice" in kwargs:
            self.voice = kwargs["voice"]

    def generate(self) -> bytes:
        # Your implementation here. Note, that self.content # in this context is the text to make MP3 from. # self.generator would be the Faker or Generator # instance from which you could extract information on # active locale. # What comes below is pseudo implementation. mary_tts = MaryTTS(locale=self.locale, voice=self.voice) return mary_tts.synth_mp3(self.content)

# Generate MP3 file from random text file = Mp3FileProvider(FAKER).mp3_file(
    mp3_generator_cls=MaryTtsMp3Generator,
)

extension: str = 'mp3'

mp3_file(storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, max_nb_chars: int =
    DEFAULT_AUDIO_MAX_NB_CHARS, content: Optional[str] = None, mp3_generator_cls:
    Optional[Type[BaseMp3Generator]] = GttsMp3Generator, mp3_generator_kwargs:
    Optional[Dict[str, Any]] = None, raw: bool = True, **kwargs) -> BytesValue

```

```
mp3_file(storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, max_nb_chars: int =
    DEFAULT_AUDIO_MAX_NB_CHARS, content: Optional[str] = None, mp3_generator_cls:
    Optional[Type[BaseMp3Generator]] = GttsMp3Generator, mp3_generator_kwargs:
    Optional[Dict[str, Any]] = None, **kwargs) → StringValue
```

Generate a MP3 file with random text.

Parameters

- **storage** – Storage. Defaults to *FileSystemStorage*.
- **prefix** – File name prefix.
- **max_nb_chars** – Max number of chars for the content.
- **content** – File content. Might contain dynamic elements, which are then replaced by correspondent fixtures.
- **mp3_generator_cls** – Mp3 generator class.
- **mp3_generator_kwargs** – Mp3 generator kwargs.
- **raw** – If set to True, return *BytesValue* (binary content of the file). Otherwise, return *StringValue* (path to the saved file).

Returns

Relative path (from root directory) of the generated file or raw content of the file.

13.7.1.1.1.33 Submodules

13.7.1.1.1.34 `faker_file.providers.bin_file` module

```
class faker_file.providers.bin_file.BinFileProvider(generator: Any)
```

Bases: *BaseProvider*, *FileMixin*

BIN file provider.

Usage example:

```
from faker import Faker
from faker_file.providers.bin_file import BinFileProvider

file = BinFileProvider(Faker()).bin_file()
```

Usage example with options:

```
file = BinFileProvider(Faker()).bin_file(
    prefix="zzz", length=1024**2,
)
```

Usage example with *FileSystemStorage* storage (for *Django*):

```
from django.conf import settings
from faker_file.storages.filesystem import FileSystemStorage

file = BinFileProvider(Faker()).bin_file(
    storage=FileSystemStorage(
        root_path=settings.MEDIA_ROOT, rel_path="tmp",
    ), prefix="zzz", length=1024**2,
)
```

Usage example with AWS S3 storage:


```

from faker_file.storages.aws_s3 import AWSS3Storage

file = BinFileProvider(Faker()).bin_file(
    storage=AWSS3Storage(bucket_name="My-test-bucket"), prefix="zzz", length=1024**2,
)

bin_file(storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, length: int = 1 * 1024 *
1024, content: Optional[bytes] = None, raw: bool = True, **kwargs) → BytesValue
bin_file(storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, length: int = 1 * 1024 *
1024, content: Optional[bytes] = None, **kwargs) → StringValue

Generate a CSV file with random text.

```

Parameters

- **storage** – Storage class. Defaults to *FileSystemStorage*.
- **prefix** – File name prefix.
- **length** –
- **content** – File content. If given, used as is.
- **raw** – If set to True, return *BytesValue* (binary content of the file). Otherwise, return *StringValue* (path to the saved file).

Returns

Relative path (from root directory) of the generated file or raw content of the file.

extension: str = 'bin'

13.7.1.1.1.35 faker_file.providers.csv_file module

class faker_file.providers.csv_file.CsvFileProvider(generator: Any)

Bases: BaseProvider, *FileMixin*

CSV file provider.

Usage example:

```

from faker import Faker
from faker_file.providers.csv_file import CsvFileProvider

file = CsvFileProvider(Faker()).csv_file()

```

Usage example with options:

```

from faker_file.providers.csv_file import CsvFileProvider

file = CsvFileProvider(Faker()).csv_file(
    prefix="zzz", num_rows=100, data_columns=('{{name}}', '{{sentence}}', '{{address}}'),
    include_row_ids=True,
)

```

Usage example with *FileSystemStorage* storage (for *Django*):

```

from django.conf import settings
from faker_file.storages.filesystem import FileSystemStorage

file = CsvFileProvider(Faker()).csv_file(
    storage=FileSystemStorage(
        root_path=settings.MEDIA_ROOT, rel_path="tmp",
    ), prefix="zzz", num_rows=100,
)

```

```
)  
  
csv_file(storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, header:  
    Optional[Sequence[str]] = None, data_columns: Tuple[str, ...] = ('{{name}}', '{{address}}'),  
    num_rows: int = 10, include_row_ids: bool = False, content: Optional[str] = None, encoding:  
    Optional[str] = None, raw: bool = True, **kwargs) → BytesValue  
  
csv_file(storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, header:  
    Optional[Sequence[str]] = None, data_columns: Tuple[str, ...] = ('{{name}}', '{{address}}'),  
    num_rows: int = 10, include_row_ids: bool = False, content: Optional[str] = None, encoding:  
    Optional[str] = None, **kwargs) → StringValue
```

Generate a CSV file with random text.

Parameters

- **storage** – Storage. Defaults to *FileSystemStorage*.
- **prefix** – File name prefix.
- **header** – The header argument expects a list or a tuple of strings that will serve as the header row if supplied.
- **data_columns** – The data_columns argument expects a list or a tuple of string tokens, and these string tokens will be passed to `pystr_format()` for data generation. Argument Groups are used to pass arguments to the provider methods. Both header and data_columns must be of the same length.
- **num_rows** – The num_rows argument controls how many rows of data to generate, and the include_row_ids argument may be set to `True` to include a sequential row ID column.
- **include_row_ids** –
- **content** – File content. If given, used as is.
- **encoding** – Encoding.
- **raw** – If set to `True`, return *BytesValue* (binary content of the file). Otherwise, return *StringValue* (path to the saved file).

Returns

Relative path (from root directory) of the generated file or raw content of the file.

extension: `str = 'csv'`

13.7.1.1.136 faker_file.providers.docx_file module

```
class faker_file.providers.docx_file.DocxFileProvider(generator: Any)
```

Bases: `BaseProvider`, `FileMixin`

DOCX file provider.

Usage example:

```
from faker import Faker  
from faker_file.providers.docx_file import DocxFileProvider  
  
file = DocxFileProvider(Faker()).docx_file()
```

Usage example with options:

```
file = DocxFileProvider(Faker()).docx_file(  
    prefix="zzz", max_nb_chars=100_000, wrap_chars_after=80,  
)
```

Usage example with *FileSystemStorage* storage (for *Django*):

```
from django.conf import settings from faker_file.storages.filesystem import FileSystemStorage

file = DocxFileProvider(Faker()).docx_file(
    storage=FileSystemStorage(
        root_path=settings.MEDIA_ROOT, rel_path="tmp",
    ), prefix="zzz", max_nb_chars=100_000, wrap_chars_after=80,
)

docx_file(storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, max_nb_chars: int =
    DEFAULT_TEXT_MAX_NB_CHARS, wrap_chars_after: Optional[int] = None, content:
    Optional[str] = None, raw: bool = True, **kwargs) → BytesValue

docx_file(storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, max_nb_chars: int =
    DEFAULT_TEXT_MAX_NB_CHARS, wrap_chars_after: Optional[int] = None, content:
    Optional[str] = None, **kwargs) → StringValue
```

Generate a DOCX file with random text.

Parameters

- **storage** – Storage. Defaults to *FileSystemStorage*.
- **prefix** – File name prefix.
- **max_nb_chars** – Max number of chars for the content.
- **wrap_chars_after** – If given, the output string would be separated by line breaks after the given position.
- **content** – File content. Might contain dynamic elements, which are then replaced by correspondent fixtures.
- **raw** – If set to True, return *BytesValue* (binary content of the file). Otherwise, return *StringValue* (path to the saved file).

Returns

Relative path (from root directory) of the generated file or raw content of the file.

extension: `str = 'docx'`

13.7.1.1.1.37 faker_file.providers.eml_file module

class `faker_file.providers.eml_file.EmlFileProvider(generator: Any)`

Bases: `BaseProvider`, `FileMixin`

EML file provider.

Usage example:

```
from faker import Faker from faker_file.providers.eml_file import EmlFileProvider

FAKER = Faker()

file = EmlFileProvider(FAKER).eml_file()
```

Usage example with attachments:

```
from faker_file.providers.helpers.inner import create_inner_docx_file from
faker_file.providers.eml_file import EmlFileProvider
```

```
file = EmlFileProvider(FAKER).eml_file(
    prefix="zzz_email_", options={
        "count": 5, "create_inner_file_func": create_inner_docx_file, "create_inner_file_args":
        {
            "prefix": "zzz_docx_file_", "max_nb_chars": 1_024,
        },
    }
)
```

Usage example of nested EMLs attachments:

```
from faker_file.providers.helpers.inner import create_inner_eml_file

file = EmlFileProvider(FAKER).eml_file(
    options={
        "create_inner_file_func": create_inner_eml_file, "create_inner_file_args": {
            "options": {
                "create_inner_file_func": create_inner_docx_file,
            }
        }
    }
)
```

If you want to see, which files were included inside the EML, check the `file.data["files"]`.

eml_file(*storage*: *Optional*[[BaseStorage](#)] = *None*, *prefix*: *Optional*[*str*] = *None*, *options*: *Optional*[*Dict*[*str*, *Any*]] = *None*, *max_nb_chars*: *int* = *DEFAULT_TEXT_MAX_NB_CHARS*, *wrap_chars_after*: *Optional*[*int*] = *None*, *content*: *Optional*[*str*] = *None*, *raw*: *bool* = *True*, ***kwargs*) → [BytesValue](#)

eml_file(*storage*: *Optional*[[BaseStorage](#)] = *None*, *prefix*: *Optional*[*str*] = *None*, *options*: *Optional*[*Dict*[*str*, *Any*]] = *None*, *max_nb_chars*: *int* = *DEFAULT_TEXT_MAX_NB_CHARS*, *wrap_chars_after*: *Optional*[*int*] = *None*, *content*: *Optional*[*str*] = *None*, ***kwargs*) → [StringValue](#)

Generate an EML file with random text.

Parameters

- **storage** – Storage. Defaults to *FileSystemStorage*.
- **prefix** – File name prefix.
- **options** – Options (non-structured) for complex types, such as ZIP.
- **max_nb_chars** – Max number of chars for the content.
- **wrap_chars_after** – If given, the output string would be separated by line breaks after the given position.
- **content** – File content. Might contain dynamic elements, which are then replaced by correspondent fixtures.
- **raw** – If set to *True*, return *BytesValue* (binary content of the file). Otherwise, return *StringValue* (path to the saved file).

Returns

Relative path (from root directory) of the generated file or raw content of the file.

```
extension: str = 'eml'
```

13.7.1.1.1.38 faker_file.providers.epub_file module

class `faker_file.providers.epub_file.EpubFileProvider(generator: Any)`

Bases: `BaseProvider`, `FileMixin`

EPUB file provider.

Usage example:

```
from faker import Faker
from faker_file.providers.epub_file import EpubFileProvider

file = EpubFileProvider(Faker()).epub_file()
```

Usage example with options:

```
file = EpubFileProvider(Faker()).epub_file(
    prefix="zzz", max_nb_chars=100_000, wrap_chars_after=80,
)
```

Usage example with `FileSystemStorage` storage (for *Django*):

```
from django.conf import settings
from faker_file.storages.filesystem import FileSystemStorage

file = EpubFileProvider(Faker()).epub_file(
    storage=FileSystemStorage(
        root_path=settings.MEDIA_ROOT, rel_path="tmp",
    ), prefix="zzz", max_nb_chars=100_000, wrap_chars_after=80,
)
```

epub_file(*storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, max_nb_chars: int = DEFAULT_TEXT_MAX_NB_CHARS, wrap_chars_after: Optional[int] = None, content: Optional[str] = None, title: Optional[str] = None, chapter_title: Optional[str] = None, raw: bool = True, **kwargs*) → *BytesValue*

epub_file(*storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, max_nb_chars: int = DEFAULT_TEXT_MAX_NB_CHARS, wrap_chars_after: Optional[int] = None, content: Optional[str] = None, title: Optional[str] = None, chapter_title: Optional[str] = None, **kwargs*) → *StringValue*

Generate a EPUB file with random text.

Parameters

- **storage** – Storage. Defaults to *FileSystemStorage*.
- **prefix** – File name prefix.
- **max_nb_chars** – Max number of chars for the content.
- **wrap_chars_after** – If given, the output string would be separated by line breaks after the given position.
- **content** – File content. Might contain dynamic elements, which are then replaced by correspondent fixtures.
- **title** – E-book title. Might contain dynamic elements, which are then replaced by correspondent fixtures.

- **chapter_title** – Chapter title. Might contain dynamic elements, which are then replaced by correspondent fixtures.
- **raw** – If set to True, return *BytesValue* (binary content of the file). Otherwise, return *StringValue* (path to the saved file).

Returns

Relative path (from root directory) of the generated file or raw content of the file.

extension: `str = 'epub'`

13.7.1.1.1.39 `faker_file.providers.ico_file` module

class `faker_file.providers.ico_file.IcoFileProvider(generator: Any)`

Bases: `BaseProvider`, `ImageMixin`

ICO file provider.

Usage example:

```
from faker import Faker
from faker_file.providers.png_file import IcoFileProvider

file = IcoFileProvider(Faker()).ico_file()
```

Usage example with options:

```
file = IcoFileProvider(Faker()).ico_file(
    prefix="zzz", max_nb_chars=100_000, wrap_chars_after=80,
)
```

Usage example with *FileSystemStorage* storage (for *Django*):

```
from django.conf import settings
from faker_file.storages.filesystem import FileSystemStorage

file = IcoFileProvider(Faker()).ico_file(
    storage=FileSystemStorage(
        root_path=settings.MEDIA_ROOT, rel_path="tmp",
    ), prefix="zzz", max_nb_chars=100_000, wrap_chars_after=80,
)
```

extension: `str = 'ico'`

ico_file(*storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, max_nb_chars: int = DEFAULT_IMAGE_MAX_NB_CHARS, wrap_chars_after: Optional[int] = None, content: Optional[str] = None, raw: bool = True, **kwargs*) → *BytesValue*

ico_file(*storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, max_nb_chars: int = DEFAULT_IMAGE_MAX_NB_CHARS, wrap_chars_after: Optional[int] = None, content: Optional[str] = None, **kwargs*) → *StringValue*

Generate an ICO file with random text.

Parameters

- **storage** – Storage. Defaults to *FileSystemStorage*.
- **prefix** – File name prefix.
- **max_nb_chars** – Max number of chars for the content.

- **wrap_chars_after** – If given, the output string would be separated by line breaks after the given position.
- **content** – File content. Might contain dynamic elements, which are then replaced by correspondent fixtures.
- **raw** – If set to True, return *BytesValue* (binary content of the file). Otherwise, return *StringValue* (path to the saved file).

Returns

Relative path (from root directory) of the generated file or raw content of the file.

13.7.1.1.1.40 faker_file.providers.jpeg_file module

class `faker_file.providers.jpeg_file.JpegFileProvider(generator: Any)`

Bases: `BaseProvider`, `ImageMixin`

JPEG file provider.

Usage example:

```
from faker import Faker
from faker_file.providers.jpeg_file import JpegFileProvider

file = JpegFileProvider(None).jpeg_file()
```

Usage example with options:

```
file = JpegFileProvider(None).jpeg_file(
    prefix="zzz", max_nb_chars=100_000, wrap_chars_after=80,
)
```

Usage example with *FileSystemStorage* storage (for *Django*):

```
from django.conf import settings
from faker_file.storages.filesystem import FileSystemStorage

file = JpegFileProvider(Faker()).jpeg_file(
    storage=FileSystemStorage(
        root_path=settings.MEDIA_ROOT, rel_path="tmp",
    ), prefix="zzz", max_nb_chars=100_000, wrap_chars_after=80,
)
```

extension: `str = 'jpg'`

jpeg_file(storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, max_nb_chars: int = DEFAULT_IMAGE_MAX_NB_CHARS, wrap_chars_after: Optional[int] = None, content: Optional[str] = None, raw: bool = True, **kwargs) → *BytesValue*

jpeg_file(storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, max_nb_chars: int = DEFAULT_IMAGE_MAX_NB_CHARS, wrap_chars_after: Optional[int] = None, content: Optional[str] = None, **kwargs) → *StringValue*

Generate a JPEG file with random text.

Parameters

- **storage** – Storage. Defaults to *FileSystemStorage*.
- **prefix** – File name prefix.
- **max_nb_chars** – Max number of chars for the content.

- **wrap_chars_after** – If given, the output string would be separated by line breaks after the given position.
- **content** – File content. Might contain dynamic elements, which are then replaced by correspondent fixtures.
- **raw** – If set to True, return *BytesValue* (binary content of the file). Otherwise, return *StringValue* (path to the saved file).

Returns

Relative path (from root directory) of the generated file or raw content of the file.

13.7.1.1.1.41 `faker_file.providers.odp_file` module

class `faker_file.providers.odp_file.OdpFileProvider(generator: Any)`

Bases: `BaseProvider`, `FileMixin`

ODP file provider.

Usage example:

```
from faker import Faker
from faker_file.providers.odp_file import OdpFileProvider

FAKER = Faker()

file = OdpFileProvider(FAKER).odp_file()
```

Usage example with options:

```
file = OdpFileProvider(FAKER).odp_file(
    prefix="zzz", max_nb_chars=100_000, wrap_chars_after=80,
)
```

Usage example with *FileSystemStorage* storage (for *Django*):

```
from django.conf import settings
from faker_file.storages.filesystem import FileSystemStorage

file = OdpFileProvider(FAKER).odp_file(
    storage=FileSystemStorage(
        root_path=settings.MEDIA_ROOT, rel_path="tmp",
    ), prefix="zzz", max_nb_chars=100_000, wrap_chars_after=80,
)
```

extension: `str = 'odp'`

odp_file(*storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, max_nb_chars: int = DEFAULT_TEXT_MAX_NB_CHARS, wrap_chars_after: Optional[int] = None, content: Optional[str] = None, raw: bool = True, **kwargs*) → *BytesValue*

odp_file(*storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, max_nb_chars: int = DEFAULT_TEXT_MAX_NB_CHARS, wrap_chars_after: Optional[int] = None, content: Optional[str] = None, **kwargs*) → *StringValue*

Generate an ODP file with random text.

Parameters

- **storage** – Storage. Defaults to *FileSystemStorage*.
- **prefix** – File name prefix.

- **max_nb_chars** – Max number of chars for the content.
- **wrap_chars_after** – If given, the output string would be separated by line breaks after the given position.
- **content** – File content. Might contain dynamic elements, which are then replaced by correspondent fixtures.
- **raw** – If set to True, return *BytesValue* (binary content of the file). Otherwise, return *StringValue* (path to the saved file).

Returns

Relative path (from root directory) of the generated file or raw content of the file.

13.7.1.1.1.42 `faker_file.providers.ods_file` module

class `faker_file.providers.ods_file.OdsFileProvider(generator: Any)`

Bases: `BaseProvider`, `TabularDataMixin`

ODS file provider.

Usage example:

```
from faker import Faker
from faker_file.providers.ods_file import OdsFileProvider

file = OdsFileProvider(Faker()).ods_file()
```

Usage example with options:

```
from faker import Faker
from faker_file.providers.ods_file import OdsFileProvider

file = OdsFileProvider(Faker()).ods_file(
    prefix="zzz", num_rows=100, data_columns={
        "name": "{{name}}", "residency": "{{address}}",
    }, include_row_ids=True,
)
```

Usage example with `FileSystemStorage` storage (for *Django*):

```
from django.conf import settings
from faker_file.storages.filesystem import FileSystemStorage

file = OdsFileProvider(Faker()).ods_file(
    storage=FileSystemStorage(
        root_path=settings.MEDIA_ROOT, rel_path="tmp",
    ), prefix="zzz", num_rows=100, data_columns={
        "name": "{{name}}", "residency": "{{address}}",
    }, include_row_ids=True,
)
```

extension: `str = 'ods'`

ods_file(*storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, data_columns: Optional[Dict[str, str]] = None, num_rows: int = 10, content: Optional[str] = None, raw: bool = True, **kwargs*) → *BytesValue*

```
ods_file(storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, data_columns:
Optional[Dict[str, str]] = None, num_rows: int = 10, content: Optional[str] = None, **kwargs)
→ StringValue
```

Generate an ODS file with random text.

Parameters

- **storage** – Storage. Defaults to *FileSystemStorage*.
- **data_columns** – The `data_columns` argument expects a list or a tuple of string tokens, and these string tokens will be passed to `pystr_format()` for data generation. Argument Groups are used to pass arguments to the provider methods. Both `header` and `data_columns` must be of the same length.
- **num_rows** – The `num_rows` argument controls how many rows of data to generate, and the `include_row_ids` argument may be set to `True` to include a sequential row ID column.
- **prefix** – File name prefix.
- **content** – List of dicts with content (JSON-like format). If given, used as is.
- **raw** – If set to `True`, return *BytesValue* (binary content of the file). Otherwise, return *StringValue* (path to the saved file).

Returns

Relative path (from root directory) of the generated file or raw content of the file.

13.7.1.1.1.43 faker_file.providers.odt_file module

```
class faker_file.providers.odt_file.OdtFileProvider(generator: Any)
```

Bases: `BaseProvider`, *FileMixin*

ODT file provider.

Usage example:

```
from faker import Faker
from faker_file.providers.odt_file import OdtFileProvider

FAKER = Faker()

file = OdtFileProvider(FAKER).odt_file()
```

Usage example with options:

```
file = OdtFileProvider(FAKER).odt_file(
    prefix="zzz", max_nb_chars=100_000, wrap_chars_after=80,
)
```

Usage example with *FileSystemStorage* storage (for *Django*):

```
from django.conf import settings
from faker_file.storages.filesystem import FileSystemStorage

file = OdtFileProvider(FAKER).odt_file(
    storage=FileSystemStorage(
        root_path=settings.MEDIA_ROOT, rel_path="tmp",
    ), prefix="zzz", max_nb_chars=100_000, wrap_chars_after=80,
)
```

```
extension: str = 'odt'
```

```
odt_file(storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, max_nb_chars: int =
    DEFAULT_TEXT_MAX_NB_CHARS, wrap_chars_after: Optional[int] = None, content:
    Optional[str] = None, raw: bool = True, **kwargs) → BytesValue
```

```
odt_file(storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, max_nb_chars: int =
    DEFAULT_TEXT_MAX_NB_CHARS, wrap_chars_after: Optional[int] = None, content:
    Optional[str] = None, **kwargs) → StringValue
```

Generate an ODT file with random text.

Parameters

- **storage** – Storage. Defaults to *FileSystemStorage*.
- **prefix** – File name prefix.
- **max_nb_chars** – Max number of chars for the content.
- **wrap_chars_after** – If given, the output string would be separated by line breaks after the given position.
- **content** – File content. Might contain dynamic elements, which are then replaced by correspondent fixtures.
- **raw** – If set to True, return *BytesValue* (binary content of the file). Otherwise, return *StringValue* (path to the saved file).

Returns

Relative path (from root directory) of the generated file or raw content of the file.

13.7.1.1.1.44 faker_file.providers.pdf_file module

```
class faker_file.providers.pdf_file.PdfFileProvider(generator: Any)
```

Bases: *BaseProvider*, *FileMixin*

PDF file provider.

Usage example:

```
from faker_file.providers.pdf_file import PdfFileProvider
file = PdfFileProvider(None).pdf_file()
```

Usage example with options:

```
from faker_file.providers.pdf_file import PdfFileProvider
file = PdfFileProvider(None).pdf_file(
    prefix="zzz", max_nb_chars=100_000, wrap_chars_after=80,
)
```

Usage example with *FileSystemStorage* storage (for *Django*):

```
from django.conf import settings from faker_file.storages.filesystem import FileSystemStorage
file = PdfFileProvider(Faker()).pdf_file(
    storage=FileSystemStorage(
        root_path=settings.MEDIA_ROOT, rel_path="tmp",
    ), prefix="zzz", max_nb_chars=100_000, wrap_chars_after=80,
```

```
)  
  
extension: str = 'pdf'  
  
pdf_file(storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, max_nb_chars: int =  
    DEFAULT_TEXT_MAX_NB_CHARS, wrap_chars_after: Optional[int] = None, content:  
    Optional[str] = None, encoding: Optional[str] = DEFAULT_FILE_ENCODING, raw: bool =  
    True, **kwargs) → BytesValue  
  
pdf_file(storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, max_nb_chars: int =  
    DEFAULT_TEXT_MAX_NB_CHARS, wrap_chars_after: Optional[int] = None, content:  
    Optional[str] = None, encoding: Optional[str] = DEFAULT_FILE_ENCODING, **kwargs) →  
    StringValue
```

Generate a PDF file with random text.

Parameters

- **storage** – Storage. Defaults to *FileSystemStorage*.
- **prefix** – File name prefix.
- **max_nb_chars** – Max number of chars for the content.
- **wrap_chars_after** – If given, the output string would be separated by line breaks after the given position.
- **content** – File content. Might contain dynamic elements, which are then replaced by correspondent fixtures.
- **encoding** – Encoding of the file.
- **raw** – If set to True, return *BytesValue* (binary content of the file). Otherwise, return *StringValue* (path to the saved file).

Returns

Relative path (from root directory) of the generated file or raw content of the file.

13.7.1.1.1.45 `faker_file.providers.png_file` module

```
class faker_file.providers.png_file.PngFileProvider(generator: Any)
```

Bases: *BaseProvider*, *ImageMixin*

PNG file provider.

Usage example:

```
from faker import Faker  
from faker_file.providers.png_file import PngFileProvider  
  
file = PngFileProvider(Faker()).png_file()
```

Usage example with options:

```
file = PngFileProvider(Faker()).png_file(  
    prefix="zzz", max_nb_chars=100_000, wrap_chars_after=80,  
)
```

Usage example with *FileSystemStorage* storage (for *Django*):

```
from django.conf import settings  
from faker_file.storages.filesystem import FileSystemStorage  
  
file = PngFileProvider(Faker()).png_file()
```

```

storage=FileSystemStorage(
    root_path=settings.MEDIA_ROOT, rel_path="tmp",
), prefix="zzz", max_nb_chars=100_000, wrap_chars_after=80,
)
extension: str = 'png'

png_file(storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, max_nb_chars: int =
    DEFAULT_IMAGE_MAX_NB_CHARS, wrap_chars_after: Optional[int] = None, content:
    Optional[str] = None, raw: bool = True, **kwargs) → BytesValue

png_file(storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, max_nb_chars: int =
    DEFAULT_IMAGE_MAX_NB_CHARS, wrap_chars_after: Optional[int] = None, content:
    Optional[str] = None, **kwargs) → StringValue

```

Generate a PNG file with random text.

Parameters

- **storage** – Storage. Defaults to *FileSystemStorage*.
- **prefix** – File name prefix.
- **max_nb_chars** – Max number of chars for the content.
- **wrap_chars_after** – If given, the output string would be separated by line breaks after the given position.
- **content** – File content. Might contain dynamic elements, which are then replaced by correspondent fixtures.
- **raw** – If set to True, return *BytesValue* (binary content of the file). Otherwise, return *StringValue* (path to the saved file).

Returns

Relative path (from root directory) of the generated file or raw content of the file.

13.7.1.1.1.46 faker_file.providers.pptx_file module

```
class faker_file.providers.pptx_file.PptxFileProvider(generator: Any)
```

Bases: *BaseProvider*, *FileMixin*

PPTX file provider.

Usage example:

```

from faker_file.providers.pptx_file import PptxFileProvider
file = PptxFileProvider(None).pptx_file()

```

Usage example with options:

```

from faker_file.providers.pptx_file import PptxFileProvider
file = PptxFileProvider(None).pptx_file(
    prefix="zzz", max_nb_chars=100_000, wrap_chars_after=80,
)

```

Usage example with *FileSystemStorage* storage (for *Django*):

```

from django.conf import settings
from faker_file.storages.filesystem import FileSystemStorage

```

```
file = PptxFileProvider(Faker()).pptx_file(
    storage=FileSystemStorage(
        root_path=settings.MEDIA_ROOT, rel_path="tmp",
    ), prefix="zzz", max_nb_chars=100_000, wrap_chars_after=80,
)

extension: str = 'pptx'

pptx_file(storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, max_nb_chars: int =
    DEFAULT_TEXT_MAX_NB_CHARS, wrap_chars_after: Optional[int] = None, content:
    Optional[str] = None, raw: bool = True, **kwargs) → BytesValue

pptx_file(storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, max_nb_chars: int =
    DEFAULT_TEXT_MAX_NB_CHARS, wrap_chars_after: Optional[int] = None, content:
    Optional[str] = None, **kwargs) → StringValue
```

Generate a file with random text.

Parameters

- **storage** – Storage. Defaults to *FileSystemStorage*.
- **prefix** – File name prefix.
- **max_nb_chars** – Max number of chars for the content.
- **wrap_chars_after** – If given, the output string would be separated by line breaks after the given position.
- **content** – File content. Might contain dynamic elements, which are then replaced by correspondent fixtures.
- **raw** – If set to True, return *BytesValue* (binary content of the file). Otherwise, return *StringValue* (path to the saved file).

Returns

Relative path (from root directory) of the generated file or raw content of the file.

13.7.1.1.1.47 faker_file.providers.random_file_from_dir module

```
class faker_file.providers.random_file_from_dir.RandomFileFromDirProvider(generator: Any)
    Bases: BaseProvider, FileMixin
```

Random file from given directory provider.

Usage example:

```
from faker_file.providers.random_file_from_dir import (
    RandomFileFromDirProvider,
)

file = RandomFileFromDirProvider(None).random_file_from_dir(
    source_dir_path="/tmp/tmp/",
)
```

Usage example with options:

```

from faker_file.providers.random_file_from_dir import (
    RandomFileFromDirProvider,
)

file = RandomFileFromDirProvider(None).random_file_from_dir(
    source_dir_path="/tmp/tmp/", prefix="zzz",
)

extension: str = ''

random_file_from_dir(source_dir_path: str, storage: Optional[BaseStorage] = None, prefix:
    Optional[str] = None, raw: bool = True, **kwargs) → BytesValue
random_file_from_dir(source_dir_path: str, storage: Optional[BaseStorage] = None, prefix:
    Optional[str] = None, **kwargs) → StringValue

```

Pick a random file from given directory.

Parameters

- **source_dir_path** – Source files directory.
- **storage** – Storage. Defaults to *FileSystemStorage*.
- **prefix** – File name prefix.
- **raw** – If set to True, return *BytesValue* (binary content of the file). Otherwise, return *StringValue* (path to the saved file).

Returns

Relative path (from root directory) of the generated file or raw content of the file.

13.7.1.1.148 faker_file.providers.rtf_file module

```
class faker_file.providers.rtf_file.RtfFileProvider(generator: Any)
```

Bases: *BaseProvider*, *FileMixin*

RTF file provider.

Usage example:

```

from faker_file.providers.rtf_file import RtfFileProvider

file = RtfFileProvider(None).rtf_file()

```

Usage example with options:

```

from faker_file.providers.rtf_file import RtfFileProvider

file = RtfFileProvider(None).rtf_file(
    prefix="zzz", max_nb_chars=100_000, wrap_chars_after=80,
)

```

Usage example with *FileSystemStorage* storage (for *Django*):

```

from django.conf import settings from faker_file.storages.filesystem import FileSystemStorage

file = RtfFileProvider(Faker()).rtf_file(
    storage=FileSystemStorage(
        root_path=settings.MEDIA_ROOT, rel_path="tmp",
    ), prefix="zzz", max_nb_chars=100_000, wrap_chars_after=80,
)

```

```
)  
  
extension: str = 'rtf'  
  
rtf_file(storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, max_nb_chars: int =  
    DEFAULT_TEXT_MAX_NB_CHARS, wrap_chars_after: Optional[int] = None, content:  
    Optional[str] = None, raw: bool = True, **kwargs) → BytesValue  
  
rtf_file(storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, max_nb_chars: int =  
    DEFAULT_TEXT_MAX_NB_CHARS, wrap_chars_after: Optional[int] = None, content:  
    Optional[str] = None, **kwargs) → StringValue
```

Generate a RTF file with random text.

Parameters

- **storage** – Storage. Defaults to *FileSystemStorage*.
- **prefix** – File name prefix.
- **max_nb_chars** – Max number of chars for the content.
- **wrap_chars_after** – If given, the output string would be separated by line breaks after the given position.
- **content** – File content. Might contain dynamic elements, which are then replaced by correspondent fixtures.
- **raw** – If set to True, return *BytesValue* (binary content of the file). Otherwise, return *StringValue* (path to the saved file).

Returns

Relative path (from root directory) of the generated file or raw content of the file.

13.7.1.1.1.49 faker_file.providers.svg_file module

```
class faker_file.providers.svg_file.SvgFileProvider(generator: Any)
```

Bases: *BaseProvider*, *ImageMixin*

SVG file provider.

Usage example:

```
from faker import Faker  
from faker_file.providers.svg_file import SvgFileProvider  
  
file = SvgFileProvider(Faker()).svg_file()
```

Usage example with options:

```
file = SvgFileProvider(Faker()).svg_file(  
    prefix="zzz", max_nb_chars=100_000, wrap_chars_after=80,  
)
```

Usage example with *FileSystemStorage* storage (for *Django*):

```
from django.conf import settings  
from faker_file.storages.filesystem import FileSystemStorage  
  
file = SvgFileProvider(Faker()).svg_file(  
    storage=FileSystemStorage(  
        root_path=settings.MEDIA_ROOT, rel_path="tmp",  
    ), prefix="zzz", max_nb_chars=100_000, wrap_chars_after=80,
```



```
)
extension:  str = 'svg'

svg_file(storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, max_nb_chars: int =
    DEFAULT_IMAGE_MAX_NB_CHARS, wrap_chars_after: Optional[int] = None, content:
    Optional[str] = None, raw: bool = True, **kwargs) → BytesValue

svg_file(storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, max_nb_chars: int =
    DEFAULT_IMAGE_MAX_NB_CHARS, wrap_chars_after: Optional[int] = None, content:
    Optional[str] = None, **kwargs) → StringValue

Generate an SVG file with random text.
```

Parameters

- **storage** – Storage. Defaults to *FileSystemStorage*.
- **prefix** – File name prefix.
- **max_nb_chars** – Max number of chars for the content.
- **wrap_chars_after** – If given, the output string would be separated by line breaks after the given position.
- **content** – File content. Might contain dynamic elements, which are then replaced by correspondent fixtures.
- **raw** – If set to True, return *BytesValue* (binary content of the file). Otherwise, return *StringValue* (path to the saved file).

Returns

Relative path (from root directory) of the generated file or raw content of the file.

13.7.1.1.1.50 `faker_file.providers.tar_file` module

```
class faker_file.providers.tar_file.TarFileProvider(generator: Any)
```

Bases: *BaseProvider*, *FileMixin*

TAR file provider.

Usage example:

```
from faker import Faker
from faker_file.providers.tar_file import TarFileProvider

FAKER = Faker()

file = TarFileProvider(FAKER).tar_file()
```

Usage example with options:

```
from faker_file.providers.helpers.inner import create_inner_docx_file
from faker_file.providers.tar_file import TarFileProvider

file = TarFileProvider(FAKER).tar_file(
    prefix="ttt_archive_", options={
        "count": 5, "create_inner_file_func": create_inner_docx_file, "create_inner_file_args":
        {
            "prefix": "ttt_docx_file_", "max_nb_chars": 1_024,
        }, "directory": "ttt",
    },
)
```

```
)
```

Usage example of nested TARs:

```
from faker_file.providers.helpers.inner import create_inner_tar_file

file = TarFileProvider(FAKER).tar_file(
    options={
        "create_inner_file_func": create_inner_tar_file, "create_inner_file_args": {
            "options": {
                "create_inner_file_func": create_inner_docx_file,
            }
        }
    },
)
```

If you want to see, which files were included inside the TAR, check the `file.data["files"]`.

extension: `str = 'tar'`

tar_file(*storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, options: Optional[Dict[str, Any]] = None, compression: Optional[str] = None, raw: bool = True, **kwargs*) → *BytesValue*

tar_file(*storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, options: Optional[Dict[str, Any]] = None, compression: Optional[str] = None, **kwargs*) → *StringValue*

Generate a TAR file with random text.

Parameters

- **storage** – Storage. Defaults to *FileSystemStorage*.
- **prefix** – File name prefix.
- **options** – Options (non-structured) for complex types, such as ZIP.
- **compression** – Desired compression. Can be `None` or `gz`, `bz2` or `xz`.
- **raw** – If set to `True`, return *BytesValue* (binary content of the file). Otherwise, return *StringValue* (path to the saved file).

Returns

Relative path (from root directory) of the generated file or raw content of the file.

13.7.1.1.151 faker_file.providers.txt_file module

class `faker_file.providers.txt_file.TxtFileProvider(generator: Any)`

Bases: `BaseProvider`, *FileMixin*

TXT file provider.

Usage example:

```
from faker import Faker
from faker_file.providers.txt_file import TxtFileProvider

file = TxtFileProvider(Faker()).txt_file()
```

Usage example with options:

```
file = TxtFileProvider(Faker()).txt_file(
    prefix="zzz", max_nb_chars=100_000, wrap_chars_after=80,
)
```

Usage example with *FileSystemStorage* storage (for *Django*):

```
from django.conf import settings
from faker_file.storages.filesystem import FileSystemStorage

file = TxtFileProvider(Faker()).txt_file(
    storage=FileSystemStorage(
        root_path=settings.MEDIA_ROOT, rel_path="tmp",
    ), prefix="zzz", max_nb_chars=100_000, wrap_chars_after=80,
)
```

extension: `str = 'txt'`

txt_file(*storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, max_nb_chars: int = DEFAULT_TEXT_MAX_NB_CHARS, wrap_chars_after: Optional[int] = None, content: Optional[str] = None, raw: bool = True, **kwargs*) → *BytesValue*

txt_file(*storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, max_nb_chars: int = DEFAULT_TEXT_MAX_NB_CHARS, wrap_chars_after: Optional[int] = None, content: Optional[str] = None, **kwargs*) → *StringValue*

Generate a TXT file with random text.

Parameters

- **storage** – Storage. Defaults to *FileSystemStorage*.
- **prefix** – File name prefix.
- **max_nb_chars** – Max number of chars for the content.
- **wrap_chars_after** – If given, the output string would be separated by line breaks after the given position.
- **content** – File content. Might contain dynamic elements, which are then replaced by correspondent fixtures.
- **raw** – If set to True, return *BytesValue* (binary content of the file). Otherwise, return *StringValue* (path to the saved file).

Returns

Relative path (from root directory) of the generated file or raw content of the file.

13.7.1.1.1.52 faker_file.providers.webp_file module

class `faker_file.providers.webp_file.WebpFileProvider(generator: Any)`

Bases: `BaseProvider`, `ImageMixin`

WEBP file provider.

Usage example:

```
from faker import Faker
from faker_file.providers.webp_file import WebpFileProvider

file = WebpFileProvider(Faker()).webp_file()
```

Usage example with options:

```
file = WebpFileProvider(Faker()).webp_file(
    prefix="zzz", max_nb_chars=100_000, wrap_chars_after=80,
)
```

Usage example with *FileSystemStorage* storage (for *Django*):

```
from django.conf import settings
from faker_file.storages.filesystem import FileSystemStorage

file = WebpFileProvider(Faker()).webp_file(
    storage=FileSystemStorage(
        root_path=settings.MEDIA_ROOT, rel_path="tmp",
    ), prefix="zzz", max_nb_chars=100_000, wrap_chars_after=80,
)
```

extension: `str = 'webp'`

webp_file(*storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, max_nb_chars: int = DEFAULT_IMAGE_MAX_NB_CHARS, wrap_chars_after: Optional[int] = None, content: Optional[str] = None, raw: bool = True, **kwargs*) → *BytesValue*

webp_file(*storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, max_nb_chars: int = DEFAULT_IMAGE_MAX_NB_CHARS, wrap_chars_after: Optional[int] = None, content: Optional[str] = None, **kwargs*) → *StringValue*

Generate a WEBP file with random text.

Parameters

- **storage** – Storage. Defaults to *FileSystemStorage*.
- **prefix** – File name prefix.
- **max_nb_chars** – Max number of chars for the content.
- **wrap_chars_after** – If given, the output string would be separated by line breaks after the given position.
- **content** – File content. Might contain dynamic elements, which are then replaced by correspondent fixtures.
- **raw** – If set to True, return *BytesValue* (binary content of the file). Otherwise, return *StringValue* (path to the saved file).

Returns

Relative path (from root directory) of the generated file or raw content of the file.

13.7.1.1.1.53 `faker_file.providers.xlsx_file` module

```
class faker_file.providers.xlsx_file.XlsxFileProvider(generator: Any)
```

Bases: *BaseProvider*, *TabularDataMixin*

XLSX file provider.

Usage example:

```
from faker import Faker
from faker_file.providers.xlsx_file import XlsxFileProvider

file = XlsxFileProvider(Faker()).xlsx_file()
```

Usage example with options:

```

from faker import Faker
from faker_file.providers.xlsx_file import XlsxFileProvider

file = XlsxFileProvider(Faker()).xlsx_file(
    prefix="zzz", num_rows=100, data_columns={
        "name": "{{name}}", "residency": "{{address}}",
    }, include_row_ids=True,
)

```

Usage example with *FileSystemStorage* storage (for *Django*):

```

from django.conf import settings
from faker_file.storages.filesystem import FileSystemStorage

file = XlsxFileProvider(Faker()).xlsx_file(
    storage=FileSystemStorage(
        root_path=settings.MEDIA_ROOT, rel_path="tmp",
    ), prefix="zzz", num_rows=100, data_columns={
        "name": "{{name}}", "residency": "{{address}}",
    }, include_row_ids=True,
)

```

extension: `str = 'xlsx'`

xlsx_file(*storage*: *Optional*[*BaseStorage*] = *None*, *prefix*: *Optional*[*str*] = *None*, *data_columns*: *Optional*[*Dict*[*str*, *str*]] = *None*, *num_rows*: *int* = 10, *content*: *Optional*[*str*] = *None*, *raw*: *bool* = *True*, ***kwargs*) → *BytesValue*

xlsx_file(*storage*: *Optional*[*BaseStorage*] = *None*, *prefix*: *Optional*[*str*] = *None*, *data_columns*: *Optional*[*Dict*[*str*, *str*]] = *None*, *num_rows*: *int* = 10, *content*: *Optional*[*str*] = *None*, ***kwargs*) → *StringValue*

Generate a XLSX file with random text.

Parameters

- **storage** – Storage. Defaults to *FileSystemStorage*.
- **data_columns** – The *data_columns* argument expects a list or a tuple of string tokens, and these string tokens will be passed to `pystr_format()` for data generation. Argument Groups are used to pass arguments to the provider methods. Both *header* and *data_columns* must be of the same length.
- **num_rows** – The *num_rows* argument controls how many rows of data to generate, and the *include_row_ids* argument may be set to *True* to include a sequential row ID column.
- **prefix** – File name prefix.
- **content** – List of dicts with content (JSON-like format). If given, used as is.
- **raw** – If set to *True*, return *BytesValue* (binary content of the file). Otherwise, return *StringValue* (path to the saved file).

Returns

Relative path (from root directory) of the generated file or raw content of the file.

13.7.1.1.1.54 `faker_file.providers.zip_file` module

class `faker_file.providers.zip_file.ZipFileProvider(generator: Any)`

Bases: `BaseProvider`, `FileMixin`

ZIP file provider.

Usage example:

```
from faker import Faker
from faker_file.providers.zip_file import ZipFileProvider

FAKER = Faker()

file = ZipFileProvider(FAKER).zip_file()
```

Usage example with options:

```
from faker_file.providers.helpers.inner import create_inner_docx_file
from faker_file.providers.zip_file import ZipFileProvider

file = ZipFileProvider(FAKER).zip_file(
    prefix="zzz_archive_", options={
        "count": 5, "create_inner_file_func": create_inner_docx_file, "create_inner_file_args": {
            {
                "prefix": "zzz_docx_file_", "max_nb_chars": 1_024,
            }, "directory": "zzz",
        },
    },
)
```

Usage example of nested ZIPs:

```
from faker_file.providers.helpers.inner import create_inner_zip_file

file = ZipFileProvider(FAKER).zip_file(
    options={
        "create_inner_file_func": create_inner_zip_file, "create_inner_file_args": {
            "options": {
                "create_inner_file_func": create_inner_docx_file,
            },
        },
    },
)
```

If you want to see, which files were included inside the ZIP, check the `file.data["files"]`.

extension: `str = 'zip'`

zip_file(*storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, options: Optional[Dict[str, Any]] = None, raw: bool = True, **kwargs*) → *BytesValue*

zip_file(*storage: Optional[BaseStorage] = None, prefix: Optional[str] = None, options: Optional[Dict[str, Any]] = None, **kwargs*) → *Union[BytesValue, StringValue]*

Generate a ZIP file with random text.

Parameters

- **storage** – Storage. Defaults to *FileSystemStorage*.
- **prefix** – File name prefix.
- **options** – Options (non-structured) for complex types, such as ZIP.
- **raw** – If set to True, return *BytesValue* (binary content of the file). Otherwise, return *StringValue* (path to the saved file).

Returns

Relative path (from root directory) of the generated file or raw content of the file.

13.7.1.1.155 Module contents

13.7.1.1.2 faker_file.storages package

13.7.1.1.2.1 Submodules

13.7.1.1.2.2 faker_file.storages.aws_s3 module

```
class faker_file.storages.aws_s3.AWSS3Storage(bucket_name: str, root_path: Optional[str] = 'tmp',
                                             rel_path: Optional[str] = 'tmp', credentials:
                                             Optional[Dict[str, Any]] = None, *args, **kwargs)
```

Bases: *CloudStorage*

AWS S3 Storage.

Usage example:

```
from faker_file.storages.aws_s3 import AWSS3Storage

s3_storage = AWSS3Storage(
    bucket_name="artur-testing-1", rel_path="tmp",
) file = s3_storage.generate_filename(prefix="ZZZ_", extension="docx") s3_storage.write_text(file,
"Lorem ipsum") s3_storage.write_bytes(file, b"Lorem ipsum")

authenticate(key_id: str, key_secret: str, **kwargs) → None
    Authenticate to AWS S3.

schema: str = 's3'
```

13.7.1.1.2.3 faker_file.storages.azure_cloud_storage module

```
class faker_file.storages.azure_cloud_storage.AzureCloudStorage(bucket_name: str, root_path:
                                                                Optional[str] = 'tmp', rel_path:
                                                                Optional[str] = 'tmp',
                                                                credentials: Optional[Dict[str,
Any]] = None, *args, **kwargs)
```

Bases: *CloudStorage*

Azure Cloud Storage.

Usage example:

```
from faker_file.storages.azure_cloud_storage import AzureCloudStorage
```

```
    azure_storage = AzureCloudStorage(
        bucket_name="artur-testing-1", rel_path="tmp",
    )
    file = azure_storage.generate_filename(prefix="zzz_", extension="docx")
    azure_storage.write_text(file, "Lorem ipsum")
    azure_storage.write_bytes(file, b"Lorem ipsum")

authenticate(connection_string: str, **kwargs) → None
    Authenticate to Azure Cloud Storage.

bucket: Pathy

bucket_name: str

credentials: Dict[str, str]

schema: Optional[str] = 'azure'
```

13.7.1.1.2.4 `faker_file.storages.base` module

```
class faker_file.storages.base.BaseStorage(*args, **kwargs)
    Bases: object
    Base storage.

    abspath(filename: Any) → str
        Return absolute path.

    exists(filename: Any) → bool
        Check if file exists.

    generate_filename(extension: str, prefix: Optional[str] = None) → Any
        Generate filename.

    relpath(filename: Any) → str
        Return relative path.

    write_bytes(filename: Any, data: bytes) → int
        Write bytes.

    write_text(filename: Any, data: str, encoding: Optional[str] = None) → int
        Write text.
```

13.7.1.1.2.5 `faker_file.storages.cloud` module

```
class faker_file.storages.cloud.CloudStorage(bucket_name: str, root_path: Optional[str] = 'tmp',
                                             rel_path: Optional[str] = 'tmp', credentials:
                                             Optional[Dict[str, Any]] = None, *args, **kwargs)

    Bases: BaseStorage
    Base cloud storage.

    abspath(filename: Pathy) → str
        Return relative path.

    abstract authenticate(*args, **kwargs)
```


bucket: Pathy

bucket_name: str

credentials: Dict[str, str]

exists(filename: Union[Pathy, str]) → bool

Check if file exists.

generate_filename(extension: str, prefix: Optional[str] = None) → Pathy

Generate filename.

relpath(filename: Pathy) → str

Return relative path.

schema: Optional[str] = None

write_bytes(filename: Pathy, data: bytes) → int

Write bytes.

write_text(filename: Pathy, data: str, encoding: Optional[str] = None) → int

Write text.

```
class faker_file.storages.cloud.PathyFileSystemStorage(bucket_name: str, root_path: Optional[str]
    = 'tmp', rel_path: Optional[str] = 'tmp',
    credentials: Optional[Dict[str, Any]] =
    None, *args, **kwargs)
```

Bases: [CloudStorage](#)

Pathy FileSystem Storage.

Usage example:

```
from faker_file.storages.cloud import PathyFileSystemStorage

fs_storage = PathyFileSystemStorage(bucket_name="artur-testing-1") file =
fs_storage.generate_filename(prefix="zzz_", extension="docx") fs_storage.write_text(file, "Lorem
ipsum") fs_storage.write_bytes(file, b"Lorem ipsum")
```

authenticate(**kwargs) → None

Authenticate. Does nothing.

schema: str = 'file'

13.7.1.1.2.6 faker_file.storages.filesystem module

```
class faker_file.storages.filesystem.FileSystemStorage(root_path: Optional[str] = 'tmp', rel_path:
    Optional[str] = 'tmp', *args, **kwargs)
```

Bases: [BaseStorage](#)

File storage.

Usage example:

```
from faker_file.storages.filesystem import FileSystemStorage

storage = FileSystemStorage() file = storage.generate_filename(prefix="zzz_", extension="docx")
storage.write_text(file, "Lorem ipsum") storage.write_bytes(file, b"Lorem ipsum")
```

Initialization with params:

```
storage = FileSystemStorage()

abspath(filename: str) → str
    Return absolute path.

exists(filename: str) → bool
    Write bytes.

generate_filename(extension: str, prefix: Optional[str] = None) → str
    Generate filename.

relpath(filename: str) → str
    Return relative path.

write_bytes(filename: str, data: bytes) → int
    Write bytes.

write_text(filename: str, data: str, encoding: Optional[str] = None) → int
    Write text.
```

13.7.1.1.2.7 `faker_file.storages.google_cloud_storage` module

```
class faker_file.storages.google_cloud_storage.GoogleCloudStorage(bucket_name: str, root_path:
    Optional[str] = 'tmp',
    rel_path: Optional[str] =
    'tmp', credentials:
    Optional[Dict[str, Any]] =
    None, *args, **kwargs)
```

Bases: [`CloudStorage`](#)

Google Cloud Storage.

Usage example:

```
from faker_file.storages.google_cloud_storage import GoogleCloudStorage

gs_storage = GoogleCloudStorage(
    bucket_name="artur-testing-1", rel_path="tmp",
) file = gs_storage.generate_filename(prefix="ZZZ_", extension="docx") gs_storage.write_text(file,
"Lorem ipsum") gs_storage.write_bytes(file, b"Lorem ipsum")

authenticate(json_file_path: str, **kwargs) → None
    Authenticate to Google Cloud Storage.

bucket: Pathy

bucket_name: str

credentials: Dict[str, str]

schema: Optional[str] = 'gs'
```

13.7.1.1.2.8 Module contents

13.7.1.1.3 `faker_file.tests` package

13.7.1.1.3.1 Submodules

13.7.1.1.3.2 `faker_file.tests.test_augment_file_from_dir_provider` module

13.7.1.1.3.3 `faker_file.tests.test_django_integration` module

```
class faker_file.tests.test_django_integration.DjangoIntegrationTestCase(methodName='runTest')
```

Bases: `TestCase`

Django integration test case.

FAKER: `Faker`

`test_file`

13.7.1.1.3.4 `faker_file.tests.test_providers` module

```
class faker_file.tests.test_providers.ProvidersTestCase(methodName='runTest')
```

Bases: `TestCase`

Providers test case.

`setUp()`

Hook method for setting up the test fixture before exercising it.

`test_broken_imports`

`test_faker`

`test_faker_retry_failures`

`test_mp3_file_generate_not_implemented_exception()`

`test_raw_standalone_providers`

`test_raw_standalone_providers_allow_failures`

`test_raw_standalone_providers_retry_failures`

`test_standalone_providers`

`test_standalone_providers_allow_failures`

`test_standalone_providers_retry_failures`

`test_standalone_tar_file`

`test_standalone_tar_file_allow_failures`

`test_standalone_zip_file`

`test_standalone_zip_file_allow_failures`

13.7.1.1.3.5 `faker_file.tests.test_sqlalchemy_integration` module

13.7.1.1.3.6 `faker_file.tests.test_storages` module

```
class faker_file.tests.test_storages.TestStoragesTestCase(methodName='runTest')
    Bases: TestCase
    Test storages.
    test_base_storage_exceptions
    test_cloud_storage_exceptions
    test_file_system_storage_abspath()
        Test FileSystemStorage abspath.
    test_pathy_file_system_storage_abspath()
        Test PathyFileSystemStorage abspath.
    test_storage
    test_storage_generate_filename_exceptions
    test_storage_initialization_exceptions
```

13.7.1.1.3.7 `faker_file.tests.texts` module

13.7.1.1.3.8 Module contents

13.7.1.2 Submodules

13.7.1.3 `faker_file.base` module

```
class faker_file.base.BytesValue
    Bases: bytes
    data: Dict[str, Any] = {}
class faker_file.base.FileMixin
    Bases: object
    File mixin.
    extension: str
    formats: List[str]
    generator: Union[Faker, Generator, Provider]
    numerify: Callable
    random_element: Callable
class faker_file.base.StringValue
    Bases: str
    data: Dict[str, Any] = {}
```

13.7.1.4 `faker_file.constants` module

13.7.1.5 `faker_file.helpers` module

`faker_file.helpers.wrap_text(text: str, wrap_chars_after: int) → str`

13.7.1.6 Module contents

13.8 Indices and tables

- [genindex](#)
- [modindex](#)
- [search](#)

PYTHON MODULE INDEX

f

- faker_file, 109
- faker_file.base, 108
- faker_file.constants, 109
- faker_file.helpers, 109
- faker_file.providers, 103
- faker_file.providers.augment_file_from_dir.augmenters, 67
- faker_file.providers.bin_file, 80
- faker_file.providers.csv_file, 81
- faker_file.providers.docx_file, 82
- faker_file.providers.eml_file, 83
- faker_file.providers.epub_file, 85
- faker_file.providers.helpers, 76
- faker_file.providers.helpers.inner, 67
- faker_file.providers.ico_file, 86
- faker_file.providers.jpeg_file, 87
- faker_file.providers.mixins, 77
- faker_file.providers.mixins.image_mixin, 76
- faker_file.providers.mixins.tablular_data_mixin, 76
- faker_file.providers.mp3_file, 78
- faker_file.providers.mp3_file.generators, 78
- faker_file.providers.mp3_file.generators.edge_tts_generator, 77
- faker_file.providers.mp3_file.generators.gtts_generator, 78
- faker_file.providers.odp_file, 88
- faker_file.providers.ods_file, 89
- faker_file.providers.odt_file, 90
- faker_file.providers.pdf_file, 91
- faker_file.providers.png_file, 92
- faker_file.providers.pptx_file, 93
- faker_file.providers.random_file_from_dir, 94
- faker_file.providers.rtf_file, 95
- faker_file.providers.svg_file, 96
- faker_file.providers.tar_file, 97
- faker_file.providers.txt_file, 98
- faker_file.providers.webp_file, 99
- faker_file.providers.xlsx_file, 100
- faker_file.providers.zip_file, 102
- faker_file.storages, 107
- faker_file.storages.aws_s3, 103
- faker_file.storages.azure_cloud_storage, 103
- faker_file.storages.base, 104
- faker_file.storages.cloud, 104
- faker_file.storages.filesystem, 105
- faker_file.storages.google_cloud_storage, 106
- faker_file.tests, 108
- faker_file.tests.test_django_integration, 107
- faker_file.tests.test_providers, 107
- faker_file.tests.test_storages, 108
- faker_file.tests.texts, 108

A

`abspath()` (*faker_file.storages.base.BaseStorage* method), 104

`abspath()` (*faker_file.storages.cloud.CloudStorage* method), 104

`abspath()` (*faker_file.storages.filesystem.FileSystemStorage* method), 106

`authenticate()` (*faker_file.storages.aws_s3.AWSS3Storage* method), 103

`authenticate()` (*faker_file.storages.azure_cloud_storage.AzureCloudStorage* method), 104

`authenticate()` (*faker_file.storages.cloud.CloudStorage* method), 104

`authenticate()` (*faker_file.storages.cloud.PathyFileSystemStorage* method), 105

`authenticate()` (*faker_file.storages.google_cloud_storage.GoogleCloudStorage* method), 106

`AWSS3Storage` (class in *faker_file.storages.aws_s3*), 103

`AzureCloudStorage` (class in *faker_file.storages.azure_cloud_storage*), 103

B

`BaseStorage` (class in *faker_file.storages.base*), 104

`bin_file()` (*faker_file.providers.bin_file.BinFileProvider* method), 81

`BinFileProvider` (class in *faker_file.providers.bin_file*), 80

`bucket` (*faker_file.storages.azure_cloud_storage.AzureCloudStorage* attribute), 104

`bucket` (*faker_file.storages.cloud.CloudStorage* attribute), 104

`bucket` (*faker_file.storages.google_cloud_storage.GoogleCloudStorage* attribute), 106

`bucket_name` (*faker_file.storages.azure_cloud_storage.AzureCloudStorage* attribute), 104

`bucket_name` (*faker_file.storages.cloud.CloudStorage* attribute), 105

`bucket_name` (*faker_file.storages.google_cloud_storage.GoogleCloudStorage* attribute), 106

`BytesValue` (class in *faker_file.base*), 108

C

`CloudStorage` (class in *faker_file.storages.cloud*), 104

`create_inner_bin_file()` (in *faker_file.providers.helpers.inner*), 67

`create_inner_csv_file()` (in *faker_file.providers.helpers.inner*), 68

`create_inner_docx_file()` (in *faker_file.providers.helpers.inner*), 68

`create_inner eml_file()` (in *faker_file.providers.helpers.inner*), 68

`create_inner_epub_file()` (in *faker_file.providers.helpers.inner*), 69

`create_inner_ico_file()` (in *faker_file.providers.helpers.inner*), 69

`create_inner_jpeg_file()` (in *faker_file.providers.helpers.inner*), 70

`create_inner_mp3_file()` (in *faker_file.providers.helpers.inner*), 70

`create_inner_odp_file()` (in *faker_file.providers.helpers.inner*), 70

`create_inner ods_file()` (in *faker_file.providers.helpers.inner*), 71

`create_inner_odt_file()` (in *faker_file.providers.helpers.inner*), 71

`create_inner_pdf_file()` (in *faker_file.providers.helpers.inner*), 71

`create_inner_png_file()` (in *faker_file.providers.helpers.inner*), 72

`create_inner_pptx_file()` (in *faker_file.providers.helpers.inner*), 72

`create_inner_rtf_file()` (in *faker_file.providers.helpers.inner*), 73

`create_inner_svg_file()` (in *faker_file.providers.helpers.inner*), 73

`create_inner_tar_file()` (in *faker_file.providers.helpers.inner*), 73

`create_inner_txt_file()` (in *faker_file.providers.helpers.inner*), 73

`create_inner_webp_file()` (in *faker_file.providers.helpers.inner*), 74

`create_inner_xlsx_file()` (in *faker_file.providers.helpers.inner*), 74

`create_inner_zip_file()` (in module `extension (faker_file.providers.ico_file.IcoFileProvider`
`faker_file.providers.helpers.inner)`, 75 `attribute)`, 86
`credentials (faker_file.storages.azure_cloud_storage.AzureCloudStorage`
`attribute)`, 104 `extension (faker_file.providers.jpeg_file.JpegFileProvider`
`attribute)`, 87
`credentials (faker_file.storages.cloud.CloudStorage` `extension (faker_file.providers.mixins.image_mixin.ImageMixin`
`attribute)`, 105 `attribute)`, 76
`credentials (faker_file.storages.google_cloud_storage.GoogleCloudStorage`
`attribute)`, 106 `extension (faker_file.providers.mixins.tabular_data_mixin.TabularDataM`
`attribute)`, 76
`csv_file()` (`faker_file.providers.csv_file.CsvFileProvider` `extension (faker_file.providers.mp3_file.Mp3FileProvider`
`method)`, 82 `attribute)`, 79
`CsvFileProvider` (class in `extension (faker_file.providers.odp_file.OdpFileProvider`
`faker_file.providers.csv_file)`, 81 `attribute)`, 88
`extension (faker_file.providers.ods_file.OdsFileProvider`
`attribute)`, 89
`extension (faker_file.providers.odt_file.OdtFileProvider`
`attribute)`, 90
`DjangoIntegrationTestCase` (class in `extension (faker_file.providers.pdf_file.PdfFileProvider`
`faker_file.tests.test_django_integration)`, 107 `attribute)`, 92
`extension (faker_file.providers.png_file.PngFileProvider`
`attribute)`, 93
`docx_file()` (`faker_file.providers.docx_file.DocxFileProvider` `extension (faker_file.providers.pptx_file.PptxFileProvider`
`method)`, 83 `attribute)`, 94
`DocxFileProvider` (class in `extension (faker_file.providers.random_file_from_dir.RandomFileFromDir`
`faker_file.providers.docx_file)`, 82 `attribute)`, 95
`extension (faker_file.providers.rtf_file.RtfFileProvider`
`attribute)`, 96
`extension (faker_file.providers.svg_file.SvgFileProvider`
`attribute)`, 97
`EdgeTtsMp3Generator` (class in `extension (faker_file.providers.svg_file.SvgFileProvider`
`faker_file.providers.mp3_file.generators.edge_tts_generator)`, 77 `attribute)`, 97
`eml_file()` (`faker_file.providers.eml_file.EmlFileProvider` `extension (faker_file.providers.tar_file.TarFileProvider`
`method)`, 84 `attribute)`, 98
`EmlFileProvider` (class in `extension (faker_file.providers.txt_file.TxtFileProvider`
`faker_file.providers.eml_file)`, 83 `attribute)`, 99
`epub_file()` (`faker_file.providers.epub_file.EpubFileProvider` `extension (faker_file.providers.webp_file.WebpFileProvider`
`method)`, 85 `attribute)`, 100
`EpubFileProvider` (class in `extension (faker_file.providers.xlsx_file.XlsxFileProvider`
`faker_file.providers.epub_file)`, 85 `attribute)`, 101
`exists()` (`faker_file.storages.base.BaseStorage` `extension (faker_file.providers.zip_file.ZipFileProvider`
`method)`, 104 `attribute)`, 102
`exists()` (`faker_file.storages.cloud.CloudStorage`
`method)`, 105 **F**
`exists()` (`faker_file.storages.filesystem.FileSystemStorage` `FAKER (faker_file.tests.test_django_integration.DjangoIntegrationTestCase`
`method)`, 106 `attribute)`, 107
`extension (faker_file.base.FileMixin` `faker_file`
`attribute)`, 108 `module`, 109
`extension (faker_file.providers.bin_file.BinFileProvider` `faker_file.base`
`attribute)`, 81 `module`, 108
`extension (faker_file.providers.csv_file.CsvFileProvider` `faker_file.constants`
`attribute)`, 82 `module`, 109
`extension (faker_file.providers.docx_file.DocxFileProvider` `faker_file.helpers`
`attribute)`, 83 `module`, 109
`extension (faker_file.providers.eml_file.EmlFileProvider` `faker_file.providers`
`attribute)`, 84 `module`, 103
`extension (faker_file.providers.epub_file.EpubFileProvider` `faker_file.providers.augment_file_from_dir.augmenters`
`attribute)`, 86 `module`, 67

faker_file.providers.bin_file
 module, 80
 faker_file.providers.csv_file
 module, 81
 faker_file.providers.docx_file
 module, 82
 faker_file.providers.eml_file
 module, 83
 faker_file.providers.epub_file
 module, 85
 faker_file.providers.helpers
 module, 76
 faker_file.providers.helpers.inner
 module, 67
 faker_file.providers.ico_file
 module, 86
 faker_file.providers.jpeg_file
 module, 87
 faker_file.providers.mixins
 module, 77
 faker_file.providers.mixins.image_mixin
 module, 76
 faker_file.providers.mixins.tablular_data_mixin
 module, 76
 faker_file.providers.mp3_file
 module, 78
 faker_file.providers.mp3_file.generators
 module, 78
 faker_file.providers.mp3_file.generators.edge_tts_generator
 module, 77
 faker_file.providers.mp3_file.generators.gtts_generator
 module, 78
 faker_file.providers.odp_file
 module, 88
 faker_file.providers.ods_file
 module, 89
 faker_file.providers.odt_file
 module, 90
 faker_file.providers.pdf_file
 module, 91
 faker_file.providers.png_file
 module, 92
 faker_file.providers.pptx_file
 module, 93
 faker_file.providers.random_file_from_dir
 module, 94
 faker_file.providers.rtf_file
 module, 95
 faker_file.providers.svg_file
 module, 96
 faker_file.providers.tar_file
 module, 97
 faker_file.providers.txt_file
 module, 98

faker_file.providers.webp_file
 module, 99
 faker_file.providers.xlsx_file
 module, 100
 faker_file.providers.zip_file
 module, 102
 faker_file.storages
 module, 107
 faker_file.storages.aws_s3
 module, 103
 faker_file.storages.azure_cloud_storage
 module, 103
 faker_file.storages.base
 module, 104
 faker_file.storages.cloud
 module, 104
 faker_file.storages.filesystem
 module, 105
 faker_file.storages.google_cloud_storage
 module, 106
 faker_file.tests
 module, 108
 faker_file.tests.test_django_integration
 module, 107
 faker_file.tests.test_providers
 module, 107
 faker_file.tests.test_storages
 module, 108
 faker_file.tests.texts
 module, 108
 FileMixin (class in *faker_file.base*), 108
 FileSystemStorage (class in *faker_file.storages.filesystem*), 105
 formats (*faker_file.base.FileMixin* attribute), 108
 formats (*faker_file.providers.mixins.image_mixin.ImageMixin* attribute), 76
 formats (*faker_file.providers.mixins.tablular_data_mixin.TablularDataMixin* attribute), 76
 fuzzy_choice_create_inner_file() (in module *faker_file.providers.helpers.inner*), 75

G

generate() (*faker_file.providers.mp3_file.generators.edge_tts_generator* method), 77
 generate() (*faker_file.providers.mp3_file.generators.gtts_generator.GttsM* method), 78
 generate_filename()
 (*faker_file.storages.base.BaseStorage* method), 104
 generate_filename()
 (*faker_file.storages.cloud.CloudStorage* method), 105
 generate_filename()
 (*faker_file.storages.filesystem.FileSystemStorage*

method), 106
 generator (*faker_file.base.FileMixin* attribute), 108
 generator (*faker_file.providers.mixins.image_mixin.ImageMixin* attribute), 76
 generator (*faker_file.providers.mixins.tablular_data_mixin.TablularDataMixin* attribute), 76
 GoogleCloudStorage (class in *faker_file.storages.google_cloud_storage*), 106
 GttsMp3Generator (class in *faker_file.providers.mp3_file.generators.gtts_generator*), 78
H
 handle_kwargs() (*faker_file.providers.mp3_file.generators.edge_tts_generator* method), 77
 handle_kwargs() (*faker_file.providers.mp3_file.generators.gtts_generator* method), 78
I
 ico_file() (*faker_file.providers.ico_file.IcoFileProvider* method), 86
 IcoFileProvider (class in *faker_file.providers.ico_file*), 86
 ImageMixin (class in *faker_file.providers.mixins.image_mixin*), 76
J
 jpeg_file() (*faker_file.providers.jpeg_file.JpegFileProvider* method), 87
 JpegFileProvider (class in *faker_file.providers.jpeg_file*), 87
L
 lang (*faker_file.providers.mp3_file.generators.gtts_generator.GttsMp3Generator* attribute), 78
M
 module
 faker_file, 109
 faker_file.base, 108
 faker_file.constants, 109
 faker_file.helpers, 109
 faker_file.providers, 103
 faker_file.providers.augment_file_from_dir.augmenters, 67
 faker_file.providers.bin_file, 80
 faker_file.providers.csv_file, 81
 faker_file.providers.docx_file, 82
 faker_file.providers.eml_file, 83
 faker_file.providers.epub_file, 85
 faker_file.providers.helpers, 76
 faker_file.providers.helpers.inner, 67
 faker_file.providers.ico_file, 86
 faker_file.providers.jpeg_file, 87
 faker_file.providers.mixins, 77
 faker_file.providers.mixins.image_mixin,
 faker_file.providers.mixins.tablular_data_mixin,
 76
 faker_file.providers.mp3_file, 78
 faker_file.providers.mp3_file.generators,
 faker_file.providers.mp3_file.generators.edge_tts_gene
 77
 faker_file.providers.mp3_file.generators.gtts_generato
 78
 faker_file.providers.png_file, 92
 faker_file.providers.pptx_file, 93
 faker_file.providers.random_file_from_dir,
 94
 faker_file.providers.rtf_file, 95
 faker_file.providers.svg_file, 96
 faker_file.providers.tar_file, 97
 faker_file.providers.txt_file, 98
 faker_file.providers.webp_file, 99
 faker_file.providers.xlsx_file, 100
 faker_file.providers.zip_file, 102
 faker_file.storages, 107
 faker_file.storages.aws_s3, 103
 faker_file.storages.azure_cloud_storage,
 103
 faker_file.storages.base, 104
 faker_file.storages.cloud, 104
 faker_file.storages.filesystem, 105
 faker_file.storages.google_cloud_storage,
 106
 faker_file.tests, 108
 faker_file.tests.test_django_integration,
 107
 faker_file.tests.test_providers, 107
 faker_file.tests.test_storages, 108
 faker_file.tests.texts, 108
 mp3_file() (*faker_file.providers.mp3_file.Mp3FileProvider*
 method), 79
 Mp3FileProvider (class in
 faker_file.providers.mp3_file), 78
N
 numerify (*faker_file.base.FileMixin* attribute), 108
 numerify (*faker_file.providers.mixins.image_mixin.ImageMixin*
 attribute), 76

`numerify` (*faker_file.providers.mixins.tablular_data_mixin.TabularDataMixin* attribute), 76

O

`odp_file()` (*faker_file.providers.odp_file.OdpFileProvider* method), 88

`OdpFileProvider` (class in *schema* (*faker_file.storages.aws_s3.AWSS3Storage* attribute), 103

`ods_file()` (*faker_file.providers.ods_file.OdsFileProvider* method), 89

`OdsFileProvider` (class in *schema* (*faker_file.storages.cloud.CloudStorage* attribute), 105

`odt_file()` (*faker_file.providers.odt_file.OdtFileProvider* method), 91

`OdtFileProvider` (class in *schema* (*faker_file.storages.google_cloud_storage.GoogleCloudStorage* attribute), 106

P

`PathyFileSystemStorage` (class in *StringValues* (*faker_file.base*), 108

`pdf_file()` (*faker_file.providers.pdf_file.PdfFileProvider* method), 92

`PdfFileProvider` (class in *SvgFileProvider* (class in *faker_file.providers.svg_file*), 96

`png_file()` (*faker_file.providers.png_file.PngFileProvider* method), 93

`PngFileProvider` (class in *TabularDataMixin* (class in *faker_file.providers.mixins.tablular_data_mixin*), 76

`pptx_file()` (*faker_file.providers.pptx_file.PptxFileProvider* method), 94

`PptxFileProvider` (class in *TarFileProvider* (class in *faker_file.providers.tar_file*), 97

`ProvidersTestCase` (class in *test_base_storage_exceptions* (*faker_file.tests.test_storages.TestStoragesTestCase* attribute), 108

R

`random_element` (*faker_file.base.FileMixin* attribute), 108

`random_element` (*faker_file.providers.mixins.image_mixin.ImageMixin* attribute), 76

`random_element` (*faker_file.providers.mixins.tablular_data_mixin.TabularDataMixin* attribute), 76

`random_file_from_dir()` (*faker_file.providers.random_file_from_dir.RandomFileFromDirProvider* method), 95

`RandomFileFromDirProvider` (class in *test_file* (*faker_file.tests.test_django_integration.DjangoIntegrationTest* attribute), 107

`relpath()` (*faker_file.storages.base.BaseStorage* method), 104

`relpath()` (*faker_file.storages.cloud.CloudStorage* method), 105

`relpath()` (*faker_file.storages.filesystem.FileSystemStorage* method), 106

`RtfFileProvider` (class in *faker_file.providers.rtf_file.RtfFileProvider* method), 96

`RtfFileProvider` (class in *faker_file.providers.rtf_file*), 95

S

`setUp()` (*faker_file.tests.test_providers.ProvidersTestCase* method), 107

`StringValue` (class in *faker_file.base*), 108

`svg_file()` (*faker_file.providers.svg_file.SvgFileProvider* method), 97

`SvgFileProvider` (class in *faker_file.providers.svg_file*), 96

`test_base_storage_exceptions (faker_file.tests.test_storages.TestStoragesTestCase attribute), 108`

`test_broken_imports (faker_file.tests.test_providers.ProvidersTestCase attribute), 107`

`test_cloud_storage_exceptions (faker_file.tests.test_storages.TestStoragesTestCase attribute), 108`

`test_faker` (*faker_file.tests.test_providers.ProvidersTestCase* attribute), 107

`test_faker_retry_failures (faker_file.tests.test_providers.ProvidersTestCase attribute), 107`

`test_file` (*faker_file.tests.test_django_integration.DjangoIntegrationTest* attribute), 107

`test_file_system_storage_abspath()` (*faker_file.tests.test_storages.TestStoragesTestCase* method), 108

`test_mp3_file_generate_not_implemented_exception()` (*faker_file.tests.test_providers.ProvidersTestCase* method), 107

`test_pathy_file_system_storage_abspath()`
(*faker_file.tests.test_storages.TestStoragesTestCase*
method), 108

`test_raw_standalone_providers`
(*faker_file.tests.test_providers.ProvidersTestCase*
attribute), 107

`test_raw_standalone_providers_allow_failures`
(*faker_file.tests.test_providers.ProvidersTestCase*
attribute), 107

`test_raw_standalone_providers_retry_failures`
(*faker_file.tests.test_providers.ProvidersTestCase*
attribute), 107

`test_standalone_providers`
(*faker_file.tests.test_providers.ProvidersTestCase*
attribute), 107

`test_standalone_providers_allow_failures`
(*faker_file.tests.test_providers.ProvidersTestCase*
attribute), 107

`test_standalone_providers_retry_failures`
(*faker_file.tests.test_providers.ProvidersTestCase*
attribute), 107

`test_standalone_tar_file`
(*faker_file.tests.test_providers.ProvidersTestCase*
attribute), 107

`test_standalone_tar_file_allow_failures`
(*faker_file.tests.test_providers.ProvidersTestCase*
attribute), 107

`test_standalone_zip_file`
(*faker_file.tests.test_providers.ProvidersTestCase*
attribute), 107

`test_standalone_zip_file_allow_failures`
(*faker_file.tests.test_providers.ProvidersTestCase*
attribute), 107

`test_storage` (*faker_file.tests.test_storages.TestStoragesTestCase*
attribute), 108

`test_storage_generate_filename_exceptions`
(*faker_file.tests.test_storages.TestStoragesTestCase*
attribute), 108

`test_storage_initialization_exceptions`
(*faker_file.tests.test_storages.TestStoragesTestCase*
attribute), 108

`TestStoragesTestCase` (class in
faker_file.tests.test_storages), 108

`tld` (*faker_file.providers.mp3_file.generators.gtts_generator.GttsMp3Generator*
attribute), 78

`txt_file()` (*faker_file.providers.txt_file.TxtFileProvider*
method), 99

`TxtFileProvider` (class in *faker_file.providers.txt_file*),
98

W

`webp_file()` (*faker_file.providers.webp_file.WebpFileProvider*
method), 100

`WebpFileProvider` (class in
faker_file.providers.webp_file), 99

`wrap_text()` (in module *faker_file.helpers*), 109

`write_bytes()` (*faker_file.storages.base.BaseStorage*
method), 104

`write_bytes()` (*faker_file.storages.cloud.CloudStorage*
method), 105

`write_bytes()` (*faker_file.storages.filesystem.FileSystemStorage*
method), 106

`write_text()` (*faker_file.storages.base.BaseStorage*
method), 104

`write_text()` (*faker_file.storages.cloud.CloudStorage*
method), 105

`write_text()` (*faker_file.storages.filesystem.FileSystemStorage*
method), 106

X

`xlsx_file()` (*faker_file.providers.xlsx_file.XlsxFileProvider*
method), 101

`XlsxFileProvider` (class in
faker_file.providers.xlsx_file), 100

Z

`zip_file()` (*faker_file.providers.zip_file.ZipFileProvider*
method), 102

`ZipFileProvider` (class in *faker_file.providers.zip_file*),
102

V

`voice` (*faker_file.providers.mp3_file.generators.edge_tts_generator.EdgeTtsMp3Generator*
attribute), 77