
faker-file Documentation

Release 0.6

Artur Barseghyan <artur.barseghyan@gmail.com>

Feb 10, 2023

CONTENTS

1 Prerequisites	3
2 Documentation	5
3 Installation	7
4 Supported file types	9
5 Usage examples	11
5.1 With Faker	11
5.1.1 One way	11
5.1.2 Or another	11
5.2 With factory_boy	11
5.2.1 upload/models.py	11
5.2.2 upload/factory.py	12
6 Testing	13
7 Writing documentation	15
8 License	17
9 Support	19
10 Author	21
11 Project documentation	23
11.1 Quick start	24
11.1.1 Installation	24
11.1.2 Usage	24
11.1.2.1 With Faker	24
11.1.2.2 With factory_boy	25
11.1.2.2.1 upload/models.py	25
11.1.2.2.2 upload/factories.py	25
11.2 Recipes	26
11.2.1 When using with Faker	26
11.2.1.1 One way	26
11.2.1.1.1 Prerequisites	26
11.2.1.1.2 Create a TXT file with static content	27
11.2.1.1.3 Create a DOCX file with dynamically generated content	27
11.2.1.1.4 Create a ZIP file consisting of TXT files with static content	27

11.2.1.1.5	Create a ZIP file consisting of 3 DOCX files with dynamically generated content	27
11.2.1.1.6	Create a ZIP file which contains 5 ZIP files which contain 5 ZIP files which contain 5 DOCX files	28
11.2.1.2	Or another	28
11.2.1.2.1	Create a TXT file with static content	29
11.2.1.2.2	Create a DOCX file with dynamically generated content	29
11.2.1.2.3	Create a PDF file with predefined template containing dynamic fixtures	29
11.2.2	When using with Django (and factory_boy)	30
11.2.2.1	Basic example	30
11.2.2.1.1	Imaginary Django model	30
11.2.2.1.2	Correspondent factory_boy factory	30
11.2.2.2	Randomize provider choice	31
11.3	Release history and notes	32
11.3.1	0.6	32
11.3.2	0.5	32
11.3.3	0.4	33
11.3.4	0.3	33
11.3.5	0.2	33
11.3.6	0.1	33
11.4	Package	33
11.4.1	faker_file package	34
11.4.1.1	Subpackages	34
11.4.1.1.1	faker_file.providers package	34
11.4.1.1.1.1	Submodules	34
11.4.1.1.1.2	faker_file.providers.bin_file module	34
11.4.1.1.1.3	faker_file.providers.csv_file module	35
11.4.1.1.1.4	faker_file.providers.docx_file module	36
11.4.1.1.1.5	faker_file.providers.ico_file module	36
11.4.1.1.1.6	faker_file.providers.jpeg_file module	37
11.4.1.1.1.7	faker_file.providers.pdf_file module	38
11.4.1.1.1.8	faker_file.providers.png_file module	39
11.4.1.1.1.9	faker_file.providers.pptx_file module	40
11.4.1.1.1.10	faker_file.providers.svg_file module	40
11.4.1.1.1.11	faker_file.providers.txt_file module	41
11.4.1.1.1.12	faker_file.providers.webp_file module	42
11.4.1.1.1.13	faker_file.providers.xlsx_file module	43
11.4.1.1.1.14	faker_file.providers.zip_file module	44
11.4.1.1.1.15	Module contents	47
11.4.1.1.2	faker_file.tests package	47
11.4.1.1.2.1	Submodules	47
11.4.1.1.2.2	faker_file.tests.test_django_integration module	47
11.4.1.1.2.3	faker_file.tests.test_providers module	47
11.4.1.1.2.4	Module contents	48
11.4.1.2	Submodules	48
11.4.1.3	faker_file.base module	48
11.4.1.4	faker_file.constants module	48
11.4.1.5	faker_file.helpers module	48
11.4.1.6	Module contents	48
12	Indices and tables	49
Python Module Index		51

Generate fake files

**CHAPTER
ONE**

PREREQUISITES

All of core dependencies of this package are *MIT* licensed. Most of optional dependencies of this package are *MIT* licensed, while a few are *BSD*- or *Apache 2* licensed. All licenses are mentioned below between the brackets.

- Core package requires Python 3.7, 3.8, 3.9, 3.10 and 3.11.
- Django (*BSD*) integration with `factory_boy` (*MIT*) has been tested with Django 2.2, 3.0, 3.1, 3.2, 4.0 and 4.1.
- DOCX file support requires `python-docx` (*MIT*).
- ICO, JPEG, PNG, SVG and WEBP files support requires `imgkit` (*MIT*).
- PDF file support requires `pdfkit` (*MIT*).
- PPTX file support requires `python-pptx` (*MIT*).
- ODS file support requires `tablib` (*MIT*) and `odfpy` (*Apache 2*).
- XLSX file support requires `tablib` (*MIT*) and `openpyxl` (*MIT*).

**CHAPTER
TWO**

DOCUMENTATION

Documentation is available on [Read the Docs](#).

**CHAPTER
THREE**

INSTALLATION

Latest stable version on PyPI:

```
pip install faker-file[all]
```

Or development version from GitHub:

```
pip install https://github.com/barseghyanartur/faker-file/archive/main.tar.gz
```

**CHAPTER
FOUR**

SUPPORTED FILE TYPES

- BIN
- CSV
- DOCX
- ICO
- JPEG
- ODS
- PDF
- PNG
- PPTX
- SVG
- TXT
- WEBP
- XLSX
- ZIP

USAGE EXAMPLES

5.1 With Faker

5.1.1 One way

```
from faker import Faker
from faker_file.providers.txt_file import TxtFileProvider

FAKER = Faker()

file = TxtFileProvider(FAKER).txt_file()
```

5.1.2 Or another

```
from faker import Faker
from faker_file.providers.txt_file import TxtFileProvider

FAKER = Faker()
FAKER.add_provider(TxtFileProvider)

file = FAKER.txt_file()
```

5.2 With factory_boy

5.2.1 upload/models.py

```
from django.db import models

class Upload(models.Model):

    # ...
    file = models.FileField()
```

5.2.2 upload/factory.py

Note, that when using faker-file with Django, you need to pass your MEDIA_ROOT setting as root_path value (which is by default set to `tempfile.gettempdir()`).

```
import factory
from django.conf import settings
from factory import Faker
from factory.django import DjangoModelFactory
from faker_file.providers.docx_file import DocxFileProvider

from upload.models import Upload

factory.Faker.add_provider(DocxFileProvider)

class UploadFactory(DjangoModelFactory):

    # ...
    file = Faker("docx_file", root_path=settings.MEDIA_ROOT)

    class Meta:
        model = Upload
```

**CHAPTER
SIX**

TESTING

Simply type:

```
pytest -vvv
```

Or use tox:

```
tox
```

Or use tox to check specific env:

```
tox -e py310-django41
```

**CHAPTER
SEVEN**

WRITING DOCUMENTATION

Keep the following hierarchy.

```
=====
title
=====

header
=====

sub-header
-----

sub-sub-header
~~~~~

sub-sub-sub-header
^^^^^

sub-sub-sub-sub-header
+++++


sub-sub-sub-sub-sub-header
*****
```

**CHAPTER
EIGHT**

LICENSE

MIT

**CHAPTER
NINE**

SUPPORT

For any security issues contact me at the e-mail given in the *Author* section.

For overall issues, go to [GitHub](#).

**CHAPTER
TEN**

AUTHOR

Artur Barseghyan <artur.barseghyan@gmail.com>

CHAPTER
ELEVEN

PROJECT DOCUMENTATION

Contents:

Table of Contents

- *faker-file*
 - *Prerequisites*
 - *Documentation*
 - *Installation*
 - *Supported file types*
 - *Usage examples*
 - * *With Faker*
 - *One way*
 - *Or another*
 - * *With factory_boy*
 - *upload/models.py*
 - *upload/factory.py*
 - *Testing*
 - *Writing documentation*
 - *License*
 - *Support*
 - *Author*
 - *Project documentation*
 - *Indices and tables*

11.1 Quick start

11.1.1 Installation

```
pip install faker-file[all]
```

11.1.2 Usage

11.1.2.1 With Faker

```
from faker import Faker
from faker_file.providers.bin_file import BinFileProvider
from faker_file.providers.csv_file import CsvFileProvider
from faker_file.providers.docx_file import DocxFileProvider
from faker_file.providers.ico_file import IcoFileProvider
from faker_file.providers.jpeg_file import JpegFileProvider
from faker_file.providers.ods_file import OdsFileProvider
from faker_file.providers.pdf_file import PdfFileProvider
from faker_file.providers.png_file import PngFileProvider
from faker_file.providers.pptx_file import PptxFileProvider
from faker_file.providers.svg_file import SvgFileProvider
from faker_file.providers.txt_file import TxtFileProvider
from faker_file.providers.webp_file import WebpFileProvider
from faker_file.providers.xlsx_file import XlsxFileProvider
from faker_file.providers.zip_file import ZipFileProvider

FAKER = Faker()
FAKER.add_provider(BinFileProvider)
FAKER.add_provider(CsvFileProvider)
FAKER.add_provider(DocxFileProvider)
FAKER.add_provider(IcoFileProvider)
FAKER.add_provider(JpegFileProvider)
FAKER.add_provider(OdsFileProvider)
FAKER.add_provider(PdfFileProvider)
FAKER.add_provider(PngFileProvider)
FAKER.add_provider(PptxFileProvider)
FAKER.add_provider(SvgFileProvider)
FAKER.add_provider(TxtFileProvider)
FAKER.add_provider(WebpFileProvider)
FAKER.add_provider(XlsxFileProvider)
FAKER.add_provider(ZipFileProvider)

bin_file = FAKER.bin_file()
csv_file = FAKER.csv_file()
docx_file = FAKER.docx_file()
ico_file = FAKER.ico_file()
jpeg_file = FAKER.jpeg_file()
ods_file = FAKER.ods_file()
pdf_file = FAKER.pdf_file()
png_file = FAKER.png_file()
```

(continues on next page)

(continued from previous page)

```
pptx_file = FAKER.pptx_file()
svg_file = FAKER.svg_file()
txt_file = FAKER.txt_file()
webp_file = FAKER.webp_file()
xlsx_file = FAKER.xlsx_file()
zip_file = FAKER.zip_file()
```

11.1.2.2 With factory_boy

11.1.2.2.1 upload/models.py

```
from django.db import models

class Upload(models.Model):
    """Upload model."""

    name = models.CharField(max_length=255, unique=True)
    description = models.TextField(null=True, blank=True)

    # Files
    docx_file = models.FileField(null=True)
    pdf_file = models.FileField(null=True)
    pptx_file = models.FileField(null=True)
    txt_file = models.FileField(null=True)
    zip_file = models.FileField(null=True)

    class Meta:
        verbose_name = "Upload"
        verbose_name_plural = "Upload"

    def __str__(self):
        return self.name
```

11.1.2.2.2 upload/factories.py

```
from django.conf import settings

from factory import Faker
from factory.django import DjangoModelFactory

# Import all providers we want to use
from faker_file.providers.docx_file import DocxFileProvider
from faker_file.providers.pdf_file import PdfFileProvider
from faker_file.providers.pptx_file import PptxFileProvider
from faker_file.providers.txt_file import TxtFileProvider
from faker_file.providers.zip_file import ZipFileProvider

from upload.models import Upload
```

(continues on next page)

(continued from previous page)

```
# Add all providers we want to use
Faker.add_provider(DocxFileProvider)
Faker.add_provider(PdfFileProvider)
Faker.add_provider(PptxFileProvider)
Faker.add_provider(TxtFileProvider)
Faker.add_provider(ZipFileProvider)

class UploadFactory(DjangoModelFactory):
    """Upload factory."""

    name = Faker("text", max_nb_chars=100)
    description = Faker("text", max_nb_chars=1000)

    # Files
    docx_file = Faker("docx_file", root_path=settings.MEDIA_ROOT)
    pdf_file = Faker("pdf_file", root_path=settings.MEDIA_ROOT)
    pptx_file = Faker("pptx_file", root_path=settings.MEDIA_ROOT)
    txt_file = Faker("txt_file", root_path=settings.MEDIA_ROOT)
    zip_file = Faker("zip_file", root_path=settings.MEDIA_ROOT)

    class Meta:
        model = Upload
```

11.2 Recipes

11.2.1 When using with Faker

11.2.1.1 One way

11.2.1.1.1 Prerequisites

Imports and initializations

```
import Faker
from faker_file.providers.docx_file import DocxFileProvider
from faker_file.providers.pdf_file import PdfFileProvider
from faker_file.providers.pptx_file import PptxFileProvider
from faker_file.providers.txt_file import TxtFileProvider
from faker_file.providers.zip_file import ZipFileProvider

FAKER = Faker()
```

11.2.1.1.2 Create a TXT file with static content

- Content of the file is `LOREM ipsum`.

```
file = TxtFileProvider(FAKER).txt_file(content="LOREM ipsum")
```

11.2.1.1.3 Create a DOCX file with dynamically generated content

- Content is generated dynamically.
- Content is limited to 1024 chars.
- Wrap lines after 80 chars.
- Prefix the filename with `zzz`.

```
file = DocxFileProvider(FAKER).docx_file(
    prefix="zzz",
    max_nb_chars=1_024,
    wrap_chars_after=80,
)
```

11.2.1.1.4 Create a ZIP file consisting of TXT files with static content

- 5 TXT files in the ZIP archive (default value is 5).
- Content of all files is `LOREM ipsum`.

```
file = ZipFileProvider(FAKER).zip_file(options={"content": "LOREM ipsum"})
```

11.2.1.1.5 Create a ZIP file consisting of 3 DOCX files with dynamically generated content

- 3 DOCX files in the ZIP archive.
- Content is generated dynamically.
- Content is limited to 1024 chars.
- Prefix the filenames in archive with `xxx_`.
- Prefix the filename of the archive itself with `zzz`.
- Inside the ZIP, put all files in directory `yyy`.

```
from faker_file.providers.zip_file import create_inner_docx_file
file = ZipFileProvider(FAKER).zip_file(
    prefix="zzz",
    options={
        "count": 3,
        "create_inner_file_func": create_inner_docx_file,
        "create_inner_file_args": {
            "prefix": "xxx_",
            "max_nb_chars": 1_024,
        }
    }
)
```

(continues on next page)

(continued from previous page)

```
        "directory": "yyy",
    }
}
```

11.2.1.1.6 Create a ZIP file which contains 5 ZIP files which contain 5 ZIP files which contain 5 DOCX files

- 5 ZIP files in the ZIP archive.
- Content is generated dynamically.
- Prefix the filenames in archive with `nested_level_1_`.
- Prefix the filename of the archive itself with `nested_level_0_`.
- Each of the ZIP files inside the ZIP file in their turn contains 5 other ZIP files, prefixed with `nested_level_2_`, which in their turn contain 5 DOCX files.

```
from faker_file.providers.zip_file import create_inner_docx_file, create_inner_zip_file
file = ZipFileProvider(FAKER).zip_file(
    prefix="nested_level_0_",
    options={
        "create_inner_file_func": create_inner_zip_file,
        "create_inner_file_args": {
            "prefix": "nested_level_1_",
            "options": {
                "create_inner_file_func": create_inner_zip_file,
                "create_inner_file_args": {
                    "prefix": "nested_level_2_",
                    "options": {
                        "create_inner_file_func": create_inner_docx_file,
                    }
                }
            }
        }
    }
)
```

11.2.1.2 Or another

Imports and initializations

```
import Faker
from faker_file.providers.docx_file import DocxFileProvider
from faker_file.providers.pdf_file import PdfFileProvider
from faker_file.providers.pptx_file import PptxFileProvider
from faker_file.providers.txt_file import TxtFileProvider
from faker_file.providers.zip_file import ZipFileProvider

FAKER = Faker()
FAKER.add_provider(DocxFileProvider)
FAKER.add_provider(PdfFileProvider)
```

(continues on next page)

(continued from previous page)

```
FAKER.add_provider(PptxFileProvider)
FAKER.add_provider(TxtFileProvider)
FAKER.add_provider(ZipFileProvider)
```

11.2.1.2.1 Create a TXT file with static content

```
file = FAKER("txt_file", content="Lorem ipsum dolor sit amet")
```

11.2.1.2.2 Create a DOCX file with dynamically generated content

- Content is generated dynamically.
- Content is limited to 1024 chars.
- Wrap lines after 80 chars.
- Prefix the filename with zzz.

```
file = FAKER(
    "docx_file",
    prefix="zzz",
    max_nb_chars=1_024,
    wrap_chars_after=80,
)
```

11.2.1.2.3 Create a PDF file with predefined template containing dynamic fixtures

- Content template is predefined and contains dynamic fixtures.
- Wrap lines after 80 chars.

```
template = """
{{date}} {{city}}, {{country}}

Hello {{name}},

{{text}} {{text}} {{text}}

{{text}} {{text}} {{text}}

{{text}} {{text}} {{text}}

Address: {{address}}

Best regards,

{{name}}
{{address}}
{{phone_number}}
"""
```

(continues on next page)

(continued from previous page)

```
file = FAKER("pdf_file", content=template, wrap_chars_after=80)
```

11.2.2 When using with Django (and factory_boy)

When used with Django (to generate fake data with `factory_boy` factories), the `root_path` argument shall be provided. Otherwise (although no errors will be triggered) the generated files will reside outside the `MEDIA_ROOT` directory (by default in `/tmp/tmp/` on Linux) and further operations with those files through Django will cause `SuspiciousOperation` exception.

11.2.2.1 Basic example

11.2.2.1.1 Imaginary Django model

```
from django.db import models

class Upload(models.Model):
    """Upload model."""

    name = models.CharField(max_length=255, unique=True)
    description = models.TextField(null=True, blank=True)

    # Files
    docx_file = models.FileField(null=True)
    pdf_file = models.FileField(null=True)
    pptx_file = models.FileField(null=True)
    txt_file = models.FileField(null=True)
    zip_file = models.FileField(null=True)
    file = models.FileField(null=True)

    class Meta:
        verbose_name = "Upload"
        verbose_name_plural = "Upload"

    def __str__(self):
        return self.name
```

11.2.2.1.2 Correspondent factory_boy factory

```
from django.conf import settings

from factory import Faker
from factory.django import DjangoModelFactory

# Import all providers we want to use
from faker_file.providers.docx_file import DocxFileProvider
from faker_file.providers.pdf_file import PdfFileProvider
```

(continues on next page)

(continued from previous page)

```

from faker_file.providers.pptx_file import PptxFileProvider
from faker_file.providers.txt_file import TxtFileProvider
from faker_file.providers.zip_file import ZipFileProvider

from upload.models import Upload

# Add all providers we want to use
Faker.add_provider(DocxFileProvider)
Faker.add_provider(PdfFileProvider)
Faker.add_provider(PptxFileProvider)
Faker.add_provider(TxtFileProvider)
Faker.add_provider(ZipFileProvider)

class UploadFactory(DjangoModelFactory):
    """Upload factory."""

    name = Faker("text", max_nb_chars=100)
    description = Faker("text", max_nb_chars=1000)

    # Files
    docx_file = Faker("docx_file", root_path=settings.MEDIA_ROOT)
    pdf_file = Faker("pdf_file", root_path=settings.MEDIA_ROOT)
    pptx_file = Faker("pptx_file", root_path=settings.MEDIA_ROOT)
    txt_file = Faker("txt_file", root_path=settings.MEDIA_ROOT)
    zip_file = Faker("zip_file", root_path=settings.MEDIA_ROOT)
    file = Faker("txt_file", root_path=settings.MEDIA_ROOT)

    class Meta:
        model = Upload

```

11.2.2 Randomize provider choice

```

from random import choice

from factory import LazyAttribute
from faker import Faker as FakerFaker

FAKER = FakerFaker()

PROVIDER_CHOICES = [
    lambda: DocxFileProvider(FAKER).docx_file(root_path=settings.MEDIA_ROOT),
    lambda: PdfFileProvider(FAKER).pdf_file(root_path=settings.MEDIA_ROOT),
    lambda: PptxFileProvider(FAKER).pptx_file(root_path=settings.MEDIA_ROOT),
    lambda: TxtFileProvider(FAKER).txt_file(root_path=settings.MEDIA_ROOT),
    lambda: ZipFileProvider(FAKER).zip_file(root_path=settings.MEDIA_ROOT),
]

def pick_random_provider(*args, **kwargs):
    return choice(PROVIDER_CHOICES)()

```

(continues on next page)

(continued from previous page)

```
class UploadFactory(DjangoModelFactory):
    """Upload factory that randomly picks a file provider."""

    # ...
    file = LazyAttribute(pick_random_provider)
    # ...
```

11.3 Release history and notes

Sequence based identifiers are used for versioning (schema follows below):

```
major.minor[.revision]
```

- It's always safe to upgrade within the same minor version (for example, from 0.3 to 0.3.4).
- Minor version changes might be backwards incompatible. Read the release notes carefully before upgrading (for example, when upgrading from 0.3.4 to 0.4).
- All backwards incompatible changes are mentioned in this document.

11.3.1 0.6

2022-12-11

- Pass optional `generator` argument to inner functions of the `ZipFileProvider`.
- Added `create_inner_zip_file` inner function which allows to create nested ZIPs.
- Reached test coverage of 100%.

11.3.2 0.5

2022-12-10

Note, that this release introduces breaking changes!

- Added `ODS` file support.
- Switched to `tablib` for easy, non-variant support of various formats (`XLSX`, `ODS`).
- Silence `imgkit` logging output.
- `ZipFileProvider` allows to pass arbitrary arguments to inner functions. Put all your inner function arguments into a dictionary and pass it in `create_inner_file_args` key inside `options` argument. See the example below.

```
zip_file = ZipFileProvider(None).file(
    prefix="zzz_archive_",
    options={
        "count": 5,
        "create_inner_file_func": create_inner_docx_file,
        "create_inner_file_args": {
            "prefix": "zzz_file_",
            "max_nb_chars": 1_024,
```

(continues on next page)

(continued from previous page)

```

        "content": "{{date}}\r\n{{text}}\r\n{{name}}",
    },
    "directory": "zzz",
}
)

```

11.3.3 0.4

2022-12-09

Note, that this release introduces breaking changes!

- Remove the concept of content generators (and the correspondent `content_generator` arguments in implemented providers). Instead, allow usage of dynamic fixtures in the provided `content` argument.
- Remove temporary files when creating ZIP archives.
- Various improvements and fixes in docs.

11.3.4 0.3

2022-12-08

- Add support for *BIN*, *CSV* and *XLSX* files.
- Better visual representation of generated images and PDFs.

11.3.5 0.2

2022-12-07

- Added support for *ICO*, *JPEG*, *PNG*, *SVG* and *WEBP* files.
- Documentation improvements.

11.3.6 0.1

2022-12-06

- Initial beta release.

11.4 Package

Contents:

Table of Contents

- *Package*

11.4.1 faker_file package

11.4.1.1 Subpackages

11.4.1.1.1 faker_file.providers package

11.4.1.1.1.1 Submodules

11.4.1.1.1.2 faker_file.providers.bin_file module

```
class faker_file.providers.bin_file.BinFileProvider(generator: Any)
```

Bases: BaseProvider, *FileMixin*

BIN file provider.

Usage example:

```
from faker_file.providers.bin_file import BinFileProvider
file = BinFileProvider(None).bin_file()
```

Usage example with options:

```
from faker_file.providers.bin_file import BinFileProvider
file = BinFileProvider(None).bin_file(
    prefix="zzz", length=1024**2,
)
bin_file(root_path: Optional[str] = None, rel_path: str = 'tmp', prefix: Optional[str] = None, length: int =
1048576, content: Optional[bytes] = None, **kwargs) → StringValue
```

Generate a CSV file with random text.

Parameters

- **root_path** – Path of your files root directory (in case of Django it would be *settings.MEDIA_ROOT*).
- **rel_path** – Relative path (from root directory).
- **prefix** – File name prefix.
- **length** –
- **content** – File content. If given, used as is.

Returns

Relative path (from root directory) of the generated file.

```
extension: str = 'bin'
```

11.4.1.1.1.3 faker_file.providers.csv_file module

```
class faker_file.providers.csv_file.CsvFileProvider(generator: Any)
```

Bases: BaseProvider, *FileMixin*

CSV file provider.

Usage example:

```
from faker_file.providers.csv_file import CsvFileProvider
file = CsvFileProvider(None).csv_file()
```

Usage example with options:

```
from faker_file.providers.csv_file import CsvFileProvider
file = CsvFileProvider(None).csv_file(
    prefix="zzz", num_rows=100, data_columns=( '{{name}}', '{{sentence}}', '{{address}}' ), include_row_ids=True,
)
csv_file(root_path: Optional[str] = None, rel_path: str = 'tmp', prefix: Optional[str] = None, header: Optional[Sequence[str]] = None, data_columns: Tuple[str, str] = ('{{name}}', '{{address}}'), num_rows: int = 10, include_row_ids: bool = False, content: Optional[str] = None, **kwargs) → StringValue
```

Generate a CSV file with random text.

Parameters

- **root_path** – Path of your files root directory (in case of Django it would be `settings.MEDIA_ROOT`).
- **rel_path** – Relative path (from root directory).
- **header** – The header argument expects a list or a tuple of strings that will serve as the header row if supplied.
- **data_columns** – The `data_columns` argument expects a list or a tuple of string tokens, and these string tokens will be passed to `pystr_format()` for data generation. Argument Groups are used to pass arguments to the provider methods. Both `header` and `data_columns` must be of the same length.
- **num_rows** – The `num_rows` argument controls how many rows of data to generate, and the `include_row_ids` argument may be set to True to include a sequential row ID column.
- **include_row_ids** –
- **prefix** – File name prefix.
- **content** – File content. If given, used as is.

Returns

Relative path (from root directory) of the generated file.

```
extension: str = 'csv'
```

11.4.1.1.4 faker_file.providers.docx_file module

```
class faker_file.providers.docx_file.DocxFileProvider(generator: Any)
```

Bases: BaseProvider, [FileMixin](#)

DOCX file provider.

Usage example:

```
from faker_file.providers.docx_file import DocxFileProvider
file = DocxFileProvider(None).docx_file()
```

Usage example with options:

```
from faker_file.providers.docx_file import DocxFileProvider
file = DocxFileProvider(None).docx_file(
    prefix="zzz", max_nb_chars=100_000, wrap_chars_after=80,
)
docx_file(root_path: Optional[str] = None, rel_path: str = 'tmp', prefix: Optional[str] = None,
          max_nb_chars: int = 10000, wrap_chars_after: Optional[int] = None, content: Optional[str] =
          None, **kwargs) → StringValue
```

Generate a DOCX file with random text.

Parameters

- **root_path** – Path of your files root directory (in case of Django it would be `settings.MEDIA_ROOT`).
- **rel_path** – Relative path (from root directory).
- **prefix** – File name prefix.
- **max_nb_chars** – Max number of chars for the content.
- **wrap_chars_after** – If given, the output string would be separated by line breaks after the given position.
- **content** – File content. Might contain dynamic elements, which are then replaced by correspondent fixtures.

Returns

Relative path (from root directory) of the generated file.

extension: str = 'docx'

11.4.1.1.5 faker_file.providers.ico_file module

```
class faker_file.providers.ico_file.IcoFileProvider(generator: Any)
```

Bases: BaseProvider, [FileMixin](#)

ICO file provider.

Usage example:

```
from faker_file.providers.png_file import IcoFileProvider
file = IcoFileProvider(None).ico_file()
```

Usage example with options:

```
from faker_file.providers.ico_file import IcoFileProvider
file = IcoFileProvider(None).ico_file(
    prefix="zzz", max_nb_chars=100_000, wrap_chars_after=80,
)
extension: str = 'ico'
ico_file(root_path: Optional[str] = None, rel_path: str = 'tmp', prefix: Optional[str] = None,
         max_nb_chars: int = 5000, wrap_chars_after: Optional[int] = None, content: Optional[str] =
         None, **kwargs) → StringValue
```

Generate an ICO file with random text.

Parameters

- **root_path** – Path of your files root directory (in case of Django it would be `settings.MEDIA_ROOT`).
- **rel_path** – Relative path (from root directory).
- **prefix** – File name prefix.
- **max_nb_chars** – Max number of chars for the content.
- **wrap_chars_after** – If given, the output string would be separated by line breaks after the given position.
- **content** – File content. Might contain dynamic elements, which are then replaced by correspondent fixtures.

Returns

Relative path (from root directory) of the generated file.

11.4.1.1.6 faker_file.providers.jpeg_file module

```
class faker_file.providers.jpeg_file.JpegFileProvider(generator: Any)
```

Bases: `BaseProvider`, `FileMixin`

JPEG file provider.

Usage example:

```
from faker_file.providers.jpeg_file import JpegFileProvider
file = JpegFileProvider(None).jpeg_file()
```

Usage example with options:

```
from faker_file.providers.jpeg_file import JpegFileProvider
file = JpegFileProvider(None).jpeg_file(
    prefix="zzz", max_nb_chars=100_000, wrap_chars_after=80,
)
extension: str = 'jpg'
jpeg_file(root_path: Optional[str] = None, rel_path: str = 'tmp', prefix: Optional[str] = None,
          max_nb_chars: int = 5000, wrap_chars_after: Optional[int] = None, content: Optional[str] =
          None, **kwargs) → StringValue
```

Generate a JPEG file with random text.

Parameters

- **root_path** – Path of your files root directory (in case of Django it would be `settings.MEDIA_ROOT`).
- **rel_path** – Relative path (from root directory).
- **prefix** – File name prefix.
- **max_nb_chars** – Max number of chars for the content.
- **wrap_chars_after** – If given, the output string would be separated by line breaks after the given position.
- **content** – File content. Might contain dynamic elements, which are then replaced by correspondent fixtures.

Returns

Relative path (from root directory) of the generated file.

11.4.1.1.7 faker_file.providers.pdf_file module

```
class faker_file.providers.pdf_file.PdfFileProvider(generator: Any)
```

Bases: `BaseProvider`, `FileMixin`

PDF file provider.

Usage example:

```
from faker_file.providers.pdf_file import PdfFileProvider
file = PdfFileProvider(None).pdf_file()
```

Usage example with options:

```
from faker_file.providers.pdf_file import PdfFileProvider
file = PdfFileProvider(None).pdf_file(
    prefix="zzz", max_nb_chars=100_000, wrap_chars_after=80,
)
extension: str = 'pdf'

pdf_file(root_path: Optional[str] = None, rel_path: str = 'tmp', prefix: Optional[str] = None,
         max_nb_chars: int = 10000, wrap_chars_after: Optional[int] = None, content: Optional[str] = None,
         **kwargs) → StringValue
```

Generate a PDF file with random text.

Parameters

- **root_path** – Path of your files root directory (in case of Django it would be `settings.MEDIA_ROOT`).
- **rel_path** – Relative path (from root directory).
- **prefix** – File name prefix.
- **max_nb_chars** – Max number of chars for the content.
- **wrap_chars_after** – If given, the output string would be separated by line breaks after the given position.

- **content** – File content. Might contain dynamic elements, which are then replaced by correspondent fixtures.

Returns

Relative path (from root directory) of the generated file.

11.4.1.1.1.8 faker_file.providers.png_file module

```
class faker_file.providers.png_file.PngFileProvider(generator: Any)
```

Bases: BaseProvider, *FileMixin*

PNG file provider.

Usage example:

```
from faker_file.providers.png_file import PngFileProvider
file = PngFileProvider(None).png_file()
```

Usage example with options:

```
from faker_file.providers.png_file import PngFileProvider
file = PngFileProvider(None).png_file(
    prefix="zzz", max_nb_chars=100_000, wrap_chars_after=80,
)
extension: str = 'png'

png_file(root_path: Optional[str] = None, rel_path: str = 'tmp', prefix: Optional[str] = None,
         max_nb_chars: int = 5000, wrap_chars_after: Optional[int] = None, content: Optional[str] =
         None, **kwargs) → StringValue
```

Generate a PNG file with random text.

Parameters

- **root_path** – Path of your files root directory (in case of Django it would be *settings.MEDIA_ROOT*).
- **rel_path** – Relative path (from root directory).
- **prefix** – File name prefix.
- **max_nb_chars** – Max number of chars for the content.
- **wrap_chars_after** – If given, the output string would be separated by line breaks after the given position.
- **content** – File content. Might contain dynamic elements, which are then replaced by correspondent fixtures.

Returns

Relative path (from root directory) of the generated file.

11.4.1.1.1.9 faker_file.providers.pptx_file module

```
class faker_file.providers.pptx_file.PptxFileProvider(generator: Any)
```

Bases: BaseProvider, [FileMixin](#)

PPTX file provider.

Usage example:

```
from faker_file.providers.pptx_file import PptxFileProvider
file = PptxFileProvider(None).pptx_file()
```

Usage example with options:

```
from faker_file.providers.pptx_file import PptxFileProvider
file = PptxFileProvider(None).pptx_file(
    prefix="zzz", max_nb_chars=100_000, wrap_chars_after=80,
)
extension: str = 'pptx'

pptx_file(root_path: Optional[str] = None, rel_path: str = 'tmp', prefix: Optional[str] = None,
          max_nb_chars: int = 10000, wrap_chars_after: Optional[int] = None, content: Optional[str] =
          None, **kwargs) → StringValue
```

Generate a file with random text.

Parameters

- **root_path** – Path of your files root directory (in case of Django it would be `settings.MEDIA_ROOT`).
- **rel_path** – Relative path (from root directory).
- **prefix** – File name prefix.
- **max_nb_chars** – Max number of chars for the content.
- **wrap_chars_after** – If given, the output string would be separated by line breaks after the given position.
- **content** – File content. Might contain dynamic elements, which are then replaced by correspondent fixtures.

Returns

Relative path (from root directory) of the generated file.

11.4.1.1.1.10 faker_file.providers.svg_file module

```
class faker_file.providers.svg_file.SvgFileProvider(generator: Any)
```

Bases: BaseProvider, [FileMixin](#)

SVG file provider.

Usage example:

```
from faker_file.providers.svg_file import SvgFileProvider
file = SvgFileProvider(None).svg_file()
```

Usage example with options:

```
from faker_file.providers.svg_file import SvgFileProvider
file = SvgFileProvider(None).svg_file(
    prefix="zzz", max_nb_chars=100_000, wrap_chars_after=80,
)
extension: str = 'svg'

svg_file(root_path: Optional[str] = None, rel_path: str = 'tmp', prefix: Optional[str] = None,
max_nb_chars: int = 5000, wrap_chars_after: Optional[int] = None, content: Optional[str] =
None, **kwargs) → StringValue
```

Generate an SVG file with random text.

Parameters

- **root_path** – Path of your files root directory (in case of Django it would be `settings.MEDIA_ROOT`).
- **rel_path** – Relative path (from root directory).
- **prefix** – File name prefix.
- **max_nb_chars** – Max number of chars for the content.
- **wrap_chars_after** – If given, the output string would be separated by line breaks after the given position.
- **content** – File content. Might contain dynamic elements, which are then replaced by correspondent fixtures.

Returns

Relative path (from root directory) of the generated file.

11.4.1.1.11 faker_file.providers.txt_file module

```
class faker_file.providers.txt_file.TxtFileProvider(generator: Any)
```

Bases: `BaseProvider`, `FileMixin`

TXT file provider.

Usage example:

```
from faker_file.providers.txt_file import TxtFileProvider
file = TxtFileProvider(None).txt_file()
```

Usage example with options:

```
from faker_file.providers.txt_file import TxtFileProvider
file = TxtFileProvider(None).txt_file(
    prefix="zzz", max_nb_chars=100_000, wrap_chars_after=80,
)
extension: str = 'txt'

txt_file(root_path: Optional[str] = None, rel_path: str = 'tmp', prefix: Optional[str] = None,
max_nb_chars: int = 10000, wrap_chars_after: Optional[int] = None, content: Optional[str] =
None, **kwargs) → StringValue
```

Generate a TXT file with random text.

Parameters

- **root_path** – Path of your files root directory (in case of Django it would be `settings.MEDIA_ROOT`).
- **rel_path** – Relative path (from root directory).
- **prefix** – File name prefix.
- **max_nb_chars** – Max number of chars for the content.
- **wrap_chars_after** – If given, the output string would be separated by line breaks after the given position.
- **content** – File content. Might contain dynamic elements, which are then replaced by correspondent fixtures.

Returns

Relative path (from root directory) of the generated file.

11.4.1.1.1.12 faker_file.providers.webp_file module

```
class faker_file.providers.webp_file.WebpFileProvider(generator: Any)
```

Bases: `BaseProvider`, `FileMixin`

WEBP file provider.

Usage example:

```
from faker_file.providers.webp_file import WebpFileProvider
file = WebpFileProvider(None).webp_file()
```

Usage example with options:

```
from faker_file.providers.webp_file import WebpFileProvider
file = WebpFileProvider(None).webp_file(
    prefix="zzz", max_nb_chars=100_000, wrap_chars_after=80,
)
extension: str = 'webp'
```

```
webp_file(root_path: Optional[str] = None, rel_path: str = 'tmp', prefix: Optional[str] = None,
          max_nb_chars: int = 5000, wrap_chars_after: Optional[int] = None, content: Optional[str] = None, **kwargs) → StringValue
```

Generate a WEBP file with random text.

Parameters

- **root_path** – Path of your files root directory (in case of Django it would be `settings.MEDIA_ROOT`).
- **rel_path** – Relative path (from root directory).
- **prefix** – File name prefix.
- **max_nb_chars** – Max number of chars for the content.
- **wrap_chars_after** – If given, the output string would be separated by line breaks after the given position.

- **content** – File content. Might contain dynamic elements, which are then replaced by correspondent fixtures.

Returns

Relative path (from root directory) of the generated file.

11.4.1.1.13 faker_file.providers.xlsx_file module

```
class faker_file.providers.xlsx_file.XlsxFileProvider(generator: Any)
    Bases: BaseProvider, FileMixin

    XLSX file provider.

    Usage example:

        from faker import Faker
        from faker_file.providers.xlsx_file import XlsxFileProvider
        file = XlsxFileProvider(Faker()).xlsx_file()

    Usage example with options:

        from faker import Faker
        from faker_file.providers.xlsx_file import XlsxFileProvider
        file = XlsxFileProvider(Faker()).xlsx_file(
            prefix="zzz", num_rows=100, data_columns={
                "name": "{name}", "residency": "{address}",
            }, include_row_ids=True,
        )
        extension: str = 'xlsx'

    xlsx_file(root_path: Optional[str] = None, rel_path: str = 'tmp', prefix: Optional[str] = None,
              data_columns: Optional[Dict[str, str]] = None, num_rows: int = 10, content: Optional[str] =
              None, **kwargs) → StringValue
```

Generate a XLSX file with random text.

Parameters

- **root_path** – Path of your files root directory (in case of Django it would be `settings.MEDIA_ROOT`).
- **rel_path** – Relative path (from root directory).
- **data_columns** – The `data_columns` argument expects a list or a tuple of string tokens, and these string tokens will be passed to `pystr_format()` for data generation. Argument Groups are used to pass arguments to the provider methods. Both `header` and `data_columns` must be of the same length.
- **num_rows** – The `num_rows` argument controls how many rows of data to generate, and the `include_row_ids` argument may be set to `True` to include a sequential row ID column.
- **prefix** – File name prefix.
- **content** – List of dicts with content (JSON-like format). If given, used as is.

Returns

Relative path (from root directory) of the generated file.

11.4.1.1.1.14 faker_file.providers.zip_file module

```
class faker_file.providers.zip_file.ZipFileProvider(generator: Any)
```

Bases: BaseProvider, [FileMixin](#)

ZIP file provider.

Usage example:

```
from faker import Faker from faker_file.providers.zip_file import ZipFileProvider

FAKER = Faker()

file = ZipFileProvider(FAKER).zip_file()
```

Usage example with options:

```
from faker_file.providers.zip_file import (
    ZipFileProvider, create_inner_docx_file
)

file = ZipFileProvider(FAKER).zip_file(
    prefix="zzz_archive_", options={
        "count": 5, "create_inner_file_func": create_inner_docx_file, "create_inner_file_args": [
            {
                "prefix": "zzz_docx_file_", "max_nb_chars": 1_024,
            }, {"directory": "zzz",
        }
    }
)
```

Usage example of nested ZIPs:

```
file = ZipFileProvider(FAKER).zip_file(
    options={
        "create_inner_file_func": create_inner_zip_file, "create_inner_file_args": {
            "options": {
                "create_inner_file_func": create_inner_docx_file,
            }
        }
    }
)
```

If you want to see, which files were included inside the zip, check the `file.data["files"]`.

extension: str = 'zip'

zip_file(root_path: Optional[str] = None, rel_path: str = 'tmp', prefix: Optional[str] = None, options: Optional[Dict[str, Any]] = None, **kwargs) → StringValue

Generate a ZIP file with random text.

Parameters

- **root_path** – Path of your files root directory (in case of Django it would be `settings.MEDIA_ROOT`).

- **rel_path** – Relative path (from root directory).
- **prefix** – File name prefix.
- **options** – Options (non-structured) for complex types, such as zip.

Returns

Relative path (from root directory) of the generated file.

```
faker_file.providers.zip_file.create_inner_bin_file(root_path: Optional[str] = None, rel_path: str = 'tmp', prefix: Optional[str] = None, generator: Optional[Union[Provider, Faker]] = None, length: int = 1048576, content: Optional[str] = None, **kwargs) → StringValue
```

Create inner BIN file.

```
faker_file.providers.zip_file.create_inner_csv_file(root_path: Optional[str] = None, rel_path: str = 'tmp', prefix: Optional[str] = None, generator: Optional[Union[Provider, Faker]] = None, header: Optional[Sequence[str]] = None, data_columns: Tuple[str, str] = ('{{name}}', '{{address}}'), num_rows: int = 10, include_row_ids: bool = False, content: Optional[str] = None, **kwargs) → StringValue
```

Create inner CSV file.

```
faker_file.providers.zip_file.create_inner_docx_file(root_path: Optional[str] = None, rel_path: str = 'tmp', prefix: Optional[str] = None, generator: Optional[Union[Provider, Faker]] = None, max_nb_chars: int = 10000, wrap_chars_after: Optional[int] = None, content: Optional[str] = None, **kwargs) → StringValue
```

Create inner DOCX file.

```
faker_file.providers.zip_file.create_inner_ico_file(root_path: Optional[str] = None, rel_path: str = 'tmp', prefix: Optional[str] = None, generator: Optional[Union[Provider, Faker]] = None, max_nb_chars: int = 5000, wrap_chars_after: Optional[int] = None, content: Optional[str] = None, **kwargs) → StringValue
```

Create inner ICO file.

```
faker_file.providers.zip_file.create_inner_jpeg_file(root_path: Optional[str] = None, rel_path: str = 'tmp', prefix: Optional[str] = None, generator: Optional[Union[Provider, Faker]] = None, max_nb_chars: int = 5000, wrap_chars_after: Optional[int] = None, content: Optional[str] = None, **kwargs) → StringValue
```

Create inner JPEG file.

```
faker_file.providers.zip_file.create_inner_ods_file(root_path: Optional[str] = None, rel_path: str = 'tmp', prefix: Optional[str] = None, generator: Optional[Union[Provider, Faker]] = None, data_columns: Optional[Dict[str, str]] = None, num_rows: int = 10, content: Optional[str] = None, **kwargs) → StringValue
```

Create inner ODS file.

```
faker_file.providers.zip_file.create_inner_pdf_file(root_path: Optional[str] = None, rel_path: str = 'tmp', prefix: Optional[str] = None, generator: Optional[Union[Provider, Faker]] = None, max_nb_chars: int = 10000, wrap_chars_after: Optional[int] = None, content: Optional[str] = None, **kwargs) → StringValue
```

Create inner PDF file.

```
faker_file.providers.zip_file.create_inner_png_file(root_path: Optional[str] = None, rel_path: str = 'tmp', prefix: Optional[str] = None, generator: Optional[Union[Provider, Faker]] = None, max_nb_chars: int = 5000, wrap_chars_after: Optional[int] = None, content: Optional[str] = None, **kwargs) → StringValue
```

Create inner PNG file.

```
faker_file.providers.zip_file.create_inner_pptx_file(root_path: Optional[str] = None, rel_path: str = 'tmp', prefix: Optional[str] = None, generator: Optional[Union[Provider, Faker]] = None, max_nb_chars: int = 10000, wrap_chars_after: Optional[int] = None, content: Optional[str] = None, **kwargs) → StringValue
```

Create inner PPTX file.

```
faker_file.providers.zip_file.create_inner_svg_file(root_path: Optional[str] = None, rel_path: str = 'tmp', prefix: Optional[str] = None, generator: Optional[Union[Provider, Faker]] = None, max_nb_chars: int = 5000, wrap_chars_after: Optional[int] = None, content: Optional[str] = None, **kwargs) → StringValue
```

Create inner SVG file.

```
faker_file.providers.zip_file.create_inner_txt_file(root_path: Optional[str] = None, rel_path: str = 'tmp', prefix: Optional[str] = None, generator: Optional[Union[Provider, Faker]] = None, max_nb_chars: int = 10000, wrap_chars_after: Optional[int] = None, content: Optional[str] = None, **kwargs) → StringValue
```

```
faker_file.providers.zip_file.create_inner_webp_file(root_path: Optional[str] = None, rel_path: str = 'tmp', prefix: Optional[str] = None, generator: Optional[Union[Provider, Faker]] = None, max_nb_chars: int = 5000, wrap_chars_after: Optional[int] = None, content: Optional[str] = None, **kwargs) → StringValue
```

Create inner WEBP file.

```
faker_file.providers.zip_file.create_inner_xlsx_file(root_path: Optional[str] = None, rel_path: str = 'tmp', prefix: Optional[str] = None, generator: Optional[Union[Provider, Faker]] = None, data_columns: Optional[Dict[str, str]] = None, num_rows: int = 10, content: Optional[str] = None, **kwargs) → StringValue
```

Create inner XLSX file.

```
faker_file.providers.zip_file.create_inner_zip_file(root_path: Optional[str] = None, rel_path: str = 'tmp', prefix: Optional[str] = None, generator: Optional[Union[Provider, Faker]] = None, options: Optional[Dict[str, Any]] = None, **kwargs) → StringValue
```

Create inner ZIP file.

11.4.1.1.1.15 Module contents

11.4.1.1.2 faker_file.tests package

11.4.1.1.2.1 Submodules

11.4.1.1.2.2 faker_file.tests.test_django_integration module

```
class faker_file.tests.test_django_integration.DjangoIntegrationTestCase(methodName='runTest')  
    Bases: TestCase  
    Django integration test case.  
FAKER: Faker  
test_file
```

11.4.1.1.2.3 faker_file.tests.test_providers module

```
class faker_file.tests.test_providers.ProvidersTestCase(methodName='runTest')  
    Bases: TestCase  
    Providers test case.  
FAKER: Faker  
test_broken_imports  
test_faker  
test_standalone_providers  
test_standalone_providers_allow_failures  
test_standalone_zip_file  
test_standalone_zip_file_allow_failures
```

11.4.1.1.2.4 Module contents

11.4.1.2 Submodules

11.4.1.3 faker_file.base module

```
class faker_file.base.FileMixin
    Bases: object
        File mixin.

    extension: str
    formats: List[str]
    generator: Union[Provider, Faker]
    numerify: Callable
    random_element: Callable

class faker_file.base.StringValue
    Bases: str
    data: Dict[str, Any] = {}
```

11.4.1.4 faker_file.constants module

11.4.1.5 faker_file.helpers module

```
faker_file.helpers.wrap_text(text: str, wrap_chars_after: int) → str
```

11.4.1.6 Module contents

CHAPTER
TWELVE

INDICES AND TABLES

- genindex
- modindex
- search

PYTHON MODULE INDEX

f

`faker_file`, 48
`faker_file.base`, 48
`faker_file.constants`, 48
`faker_file.helpers`, 48
`faker_file.providers`, 47
`faker_file.providers.bin_file`, 34
`faker_file.providers.csv_file`, 35
`faker_file.providers.docx_file`, 36
`faker_file.providers.ico_file`, 36
`faker_file.providers.jpeg_file`, 37
`faker_file.providers.pdf_file`, 38
`faker_file.providers.png_file`, 39
`faker_file.providers.pptx_file`, 40
`faker_file.providers.svg_file`, 40
`faker_file.providers.txt_file`, 41
`faker_file.providers.webp_file`, 42
`faker_file.providers.xlsx_file`, 43
`faker_file.providers.zip_file`, 44
`faker_file.tests`, 48
`faker_file.tests.test_django_integration`, 47
`faker_file.tests.test_providers`, 47

INDEX

B

`bin_file()` (*faker_file.providers.bin_file.BinFileProvider method*), 34
`BinFileProvider` (class *faker_file.providers.bin_file*), 34

C

`create_inner_bin_file()` (in *faker_file.providers.zip_file*), 45
`create_inner_csv_file()` (in *faker_file.providers.zip_file*), 45
`create_inner_docx_file()` (in *faker_file.providers.zip_file*), 45
`create_inner_ico_file()` (in *faker_file.providers.zip_file*), 45
`create_inner_jpeg_file()` (in *faker_file.providers.zip_file*), 45
`create_inner_ods_file()` (in *faker_file.providers.zip_file*), 45
`create_inner_pdf_file()` (in *faker_file.providers.zip_file*), 46
`create_inner_png_file()` (in *faker_file.providers.zip_file*), 46
`create_inner_pptx_file()` (in *faker_file.providers.zip_file*), 46
`create_inner_svg_file()` (in *faker_file.providers.zip_file*), 46
`create_inner_txt_file()` (in *faker_file.providers.zip_file*), 46
`create_inner_webp_file()` (in *faker_file.providers.zip_file*), 46
`create_inner_xlsx_file()` (in *faker_file.providers.zip_file*), 46
`create_inner_zip_file()` (in *faker_file.providers.zip_file*), 47
`csv_file()` (*faker_file.providers.csv_file.CsvFileProvider method*), 35
`CsvFileProvider` (class *faker_file.providers.csv_file*), 35

D

`data` (*faker_file.base.StringValue attribute*), 48

`DjangoIntegrationTestCase` (class *faker_file.tests.test_django_integration*), 47
`in docx_file()` (*faker_file.providers.docx_file.DocxFileProvider method*), 36
`DocxFileProvider` (class *faker_file.providers.docx_file*), 36
`module extension` (*faker_file.base.FileMixin attribute*), 48
`module extension` (*faker_file.providers.bin_file.BinFileProvider attribute*), 34
`module extension` (*faker_file.providers.csv_file.CsvFileProvider attribute*), 35
`module extension` (*faker_file.providers.docx_file.DocxFileProvider attribute*), 36
`module extension` (*faker_file.providers.ico_file.IcoFileProvider attribute*), 37
`module extension` (*faker_file.providers.jpeg_file.JpegFileProvider attribute*), 37
`module extension` (*faker_file.providers.pdf_file.PdfFileProvider attribute*), 38
`module extension` (*faker_file.providers.png_file.PngFileProvider attribute*), 39
`module extension` (*faker_file.providers.pptx_file.PptxFileProvider attribute*), 40
`module extension` (*faker_file.providers.svg_file.SvgFileProvider attribute*), 41
`module extension` (*faker_file.providers.txt_file.TxtFileProvider attribute*), 41
`module extension` (*faker_file.providers.webp_file.WebpFileProvider attribute*), 42
`module extension` (*faker_file.providers.xlsx_file.XlsxFileProvider attribute*), 43
`module extension` (*faker_file.providers.zip_file.ZipFileProvider attribute*), 44

F

`FAKER` (*faker_file.tests.test_django_integration.DjangoIntegrationTestCase attribute*), 47
`FAKER` (*faker_file.tests.test_providers.ProvidersTestCase attribute*), 47

faker_file
 module, 48
faker_file.base
 module, 48
faker_file.constants
 module, 48
faker_file.helpers
 module, 48
faker_file.providers
 module, 47
faker_file.providers.bin_file
 module, 34
faker_file.providers.csv_file
 module, 35
faker_file.providers.docx_file
 module, 36
faker_file.providers.ico_file
 module, 36
faker_file.providers.jpeg_file
 module, 37
faker_file.providers.pdf_file
 module, 38
faker_file.providers.png_file
 module, 39
faker_file.providers.pptx_file
 module, 40
faker_file.providers.svg_file
 module, 40
faker_file.providers.txt_file
 module, 41
faker_file.providers.webp_file
 module, 42
faker_file.providers.xlsx_file
 module, 43
faker_file.providers.zip_file
 module, 44
faker_file.tests
 module, 48
faker_file.tests.test_django_integration
 module, 47
faker_file.tests.test_providers
 module, 47
FileMixin (class in faker_file.base), 48
formats (faker_file.base.FileMixin attribute), 48

G

generator (faker_file.base.FileMixin attribute), 48

I

ico_file() (faker_file.providers.ico_file.IcoFileProvider
 method), 37

IcoFileProvider (class
 in faker_file.providers.ico_file), 36

J

jpeg_file() (faker_file.providers.jpeg_file.JpegFileProvider
 method), 37
JpegFileProvider (class
 in faker_file.providers.jpeg_file), 37

M

module
 faker_file, 48
 faker_file.base, 48
 faker_file.constants, 48
 faker_file.helpers, 48
 faker_file.providers, 47
 faker_file.providers.bin_file, 34
 faker_file.providers.csv_file, 35
 faker_file.providers.docx_file, 36
 faker_file.providers.ico_file, 36
 faker_file.providers.jpeg_file, 37
 faker_file.providers.pdf_file, 38
 faker_file.providers.png_file, 39
 faker_file.providers.pptx_file, 40
 faker_file.providers.svg_file, 40
 faker_file.providers.txt_file, 41
 faker_file.providers.webp_file, 42
 faker_file.providers.xlsx_file, 43
 faker_file.providers.zip_file, 44
 faker_file.tests, 48
 faker_file.tests.test_django_integration,
 47
 faker_file.tests.test_providers, 47

N

numerify (faker_file.base.FileMixin attribute), 48

P

pdf_file() (faker_file.providers.pdf_file.PdfFileProvider
 method), 38
PdfFileProvider (class
 in faker_file.providers.pdf_file), 38
png_file() (faker_file.providers.png_file.PngFileProvider
 method), 39
PngFileProvider (class
 in faker_file.providers.png_file), 39
pptx_file() (faker_file.providers.pptx_file.PptxFileProvider
 method), 40
PptxFileProvider (class
 in faker_file.providers.pptx_file), 40
ProvidersTestCase (class
 in faker_file.tests.test_providers), 47

R

random_element (faker_file.base.FileMixin attribute),
 48

S

`StringValue` (*class in faker_file.base*), 48
`svg_file()` (*faker_file.providers.svg_file.SvgFileProvider method*), 41
`SvgFileProvider` (*class in faker_file.providers.svg_file*), 40

T

`test_broken_imports`
 (*faker_file.tests.test_providers.ProvidersTestCase attribute*), 47
`test_faker` (*faker_file.tests.test_providers.ProvidersTestCase attribute*), 47
`test_file` (*faker_file.tests.test_django_integration.DjangoIntegrationTestCase attribute*), 47
`test_standalone_providers`
 (*faker_file.tests.test_providers.ProvidersTestCase attribute*), 47
`test_standalone_PROVIDERS_allow_failures`
 (*faker_file.tests.test_providers.ProvidersTestCase attribute*), 47
`test_standalone_zip_file`
 (*faker_file.tests.test_providers.ProvidersTestCase attribute*), 47
`test_standalone_zip_file_ALLOW_FAILURES`
 (*faker_file.tests.test_providers.ProvidersTestCase attribute*), 47
`txt_file()` (*faker_file.providers.txt_file.TxtFileProvider method*), 41
`TxtFileProvider` (*class in faker_file.providers.txt_file*), 41

W

`webp_file()` (*faker_file.providers.webp_file.WebpFileProvider method*), 42
`WebpFileProvider` (*class in faker_file.providers.webp_file*), 42
`wrap_text()` (*in module faker_file.helpers*), 48

X

`xlsx_file()` (*faker_file.providers.xlsx_file.XlsxFileProvider method*), 43
`XlsxFileProvider` (*class in faker_file.providers.xlsx_file*), 43

Z

`zip_file()` (*faker_file.providers.zip_file.ZipFileProvider method*), 44
`ZipFileProvider` (*class in faker_file.providers.zip_file*), 44